



500L SPECIFICATIONS

2015 Fiat 500L SPECIFICATIONS

Dimensions are in inches (millimeters) unless otherwise noted.

GENERAL INFORMATION

Vehicle Type	B-segment multipurpose vehicle (MPV)
EPA Vehicle Class	Small Station Wagon
Assembly Plant	Kragujevac, Serbia
Introduction Date	Mid-2013 as a 2014 model

BODY/CHASSIS

Layout	Transverse-mounted front engine, front-wheel drive
Construction	Unitized steel body

ENGINE: 1.4-LITER SOHC 16-VALVE TURBOCHARGED MULTIAIR INLINE FOUR-CYLINDER

Availability	Standard — 500L Pop, Easy, Trekking and Lounge models
Type and Description	Inline four-cylinder, liquid-cooled, turbocharged
Displacement	83.48 cu. in. (1,368 cu. cm)
Bore x Stroke	2.83 x 3.31 (72 x 84)
Valve System	Belt-driven, MultiAir, SOHC, 16 valves, hydraulic end-pivot roller rockers
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	Cast-iron block with aluminum-alloy head and aluminum-alloy bedplate
Compression Ratio	9.8:1
Maximum Turbo Boost (psi / bar)	21 psi / 1.45 bar
Power (SAE)	160 bhp (119 kW) @ 5,500 rpm (117 bhp/liter)
Torque (SAE)	184 lb.-ft. (250 N•m) @ 2,500-4,000 rpm
Max. Engine Speed	6,500 rpm (electronically limited)
Fuel Requirement	87 octane (R+M)/2 acceptable 91 octane recommended
Oil Capacity	4.0 qt. (3.8 liter) with dry filter
Coolant Capacity	4.6 qt. (14.4 liter)
Emission Controls	Dual three-way catalytic converters, heated oxygen sensors and internal engine features ^(a)
Max. Gross Trailer Weight	Not rated for trailer tow



500L SPECIFICATIONS

Estimated EPA Fuel Economy mpg (city/highway/combined)	25 / 33 / 28 with six-speed manual transmission
	24 / 33 / 27 with Euro Twin Clutch six-speed transmission
	22 / 30 / 25 with six-speed automatic transmission

Engine Assembly Plant	Termoli, Italy
-----------------------	----------------

(a) Meets Federal Tier 2 Bin 5 emission requirements and LEV II requirements in California, Massachusetts, New York, Maine, Vermont, Connecticut, Pennsylvania, Rhode Island, New Jersey, Oregon and Washington.

C635 SIX-SPEED MANUAL TRANSMISSION

Availability	Standard on 500L Pop, Easy and Trekking
Description	1st, 2nd gear: Double Cone 3rd, 4th, 5th, 6th gear: Single Cone
Gear Ratios	
1st	4.154
2nd	2.118
3rd	1.361
4th	0.978
5th	0.756
6th	0.622
Reverse	4.00
Final-drive Ratio	3.833
Overall Top Gear	2.38

C635 EURO TWIN CLUTCH SIX-SPEED TRANSMISSION

Availability	Optional on 500L Pop
Description	1st, 2nd gear: Double Cone 3rd, 4th, 5th, 6th gear: Single Cone
Gear Ratios	
1st	4.154
2nd	2.269
3rd	1.435
4th	0.978
5th	0.755
6th	0.622
Reverse	4.00
Final-drive Ratio	4.118
Overall Top Gear	2.56



500L SPECIFICATIONS

AISIN SIX-SPEED AUTOMATIC TRANSMISSION

Availability	Optional on 500L Easy and Trekking Standard on 500L Lounge
Gear Ratios	
1st	4.04
2nd	2.37
3rd	1.56
4th	1.16
5th	0.85
6th	0.67
Reverse	3.19
Final-drive Ratio	3.683
Overall Top Gear	2.47
Steering Turns (lock-to-lock)	3.0

BRAKES

Availability	Standard on all 500L models
Front	
Rotor size and type	12.0 x 1.10 (305 x 28) vented
Caliper size and type	2.24 (57) single-piston with cast iron
Swept area	345 sq. in. (876.1 sq. cm)
Rear	
Rotor size and type	10.4 x 0.4 (264 x 10) solid
Caliper size and type	1.49 (38) single-piston with aluminum housing
Swept area	233 sq. in. (591.8 sq. cm)

DIMENSIONS AND CAPACITIES^(a)

Wheelbase	102.8 (2,612)
Track, Front	59.1 (1,502)
Track, Rear	59.4 (1,510)
Overall Length	167.3 (4,249) 168.1 (4,270) — 500L Trekking
Overall Width	69.8 (1,774) — without mirrors 80.2 (2,036) — with mirrors 70.9 (1,800) — 500L Trekking
Overall Height	65.7 (1,670)



500L SPECIFICATIONS

Ground Clearance	4.7 (120)
Drag Coefficient (Cd) (estimated)	0.310 — 500L Pop/Easy/Lounge 0.320 — 500L Trekking
Curb Weight, lb. (kg) (estimated)	3,212 (1,457) — 500L with six-speed manual 3,262 (1,479) — 500L with six-speed Euro Twin Clutch 3,254 (1,476) — 500L with six-speed automatic
Weight Distribution, percent F/R	60/40 — 500L with six-speed manual 60/40 — 500L with six-speed Euro Twin Clutch 60/40 — 500L with six-speed automatic
Fuel Tank Capacity, gal. (liter)	13.2 (50)

(a) All dimensions measured at curb weight with standard tires.

ACCOMMODATIONS

Seating Capacity, F/R	2/3
Front Seat	
Head room	40.7 (1,034) 40.5 (1,028) with dual-pane sunroof
Legroom	40.0 (1,015)
Shoulder room	57.3 (1,456)
Hip room	54.9 (1,394)
Total seat travel	8.3 (210) — driver 9.0 (230) — passenger
EPA front row interior volume	54.0 cu. ft. (1.529 cu. m)
Rear Seat	
Head room	38.7 (983) 38.0 (966) with dual-pane sunroof
Legroom	36.7 (931)
Shoulder room	54.6 (1,388)
Hip room	49.4 (1,256)
Total seat travel	4.7 (120)
EPA second row interior volume	44.8 cu. ft. (1.268 cu. m)
Total Interior Volume	98.8 cu. ft. (2.797 cu. m)
EPA Luggage Compartment Volume	22.4 cu. ft. (0.633 cu. m)
EPA Volume behind front row (maximum cargo)	68.0 cu. ft. (1.927 cu. m)
EPA Interior Volume Index	121.1 cu. ft. (3.430 cu. m)
Trunk Liftover Height	25.9 (657)



500L SPECIFICATIONS

TIRES

Availability	Standard on 500L Pop, Easy and Lounge
Size and Type	205/55R16 BSW All-season
Mfr. and Model	Continental Conti ProContact or Goodyear Eagle LS2 or Nexen CP671 Classe Premiere
Revs per mile (km)	836 (519)
Availability	Standard on 500L Trekking Included with 17-in. wheels on 500L Lounge
Size and Type	225/45R17 BSW All-Season
Mfr. and Model	Continental Conti ProContact or Goodyear Eagle LS2 or Nexen CP671 Classe Premiere
Revs per mile (km)	832 (517)

WHEELS

Availability	Standard on 500L Easy and 500L Lounge
Type and Material	Cast-aluminum, 13-spoke radial design, fully painted Argento
Size	16 x 6.5-in.
Availability	Optional on 500L Lounge
Type and Material	Cast-aluminum, seven-spoke, oval-twist design, painted Argento with Grigio (gray) pockets
Size	16 x 6.5-in.
Availability	Standard on 500L Trekking
Type and Material	Cast-aluminum, seven-hole design, machined face with painted Grigio pockets
Size	17 x 7.0-in.
Availability	Optional on 500L Lounge and 500L Trekking
Type and Material	Cast-aluminum, five-oval design, painted Argento with Grigio pockets
Size	17 x 7.0-in.
Availability	Optional on 500L Lounge
Type and Material	Cast-aluminum, seven-spoke, dual-twist design, painted Argento with Nero (black) pockets (must have optional Nero painted roof)
Size	17 x 7.0-in.



500L

SPECIFICATIONS

Availability	Optional on 500L Lounge
Type and Material	Cast-aluminum, seven-spoke, dual-twist design, painted Argento with Bianco (white) pockets (must have optional Bianco painted roof)
Size	17 x 7.0-in.

