



RAM

2016 RAM PROMASTER CITY TOWING CHART

2016 RAM - Promaster City - Trailer Towing Chart - SAE J2807 compliant												
Engine	Transmission	Mkt	Axle Ratio	GVWR	Payload ¹	Base Weight			GAWR		GCWR ²	Max. Trailer Weight Rating ³
						Total	Front	Rear	Front	Rear		
RAM Promaster City												
2.4L I4 GASOLINE MULTIAIR ENGINE	9-SPD AUTO 948TE	USA	3.73	5,395	1,883	3,512	2,213	1,299	2,690	2,866	5,900	2,000
2.4L I4 GASOLINE MULTIAIR ENGINE	9-SPD AUTO 948TE	CAN	3.73	5,395	1,900	3,495	2,209	1,286	2,690	2,866	5,900	2,000

- 1 Payload and Max Trailer weights are ESTIMATED values.
- 2 All values are shown in pounds unless otherwise stated
- 3 (1) Payload. (Payload = GVWR - Base Weight)
- 4 (2) GCWR is a defined valude from Chrysler Vehicle Engineering in lbs (max GCWR = 5,900 lbs)
- 5 (3) Max Trailer weight is limited to 2,000 lbs.
- 6 Payload and Maximum Trailer weight are mutually exclusive.
- 7 Trailer Weight Rating and Tow Vehicle Trailing Weight are calculated as specified in SAE J2807.
Driver and passenger Weight = 300lb
Trailing Equipment Weight: 50.7 lb for Convencional Hitch.
- 8 The recommended tongue weight is 10% of trailer weight.
- 9 Hitch rating, GAWRs, and GCWR should never be exceeded.