

2015 Chrysler 200

CANADIAN SPECIFICATIONS

*NOTE: The information shown is preliminary and based on data available at the time of publication and is subject to change
All dimensions are in millimetres (inches) unless otherwise noted.
All dimensions are measured at curb weight with standard wheels and tires unless otherwise noted.*

GENERAL INFORMATION

Body Style	Four-door sedan
Assembly Plant	Sterling Heights Assembly, Mich.(U.S.A.)
EnerGuideVehicle Class	Mid-size sedan
Introduction Date	Spring 2014

BODY/CHASSIS

Layout	Transverse front engine with front-wheel drive (FWD) or all-wheel drive (AWD)
Construction	Steel uni-frame

ENGINE: 2.4-LITRE, I-4, MULTIAIR TIGERSHARK, 16-VALVE, GASOLINE, SOHC

Availability	Standard on all models
Type and Description	Four-cylinder inline, 16-valve MultiAir with multiport fuel injection
Displacement	2,360 cu. cm (144 cu. in.)
Bore x Stroke	88 x 97 (3.46 x 3.82)
Valve System	SOHC, 16 valves (4 valves per cylinder)
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	High-pressure die-cast aluminum block with dry iron liners, cast-aluminum cylinder heads, cast-aluminum ladder frame, forged-steel crankshaft
Compression	10.0:1
Power	184 hp @ 6,250 rpm (preliminary)
Torque	173 lb.-ft. @ 4,600 rpm (preliminary)
Max. Engine Speed	6,500 rpm (electronically limited)
Fuel Requirement	Unleaded regular, 87 octane
Oil Capacity	5.2 litre (5.5 qt.)
Coolant Capacity	6.7 litre (7.1 qt.)
Emission Controls	GPEC3 engine-management system with close-coupled catalyst; and wide range O ² sensor
Engine Assembly Plant	Dundee Engine Plant, Dundee, Mich.(U.S.A.)
Estimated EnerGuideFuel Economy, L/100 km (mpg) (city/hwy/combined)	TBA

ENGINE: 3.6-LITRE PENTASTAR V6, DOHC GASOLINE, 24-VALVE, VVT

Availability	Available on 200 Limited, 200S, and 200C models; Standard on AWD models
Type and Description	60-degree bank angle, liquid-cooled, three-plenum intake manifold with electronically controlled manifold tuning valve and short-runner valves
Displacement	3,605 cu. cm (220 cu. in.)
Bore x Stroke	96 x 83 mm (3.78 x 3.27)
Valve System	Chain-drive DOHC, 24 valves (4 valves per cylinder), hydraulic end-pilot roller rockers, variable cam phasing on intake and exhaust cams
Fuel Injection	Sequential, multiport, electronic
Construction	High-pressure die-cast A380 aluminum block with iron liners and semi-permanent mould A319 aluminum heads
Compression Ratio	10.2:1
Power	295 bhp @ 6,350 rpm
Torque	262 lb.-ft. @ 4,250 rpm
Max. Engine Speed	6,400 rpm (electronically limited)
Fuel Requirement	Unleaded regular, 87 octane (R+M)/2
Oil Capacity	5.7 litre (6 qt.) with dry filter SAE 5W30
Coolant Capacity	8.12 litre (8.58 qt.)
Emission Controls	Integrated cast-aluminum header manifolds; positive crankcase ventilation; inlet and exhaust cam phasers with internal exhaust gas recirculation (no EGR/AIR required); evaporative emissions system
Estimated EnerGuide Fuel Economy, L/100 km (mpg) (city/hwy/combined)	TBA
Engine Assembly Plant	Trenton Engine Plant, Trenton, Mich. (U.S.A.)

TRANSMISSION: 948TE/9HP48, AUTOMATIC NINE-SPEED

Availability	Standard on all models
Description	Nine-speed FWD/AWD, electronically controlled automatic overdrive transmission with torque converter clutch. Clutch-to-clutch architecture, with integral electro/hydraulic controls module
Gear Ratios	
1st	4.71
2 nd	2.84
3 rd	1.91
4 th	1.38
5 th	1.00
6 th	0.81

7 th	0.70
8 th	0.58
9 th	0.48
Reverse	3.81
Spread	9.81
Final Drive Ratio – 948TE	3.73 with 2.4-litre engine
Final Drive Ratio – 9HP48	3.52 with 3.6-litre engine

SUSPENSION

Front	MacPherson strut, dual reacting twin tube shock absorbers
Rear	Multi-link independent dual reacting twin tube shock absorbers

STEERING

Type	Electric power rack and pinion
Overall Ratio	15:2 (FWD and AWD)
Turning Diameter (curb-to-curb)	FWD: 11.94 m (39.2 ft.) , AWD: 12.03 m (39.5 ft.)
Steering Turns (lock-to-lock)	2.67

BRAKES

mm (in.) unless otherwise noted

Power-assist Type	Vacuum assist
Availability	Standard on all models
Front	
Size and Type	2.4-litre: (305 x 28) rotors with (60.0) single-piston iron caliper 3.6-litre: (330 x 28) rotors with (60.0) single-piston iron caliper
Swept Area (Total Front)	2.4-litre: 394.1 sq. cm (61.1 sq. in.) 3.6-litre: 436.8 sq. cm (67.7 sq. in.)
Rear	
Size and Type	(278 x 12) rotors with (38.0) single-piston aluminum caliper
Swept Area (Total Rear)	638.6 sq. cm (98.98 sq. in.)
Parking Brake Type	Electronic Park Brake
Anti-lock Brake System (ABS)	Standard
Electronic Stability Control (ESC)	Standard
Traction Control	Standard
Brake Assist	Standard

DIMENSIONS AND CAPACITIES**mm (in.) unless otherwise noted**

Wheelbase	2,742.0 (108.0)
Track, Front	1,577.8 (62.1)
Track, Rear	1,575.6 (62.0)
Overall Length	4,884.7 (192.3)
Overall Width	1,871 (73.6)
Overall Height	1,491 (58.7)
Front Overhang	1,039 (40.9)
Rear Overhang	1,103 (43.4)
Approach Angle (Deg.)	13.5
Departure Angle (Deg.)	17.8
Ground Clearance	3.6-litre FWD with 17-in. Tire (lowest available): 147mm
Aero	
Cd	0.270
Fuel Tank Capacity, litre (gal.)	59.8 (15.8)
Towing Capabilities, NAFTA Markets kg (lbs.)	No Trailer Tow Recommended
Curb Weight, Base Vehicle, kg (lbs.)	1,575 (3,473)
GVWR (Base vehicle)	2,092 (4,612)

ACCOMMODATIONS**mm (in.) unless otherwise noted**

Seating Capacity - F/R	2/3
Total Interior Passenger Volume,	2,871 litres (101.4 cu.ft.)
Front	
Head Room	982 (37.7)
Legroom	1,071 (42.2)
Shoulder Room	1,485 (58.5)
Hip Room	1,384 (54.5)
Seat Travel	210
Front Compartment Volume	1,666 litres (55.3 cu.ft.)
Rear	
Head Room	950 (37.4)
Legroom	956 (37.6)

Shoulder Room	1,441 (56.7)
Hip Room	1,338 (52.7)
Knee Clearance	71.3
Rear Compartment Volume Index	1,305 litres (46.1 cu. ft.)
Cargo	
Trunk Lift-over Height	726
Trunk Volume	453 litres (16 cu. ft.)
Interior Volume	3,282 litres (115.9 cu. ft.)
Passenger Volume	2,871 litres (101.4 cu. ft.)

WHEELS

Availability	200 LX
Type and Material	Steel with cover
Size	17 in. x 7.0 in.
Availability	200 Limited
Type and Material	Cast Aluminum, Painted-Tech Silver - Standard Cast Aluminum, Painted - Available
Size	17 in. x 7.5 in. - Standard 18 in. x 8.0 in. - Available
Availability	200S
Type and Material	Cast Aluminum, Painted-Satin Carbon - Standard Cast Aluminum, Painted-Hyper Black - Available
Size	18 in. x 8.0 in. - Standard 19 in. x 8.0 in. - Available
Availability	200C
Type and Material	Cast Aluminum, Painted-Satin Silver – Standard FWD Cast Aluminum, Polished-Satin Clear – Standard AWD Cast Aluminum, Polished Face-Painted Pockets – Available FWD & AWD
Size	17 in. x 7.5 in. – Standard FWD 18 in. x 8.0 in. – Standard AWD 19 in. x 8.0 in. – Available FWD & AWD

TIRES

Availability	200 LX
Size and Type (Revs per kilometre)	Bridgestone 215/55R17 (787) Nexen 215/55R17 (793) Goodyear 215/55R17 (790)
Availability	200 Limited
Size and Type (Revs per kilometre)	Bridgestone 215/55R17 (787) Nexen 215/55R17 (793) Goodyear 215/55R17 (790) Bridgestone 235/45R18 (796) Nexen 235/45R18 (792) Kuhmo 235/45R18 (793)
Availability	200S
Size and Type (Revs per kilometre)	Bridgestone 235/45R18 (797) Kuhmo 235/45R18 (793) Nexen 235/45R18 (792) Nexen 235/40R19 (789)
Availability	200C
Size and Type (Revs per kilometre)	Bridgestone 215/55R17 (789) Nexen 215/55R17 (793) Goodyear 215/55R17 (790) Bridgestone 235/45R18 (797) Nexen 235/45R18 (792) Kuhmo 235/45R18 (793) Nexen 235/40R19 (789)

