



2017 JEEP® COMPASS SPECIFICATIONS



2017 Jeep® Compass SPECIFICATIONS

EMBARGO DATE: 12:01 a.m. September 1, 2016

Specifications are for U.S. models only and are based on the latest product information available at the time of publication. All dimensions are in inches (millimeters) at curb weight and with standard wheels and tires unless otherwise noted. Note: Information shown is correct at time of publication, and is subject to change without notice.

GENERAL INFORMATION

Body Style	Sport-utility vehicle (SUV)
Assembly Plant	Belvidere, Ill.
EPA Vehicle Class	Compact SUV
Introduction Date	August 2006

BODY AND CHASSIS

Layout	Transverse front-engine, front-wheel drive or four-wheel drive
Construction	Unitized steel body

ENGINE: 2.0-LITER I-4 WORLD GAS ENGINE

Availability	Standard — Sport and Latitude 4x2 models
Type and Description	Four-cylinder inline, tuned intake manifold with electronic active charge motion control valves, dual counter-rotating balance shafts
Displacement	121.9 cu. in. (1,998 cu. cm)
Bore x Stroke	3.39 x 3.39 (86 x 86)
Valve System	Chain-driven DOHC, 16 valves, electronically-controlled dual variable-valve timing (VVT), direct-acting shimless mechanical bucket tappets
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	High-pressure die-cast aluminum block with dry iron liners, cast-aluminum cylinder head, cast-aluminum ladder frame, forged-steel crankshaft
Compression Ratio	10.5:1
Power (SAE net, estimated)	158 bhp (117 kW) @ 6,400 rpm (79 bhp/liter)
Torque (SAE net, estimated)	141 lb.-ft. (191 N•m) @ 5,000 rpm
Maximum Engine Speed	6,750 rpm (electronically limited)



2017 JEEP® COMPASS
SPECIFICATIONS



Fuel Requirement	Unleaded regular, 87 octane (R+M)/2
Oil Capacity	5.0 quarts (4.7 liters) SAE 5W/20
Coolant Capacity	7.2 quarts (6.8 liters)
Emission Controls	Single catalytic converter, dual heated oxygen sensors and engine features
Smog-forming Pollution	0.9 g/mile (0.56 g/km) ^(a)
EPA Fuel Economy mpg (city/highway/combined)	23/30/25 — 2WD with five-speed manual transaxle 22/26/24 — 2WD with continuously-variable transmission II (CVT2) automatic transmission

^(a) 2.0L CVT FWD = 50 state BIN 4

ENGINE: 2.4-LITER I-4 WORLD GAS ENGINE

Availability	Standard — Sport and Latitude 4x4 models Available — Sport and Latitude 4x2 models
Type and Description	Four-cylinder inline, tuned intake manifold with electronic active charge motion control valves dual counter-rotating balance shafts
Displacement	144 cu. in. (2,360 cu. cm)
Bore x Stroke	3.46 x 3.82 (88 x 97)
Valve System	Chain-driven DOHC, 16 valves, electronically-controlled dual VVT, direct-acting shimless mechanical bucket tappets
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	High-pressure die-cast aluminum block with dry iron liners, cast-aluminum cylinder head, cast-aluminum ladder frame, forged-steel crankshaft
Compression Ratio	10.5:1
Power (SAE net, estimated)	172 bhp (129 kW) @ 6,000 rpm (72 bhp/liter)
Torque (SAE net, estimated)	165 lb.-ft. (224 N•m) @ 4,400 rpm
Maximum Engine Speed	6,500 rpm (electronically limited)
Fuel Requirement	Unleaded regular, 87 octane (R+M)/2
Oil Capacity	5.0 quarts (4.7 liters) SAE 5W/20
Coolant Capacity	7.2 quarts (6.8 liters)
Emission Controls	Single catalytic converter, 2WD, dual catalytic converter, 4WD dual heated oxygen sensors and engine features
Smog-forming Pollution	0.9 g/mile (0.56 g/km) ^(b)



2017 JEEP® COMPASS
SPECIFICATIONS



Maximum Gross Trailer Weight	1,000 lbs. (450 kg) 2,000 lbs. (900 kg) — with Trailer-tow Prep Group
EPA Fuel Economy mpg (city/highway/combined)	23/28/25 — 2WD with five-speed manual transaxle 21/27/23 — 2WD with six-speed automatic transmission 22/27/24 — 4WD with five-speed manual transaxle 20/25/22 — Freedom Drive I 4WD with six-speed automatic transmission 20/23/21 — Freedom Drive II Off-road Package 4WD with CVT2L

^(b) 2.4L A6 FWD = 50 State BIN 4, 2.4L A6/CVTL 4WD = 50 State BIN 4, 2.4L M5 FWD/4WD = 50 State BIN 5/LEV II

TRANSAXLE: MANUAL MAGNA DRIVELINE T355 FIVE-SPEED

Availability	Standard — 2.0-liter engine
Description	Five-speed, overdrive, synchronized in all forward ratios, cable-operated, three-plane shifter
Gear Ratios	
1st	3.77
2nd	2.16
3rd	1.41
4th	1.026
5th	0.72
Reverse	3.417
Final-drive Ratio	4.12
Overall Top-gear	2.97

TRANSAXLE: AUTOMATIC 6F24 SIX-SPEED POWERTECH WITH AUTO STICK

Availability	Optional — 2.4-liter engine (FWD and 4x4) Sport and Latitude models
Description	Six-speed automatic transmission, lockup torque converter, electronic controls
Gear Ratios	
1st	4.212
2nd	2.637
3rd	1.800



2017 JEEP® COMPASS SPECIFICATIONS

17

4th	1.386
5th	1.000
6th	0.772
Reverse	3.285
Final-drive Ratio	3.367:1 (2.4-liter engine)
Overall Top-gear Ratio	2.600 (2.4-liter engine)
Auto Stick	Standard with 6F24

TRANSAXLE: AUTOMATIC JATCO MODEL Continuously-Variable Transmission II (CVT2)

Availability	Standard — 2.4-liter engine Optional — 2.0-liter engine
Description	Continuously-variable ratio, lockup torque converter, electronic controls
Gear Ratios	
Forward	2.349:1 to 0.394:1 continuously variable
Reverse	1.75:1
Final-drive Ratio	6.12:1
Overall Top-gear Ratio	2.41:1
Effective Maximum Low-gear Ratio	19.11:1

TRANSAXLE: AUTOMATIC JATCO MODEL CVT2L (FREEDOM DRIVE II)

Availability	Optional — Sport 4WD with 2.4-liter engine and Freedom Drive II
Description	Continuously-variable ratio, lockup torque converter, electronic controls
Gear Ratios	
Forward	2.349:1 to 0.394:1 continuously variable
Reverse	1.75:1
Final-drive Ratio	8.135:1
Overall Top-gear Ratio	3.21:1
Effective Maximum Low-gear Ratio	19.11:1



DRIVETRAIN

Front-wheel Drive	
Availability	Standard
Front Differential	Open
Four-wheel Drive	
Availability	Optional
Type	Electronically-controlled coupling (ECC) with four-wheel-drive lock
Rear Differential	Open

ELECTRICAL SYSTEM

Alternator	120-amp; 140-amp with CVT2L (Freedom Drive II)
Battery	525 CCA, maintenance-free

SUSPENSION

Front	Independent MacPherson strut, coil spring over gas-charged shock absorbers and stabilizer bar
Rear	Multi-link independent with coil springs, link-type stabilizer bar, gas-charged shock absorbers

STEERING

Type	Rack and pinion with hydraulic power assist
Overall Ratio	16.4:1
Turning Diameter (curb-to-curb)	17-in. wheels and tires — 35.6 ft. (10.8 m)
	18-in. wheels and tires — 37.2 ft. (11.3 m)
Steering Turns (lock-to-lock)	17-in. wheels and tires — 2.88
	18-in. wheels and tires — 2.76

BRAKES

Availability	Standard — 4x2 Sport
Front	
Size and Type	11.5 x 1.0 (294 x 26) vented disc with 2.2 (57) single-piston floating caliper



2017 JEEP® COMPASS SPECIFICATIONS

17

Swept Area	223.52 sq. in. (1,442.12 sq. cm)
Rear	
Size and Type	9.0 x 1.38 (229 x 35) drums
Swept Area	78.1 sq. in. (503 sq. cm)
Power-assist Type	10 (254) single-diaphragm vacuum
Anti-lock Brake System (ABS)	Standard
Electronic Stability Control (ESC)	Standard
Hill-start Assist (HSA)	Standard with manual transmission
Availability	Standard — 4x4 Compass and Latitude
Front	
Size and Type	11.5 x 1.0 (294 x 26) vented disc with 2.2 (57) single-piston floating caliper
Swept Area	223.52 sq. in. (1,442.12 sq. cm)
Rear	
Size and Type	10.3 x 0.39 (262 x 10) solid disc with 1.4 (35) single-piston floating caliper
Swept Area	138.64 sq. in. (894.6 sq. cm)
Power-assist Type	10 (254) single-diaphragm vacuum
Anti-lock Brake System (ABS)	Standard
Electronic Stability Control (ESC)	Standard
Hill-start Assist (HSA)	Standard with manual transmission and Freedom Drive II Off-road Package
Off-road BrakeTraction-Control System (BTCS)	Included with Freedom Drive II Off-road Package
Hill-descent Control (HDC)	Included with Freedom Drive II Off-road Package
DIMENSIONS AND CAPACITIES^(d)	
Wheelbase	103.7 (2,635)
Track, Front	59.8 (1,520)
Track, Rear	59.8 (1,520)
Overall Length	175.1 (4,448)
Overall Width	71.4 (1,812)



2017 JEEP® COMPASS
SPECIFICATIONS



Overall Height	65.0 (1,651)
Overhang, Front	36.1 (916)
Overhang, Rear	35.3 (897)
Approach Angle with P215/60/R17 tire (degrees)	19.5
Breakover Angle with P215/60/R17 tire (degrees)	20.6
Departure Angle with P215/60/R17 tire (degrees)	28.5
Ground Clearance with P215/60/R17 tire	8.1 (206)
Approach Angle with Freedom Drive II Off-road Package P215/65/R17 tire (degrees)	29.6
Breakover Angle with Freedom Drive II Off-road Package P215/65/R17 tire	23.6
Departure Angle with Freedom Drive II Off-road Package P215/65/R17 tire	31.2
Ground Clearance with Freedom Drive II Off-road Package P215/65/R17 tire	9.1 (231)
Aero (CdA)	10.5 — 2WD 10.6 — 4WD
Curb Weight, lb. (kg)	Sport 2WD — 3,107 (1,409 kg) 2.0-liter (manual) Sport 2WD — 3,185 (1,445 kg) 2.0-liter (CVT2) Sport 2WD — 3,103 (1,407 kg) 2.4-liter (manual) Sport 2WD — 3,178 (1,442kg) 2.4-liter (automatic) Sport 4WD — 3,258 (1,478 kg) 2.4-liter (manual) Sport 4WD — 3,354 (1,528 kg) 2.4-liter (automatic) Sport 4WD — 3,341 (1,515 kg) 2.4-liter (CVT2L)
Weight Distribution, percent F/R	59/41 — 2WD 58/42 — 4WD
Fuel Tank Capacity, gal. (liter)	13.6 (51.5) — 2WD; 13.5 (51.1) — 4WD

^(d) All dimensions measured at curb weight with standard tires.

ACCOMMODATIONS

Seating Capacity, front/rear	2/3
Front	
Headroom without Sunroof	40.7 (1,033)
Legroom	40.6 (1,032)



2017 JEEP® COMPASS SPECIFICATIONS

17

Shoulder Room	54.6 (1,387)
Hip Room	52.3 (1,328)
Seat Travel	Driver — 10.2 (260); Passenger — 10.2 (260)
Recliner Angle Range (degrees)	Driver — up to 88; Passenger — up to 88
SAE Front Seat Volume Index, cu. ft. (cu. m)	52.2 (1.478)
Rear	
Headroom	39.9 (1,013)
Legroom	39.4 (1,001)
Knee Clearance	1.7 (44.1)
Shoulder Room	54.0 (1,372)
Hip Room	51.0 (1,295)
SAE Rear Seat Volume Index, cu. ft. (cu. m)	49.1 (1.391)
SAE Interior Volume, cu. ft. (cu. m)	101.3 (2.87)
Cargo Volume Indexes	
Rear Seats Up, cu. ft. (cu. m)	22.7 (0.643)
Rear Seats Folded, cu. ft. (cu. m)	53.6 (1.519)
EPA Interior Volume Index, cu. ft. (cu. m)	124 (3.512)
Trunk Lift-over Height	30.5 (775)
Cargo Volume with Front Passenger Seat and Rear Seat Folded, cu. ft. (cu. m)	62.7 (1.776)
Minimum Cargo Width at Liftgate Opening	38.5 (976)
Minimum Cargo Height at Liftgate Opening	25.0 (634)
Maximum Cargo Width at Liftgate Opening	45.3 (1,150)
Maximum Cargo Height at Liftgate Opening	26.7 (681)
Distance Between Wheelhouse Interior Trim	38.0 (966)
WHEELS	
Availability	Standard — Sport, and Latitude FWD with 2.0-liter engine
Type and Material	Full-painted aluminum
Size	16 x 6.5



2017 JEEP® COMPASS SPECIFICATIONS



Availability	Standard — Sport, Latitude with 2.4-liter engine, optional with 2.0-liter
Type and Material	Full-painted aluminum
Size	17 x 6.5

Availability	Optional — Latitude
Type and Material	Chrome-clad aluminum
Size	18 x 7.0

TIRES

Availability	Standard — Sport, Latitude with 2.0-liter engine
Size and Type	P205/70R16 BSW All-season Touring
Manufacturer and Model	Goodyear Eagle LS
Revs per Mile (Km)	763 (475)

Availability	Standard — Latitude
Size and Type	P215/60R17 BSW All-season Touring
Manufacturer and Model	Firestone Affinity S3
Revs per Mile (Km)	771 (479)

Availability	Optional — the Latitude
Size and Type	P225/60R17 BSW All-season Touring
Manufacturer and Model	Kumho Solus KL21
Revs per Mile (Km)	756 (470)

Availability	Optional — Sport, Latitude
Size and Type	P215/65R17 outlined white letter (OWL) All-terrain
Manufacturer and Model	Goodyear Wrangler GTA 03
Revs per Mile (Km)	743 (462)



2017 JEEP® COMPASS
SPECIFICATIONS



Availability	Optional — Latitude
Size and Type	P215/55R18 All-season Performance
Manufacturer and Model	Firestone Firehawk GTA 03
Revs per Mile (Km)	765 (476)

