

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

All dimensions are in inches (millimeters) unless otherwise noted.
All dimensions measured at curb weight with standard tires and wheels.

GENERAL INFORMATION

Body Styles _____ Regular cab and Quad Cab
Assembly Plants _____ Saltillo, Mexico and St. Louis, Missouri
EPA Vehicle Class _____ Standard Pickup

ENGINE: 5.7-LITER HEMI MAGNUM V-8

Availability _____ Std.—All(a)
Type and Description _____ Eight-cylinder, 90° V-type, liquid-cooled
Displacement _____ 343 cu. in. (5654 cu. cm)
Bore x Stroke _____ 3.92 x 3.58 (99.5 x 90.9)
Valve System _____ Pushrod-operated overhead valves, 16 valves, hydraulic lifters with roller followers
Fuel Injection _____ Sequential, multi-port, electronic, returnless
Construction _____ Deep-skirt cast-iron block with cross-bolted main bearing caps, aluminum alloy heads with hemispherical combustion chambers
Compression Ratio _____ 9.6:1
Power (SAE net) _____ 345 bhp (257 kW) @ 5,400 rpm, (58.4 bhp/L), 2500 Series(b);
330 bhp (246 kW) @ 4,800 rpm, (55.9 bhp/L), 3500 Series
Torque (SAE net) _____ 375 lb.-ft. (509 N•m) @ 4,200 rpm, 2500 and 3500 Series
Max. Engine Speed _____ 5,800 rpm
Fuel Requirement _____ Unleaded mid-grade, 89 octane (R+M)/2—recommended,
Unleaded regular, 87 octane (R+M)/2—acceptable
Oil Capacity _____ 7 qt. (6.6L)
Coolant Capacity _____ 18.7 qt. (17.7L)
Emission Control _____ Dual three-way catalytic converters, internal engine features with knock sensors(b)

(a) Not available on 3500 SRW.

(b) All manual transmission equipped vehicles meet LEV I chassis-certified emissions requirements in California, New York, Massachusetts, Maine and Vermont. Meets Tier 2 HDV 1,2 chassis-certified emissions requirements in 45 remaining states. Ram 2500 and 3500 models equipped with automatic transmission and sold in 45 states meet Tier 2 HDV 1,2 chassis-certified emissions requirements. Ram 2500 models equipped with automatic transmission and sold in California, New York, Massachusetts, Maine and Vermont meet LEV II—MDV 1 category chassis-certified emissions requirements. Ram 3500 models equipped with automatic transmission and sold in California, New York, Massachusetts, Maine and Vermont meet LEV II—MDV 2 category chassis-certified emissions requirements.

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

ENGINE: 5.9-LITER H.O. CUMMINS TURBO DIESEL I-6

Availability _____ Opt.—All
Type and Description _____ Six-cylinder, inline, liquid-cooled, turbocharged, intercooled
Displacement _____ 359 cu. in. (5883 cu. cm)
Bore x Stroke _____ 4.02 x 4.72 (102.1 x 119.9)
Valve System _____ OHV, 24 valves, solid lifters
Fuel Injection _____ Electronic high-pressure common rail
Construction _____ Cast-iron block and head
Compression Ratio _____ 17.2:1
Power (SAE net) _____ 325 bhp (242 kW) @ 2,900 rpm—High Output (51.7 bhp/L)(a)
Torque (SAE net) _____ 610 lb.-ft. (827 N•m) @ 1,600 rpm—high output(a)
Maximum High-Idle Engine Speed _____ 3,500 rpm
Fuel Requirement _____ Diesel
Oil Capacity _____ 12 qt. (11.4L) with filter
Coolant Capacity _____ 32.7 qt. (30.9L)
Emission Controls _____ Oxidation catalytic converter and internal engine features(a)(b)

ELECTRICAL SYSTEM

Alternator

Availability _____ Standard—All
Rating _____ 136-amp
Availability _____ Included with Heavy Duty Snow Plow Group
Rating _____ 160-amp

Battery

Availability _____ Standard—2500 and 3500 with gasoline engines
Description _____ Group 65, maintenance-free, 600 CCA
Availability _____ Standard—All with diesel engines; included in Heavy Duty Snow Plow and Trailer Tow Groups
Description _____ Group 65, maintenance-free, 750 CCA

TRANSMISSION: G56—MANUAL, SIX-SPEED OVERDRIVE

Availability _____ Std. with 5.7-liter V-8; Std. with 5.9-liter H.O. Diesel

(a) Not available on 3500 SRW.

(b) All manual transmission equipped vehicles meet LEV I chassis-certified emissions requirements in California, New York, Massachusetts, Maine and Vermont. Meets Tier 2 HDV 1,2 chassis-certified emissions requirements in 45 remaining states. Ram 2500 and 3500 models equipped with automatic transmission and sold in 45 states meet Tier 2 HDV 1,2 chassis-certified emissions requirements. Ram 2500 models equipped with automatic transmission and sold in California, New York, Massachusetts, Maine and Vermont meet LEV II—MDV 1 category chassis-certified emissions requirements. Ram 3500 models equipped with automatic transmission and sold in California, New York, Massachusetts, Maine and Vermont meet LEV II—MDV 2 category chassis-certified emissions requirements.

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

Description _____ Synchronized in all gears

Gear Ratios

1st _____	6.29
2nd _____	3.48
3rd _____	2.10
4th _____	1.38
5th _____	1.00
6th _____	0.79
Reverse _____	5.74

TRANSMISSION: 5-45RFE—AUTOMATIC FIVE-SPEED

Availability _____ Optional with 5.7-liter engines

Description _____ Three planetary gear sets, one overrunning clutch,
full electronic control, electronically controlled converter clutch

Gear Ratios

1st _____	3.0
2nd _____	1.67—upshift; 1.50—kick-down
3rd _____	1.0
4th _____	0.75
5th _____	0.67
Reverse _____	3.00

Overall Top Gear _____ 2.50 with 3.73 axle ratio; 2.75 with 4.10 axle ratio

TRANSMISSION: 48RE—AUTOMATIC, FOUR-SPEED OVERDRIVE

Availability _____ 48RE—optional with Cummins diesel engine

Description _____ Hydraulic control, electronically controlled governor overdrive,
overdrive lockout and converter clutch

Gear Ratios

1st _____	2.45
2nd _____	1.45
3rd _____	1.0
4th _____	0.69
Reverse _____	2.20

Overall Top Gear Ratio _____ 2.57 with 3.73 axle ratio; 2.82 with 4.10 axle ratio

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

TRANSFER CASES: NV271/NV273

Availability _____ NV271—std. 4x4 ST
 NV273—std. Laramie; opt. SLT
 Type _____ Part-time
 Operating Modes _____ 2WD; 4WD High; Neutral; 4WD Low
 Shift Mechanism _____ NV271—manual; NV273—electric
 Low-Range Ratio _____ 2.72
 Center Differential _____ None

DIMENSIONS AND CAPACITIES

Series	2500		3500		
Box	Short	Long	Short—Single Rear Wheels	Long—Single Rear Wheels	Long—Dual Rear Wheels
QUAD CAB—2WD			265/70R17	245/70R17	
Wheelbase _____	140.5 _____	160.5 _____	140.5 _____	160.5 _____	160.5 _____
Track, Front _____	68.6 _____	68.6 _____	68.6 _____	68.6 _____	68.6 _____
Track, Rear _____	68.2 _____	67.9 _____	68.2 _____	68.2 _____	75.8 _____
Overall Length _____	227.7 _____	249.7 _____	227.7 _____	249.7 _____	249.7 _____
Overall Width _____	79.5 _____	79.5 _____	79.5 _____	79.5 _____	96 _____
Overall Height _____	74.5 _____	73.8 _____	75 _____	74.3 _____	75.1 _____
Tailgate Load Height _____	33 _____	32.7 _____	33.7 _____	32.9 _____	34.1 _____
Ground Clearance					
Front axle _____	8.4 _____	7.7 _____	7.8 _____	8.4 _____	8.0 _____
Rear axle _____	7.1 _____	7.4 _____	7.4 _____	7.1 _____	7.6 _____
Approach Angle _____	16.1° _____	14.9° _____	16.6° _____	16.2° _____	16.9° _____
Ramp Breakover Angle _____	16.2° _____	18.4° _____	17.0° _____	15.1° _____	16.3° _____
Departure Angle _____	24.4° _____	23.1° _____	25.3° _____	23.3° _____	24.6° _____
Frontal Area, sq. ft. _____	35.1 _____	35.1 _____	35.1 _____	35.1 _____	36.8 _____
Drag Coefficient _____	— _____	— _____	— _____	— _____	— _____
Fuel Tank, gal. (L) _____	34 (128) _____	35 (132) _____	34 (128) _____	35 (132) _____	35 (132) _____

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

DIMENSIONS AND CAPACITIES (CONTINUED)

Series	2500		3500		
Box	Short	Long	Short-Single Rear Wheels	Long-Single Rear Wheels	Long-Dual Rear Wheels
QUAD CAB—4WD			265/70R17	245/70R17	
Wheelbase	140.5	160.5	140.5	160.5	160.5
Track, Front	69.5	69.5	69.5	69.5	69.5
Track, Rear	68.2	68.2	68.2	68.2	75.8
Overall Length	227.7	249.7	227.7	249.7	249.7
Overall Width	79.5	79.5	79.5	79.5	96
Overall Height	78.6	78.5	79.1	78.5	79.1
Tailgate Load Height	36.3	36.2	37.0	36.2	37.1
Ground Clearance					
Front axle	12.9	12.9	8.1	12.9	8.2
Rear axle	7.1	7.1	7.4	7.1	7.6
Approach Angle	23.7°	23.8°	24.2°	23.8°	24.5°
Ramp Breakover Angle	27.2°	22.9°	25.2°	22.9°	23.9°
Departure Angle	28.0°	27.3°	28.9°	27.3°	27.8°
Frontal Area, sq. ft.	35.4	35.4	35.4	35.4	37.1
Drag Coefficient	—	—	—	—	—
Fuel Tank, gal. (L)	34 (128)	35 (132)	34 (128)	35 (132)	35 (132)

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

REGULAR CAB—2WD

Model	2500—245/70R17	3500—Dual Rear Wheels
Wheelbase	140.5	140.5
Track, Front	68.6	68.6
Track, Rear	68.2	75.8
Overall Length	229.7	229.7
Overall Width	79.6	96
Overall Height	73.9	74.7
Tailgate Load Height	33	34.4
Ground Clearance		
Front axle	8.4	8.0
Rear axle	7.1	7.6
Approach Angle	16.1	16.7
Ramp Breakover Angle	16.2	17.5
Departure Angle	23.4	24.8
Frontal Area, sq. ft.	35.1	36.8
Drag Coefficient	—	—
Fuel Tank, gal. (L)	35 (132)	35 (132)

REGULAR CAB—4WD

Wheelbase	140.5	140.5
Track, Front	69.5	69.5
Track, Rear	68.2	75.8
Overall Length	229.7	229.7
Overall Width	79.6	96
Overall Height	78.1	78.7
Tailgate Load Height	36.3	37.2
Ground Clearance		
Front axle	12.9	8.2
Rear axle	7.1	7.6
Approach Angle, deg.	23.7	24.4
Ramp Breakover Angle, deg.	27.2	25.5
Departure Angle, deg.	27.3	27.9
Frontal Area, sq. ft.	35.4	37.1
Drag Coefficient	—	—
Fuel Tank, gal. (L)	35 (132)	35 (132)

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

CARGO BOX

Model	2500-245/70R17	3500-Dual Rear Wheels
Nominal Box Size	6 ft., 3 in.	8 ft.
SAE Volume	60.9 cu. ft. (1.723 cu. m)	74.9 cu. ft. (2.121 cu. m)
Length at Floor, Tailgate Closed	76.3 (1938.3)	98.3 (2497.1)
Cargo Width	70.2 (1783.9)	66.4 (1687)
Distance Between Wheelhouses	51.0 (1295)	51.0 (1295)
Depth	20.2 (514.0)	20.2 (514.0)
Tailgate Opening Width	60.6 (1538.0)	60.6 (1538.0)

ACCOMMODATIONS

	Quad Cab	Regular Cab
Seating Capacity, F/R	3/3	3/-
Front		
Head room	40.8 (1037)	40.9 (1040)
Leg room	41.0 (1041)	41.0 (1041)
Shoulder room	67.0 (1702)	67.1 (1705.6)
Hip room	64.9 (1648.2)	64.9 (1648.2)
Seat travel	9.0 (229)	9.0 (229)
Recliner range	45°	45°
Rear		
Head room	40.0 (1015)	-
Leg room	36.7 (1648.2)	-
Shoulder room	66.7 (1094)	-
Hip room	64.6 (1640)	-
Knee clearance	1.1 (28.4)	-
Interior Volume		
Front	64.92 cu. ft.	65.2 cu. ft.
Rear	56.7 cu. ft.	-

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

BODY AND CHASSIS

	4x2	4x4
Layout	Longitudinal, front engine; Hotchkiss drive	Longitudinal, front engine; Hotchkiss drive, transfer case
Construction	Ladder-type frame, steel cab, double-wall steel pickup box	Ladder-type frame, steel cab, double-wall steel pickup box

SUSPENSION

Front	Short and long arm independent, coil springs, gas-charged shock absorbers, stabilizer bar	Live axle, Quadra Link leading arms, track bar, coil springs bar, coil springs, stabilizer bar, gas-charged shock absorbers
Rear	Live axle, longitudinal leaf springs, gas-charged shock absorbers—2500 auxiliary springs added—3500	Live axle, longitudinal leaf springs, gas-charged shock absorbers—2500; auxiliary springs added—3500

STEERING

Model	Quad Cab, Short Box	Regular Cab	Quad Cab, Long Box
4x2			
Overall Ratio	15.4:1	15.4:1	15.4:1
Steering Wheel Turns Lock to Lock	3	3	3
Turning Diameter			
(Curb to Curb)	44.6 ft. (13.6 m)	44.6 ft. (13.6 m)	50.3 ft. (15.3 m)
4x4			
Overall Ratio	13.4:1	13.4:1	13.4:1
Steering Wheel Turns Lock to Lock	2.75	2.75	2.75
Turning Diameter			
(Curb to Curb)(a)	48.9 ft. (14.9 m)	48.9 ft. (14.9 m)	52.0 ft. (15.8 m)

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

BRAKES

Model	2500	3500
Front Size and Type	13.9 x 1.26 (353 x 35.5) vented disc with 2 x 2.20 (2 x 56) twin-piston sliding caliper and ABS	13.9 x 1.26 (353 x 35.5) vented disc with 2 x 2.20 in. (2 x 56) twin-piston sliding caliper and ABS
Swept Area	313.2 sq. in. (2021 sq. cm)	313.2 sq. in. (2021 sq. cm)
Rear Size and Type	13.9 x 1.18 (352.5 x 30) disc with 2 x 1.77 (2 x 45) twin-piston sliding caliper and ABS	Single Rear Wheels— 13.9 x 1.18 (352.5 x 30) disc with 2 x 1.77 (2 x 45) twin-piston sliding caliper and ABS Dual Rear Wheels—13.9 x 1.18 (352.5 x 30) disc with 2 x 2.01 in. (2 x 51 mm) twin-piston sliding caliper and ABS
Swept Area	309.6 sq. in. (1997 sq. cm)	309.6 sq. in. (1997 sq. cm)
Power Assist Type	Tandem diaphragm vacuum with gasoline	Hydraulic engines; hydraulic with diesel engines

ESTIMATED TRAILER TOWING CAPACITIES

2500 RAM QUAD CAB 2WD SHORT BED ST

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	3.73	8800	3020	5784	3208	2576	4410	6000	15,000	9050
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	8800	3020	5784	3208	2576	4410	6000	17,000	11,050
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.73	8800	3070	5735	3160	2575	4410	6000	15,000	9100
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	8800	3070	5735	3160	2575	4410	6000	17,000	11,100
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9000	2460	6541	3919	2622	4630	6000	20,000	13,300
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9000	2540	6463	3856	2607	4630	6000	20,000	13,400
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9000	2540	6463	3856	2607	4630	6000	20,000	13,400

(a) Estimated Trailer Tow Ratings are for ST models with 4.10 axle ratio. Ratings for SLT models are approximately 100 lbs. less. Ratings with 3.73 axle ratio may also be less.

1. Payload is rounded to the nearest 10 lbs. Payload = GVWR - curb wt.

2. Maximum trailer weights are rounded to the nearest 50 lbs. Maximum trailer weight = GCWR - curb wt. - 150 lbs. (allowance for driver).

3. Use an exhaust brake recommended for all applications with a trailer weight over 10,000 lbs.

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

2500 RAM QUAD CAB 2WD SHORT BED SLT

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd MANU (DEG)	3.73	8800	2960	5843	3235	2608	4750	6010	15,000	9000
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	8800	2960	5843	3235	2608	4750	6010	17,000	11,000
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.73	8800	3010	5794	3187	2607	4750	6010	15,000	9050
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	8800	3010	5794	3187	2607	4750	6010	17,000	11,050
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9000	2420	6578	3908	2670	4750	6010	20,000	13,250
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9000	2500	6500	3845	2655	4750	6010	20,000	13,350
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9000	2500	6500	3845	2655	4750	6010	20,000	13,350

2500 RAM QUAD CAB 2WD SHORT BED LARAMIE

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	3.73	8800	2860	5941	3289	2653	4750	6010	15,000	8900
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	8800	2860	5941	3289	2653	4750	6010	17,000	10,900
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.73	8800	2910	5892	3241	2652	4750	6010	15,000	8950
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	8800	2910	5892	3241	2652	4750	6010	17,000	10,950
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9000	2320	6675	3962	2714	4750	6010	20,000	13,150
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9000	2400	6598	3899	2699	4750	6010	20,000	13,250
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9000	2400	6598	3899	2699	4750	6010	20,000	13,250

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

2500 RAM QUAD CAB 2WD LONG BED ST

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	3.73	8800	2970	5828	3303	2525	4410	6000	15,000	9000
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	8800	2970	5828	3303	2525	4410	6000	17,000	11,000
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.73	8800	3020	5779	3255	2524	4410	6000	15,000	9050
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	8800	3020	5779	3255	2524	4410	6000	17,000	11,050
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9000	2390	6614	4023	2591	4630	6000	20,000	13,250
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9000	2460	6536	3960	2576	4630	6000	20,000	13,300
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9000	2460	6536	3960	2576	4630	6000	20,000	13,300

2500 RAM QUAD CAB 2WD LONG BED SLT

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	3.73	8800	2900	5900	3339	2561	4750	6010	15,000	8950
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	8800	2900	5900	3339	2561	4750	6010	17,000	10,950
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.73	8800	2950	5851	3291	2560	4750	6010	15,000	9000
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	8800	2950	5851	3291	2560	4750	6010	17,000	11,000
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9000	2330	6669	4052	2617	4750	6010	20,000	13,200
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9000	2410	6591	3989	2602	4750	6010	20,000	13,250
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9000	2410	6591	3989	2602	4750	6010	20,000	13,250

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

2500 RAM QUAD CAB 2WD LONG BED LARAMIE

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	3.73	8800	2800	5998	3397	2601	4750	6010	15,000	8850
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	8800	2800	5998	3397	2601	4750	6010	17,000	10,850
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.73	8800	2850	5949	3349	2600	4750	6010	15,000	8900
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	8800	2850	5949	3349	2600	4750	6010	17,000	10,900
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9000	2230	6767	4111	2656	4750	6010	20,000	13,100
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9000	2310	6689	4048	2642	4750	6010	20,000	13,150
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9000	2310	6689	4048	2642	4750	6010	20,000	13,150

2500 RAM REGULAR CAB 2WD LONG BED ST

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	3.73	8650	3180	5467	3127	2340	4410	6000	15,000	9400
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	8650	3180	5467	3127	2340	4410	6000	17,000	11,400
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.73	8650	3230	5418	3079	2339	4410	6000	15,000	9450
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	8650	3230	5418	3079	2339	4410	6000	17,000	11,450
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9000	2760	6237	3850	2388	4630	6000	20,000	13,600
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9000	2840	6160	3786	2373	4630	6000	20,000	13,700
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9000	2840	6160	3786	2373	4630	6000	20,000	13,700

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

2500 RAM REGULAR CAB 2WD LONG BED SLT

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	3.73	8650	3,150	5505	3135	2370	4750	6010	15,000	9350
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	8650	3150	5505	3135	2370	4750	6010	17,000	11,350
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.73	8650	3190	5456	3087	2369	4750	6010	15,000	9400
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	8650	3190	5456	3087	2369	4750	6010	17,000	11,400
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9000	2680	6317	3893	2424	4750	6010	20,000	13,550
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9000	2760	6239	3830	2409	4750	6010	20,000	13,600
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9000	2760	6239	3830	2409	4750	6010	20,000	13,600

2500 RAM REGULAR CAB 2WD LONG BED LARAMIE

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	3.73	8650	3130	5522	3147	2375	4750	6010	15,000	9350
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	8650	3130	5522	3147	2375	4750	6010	17,000	11,350
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.73	8650	3180	5473	3099	2374	4750	6010	15,000	9400
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	8650	3180	5473	3099	2374	4750	6010	17,000	11,400
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9000	2670	6334	3905	2429	4750	6010	20,000	13,500
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9000	2740	6256	3842	2414	4750	6010	20,000	13,600
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9000	2740	6256	3842	2414	4750	6010	20,000	13,600

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

2500 RAM QUAD CAB 4WD SHORT BED ST

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	3.73	8800	2580	6217	3596	2621	5200	6000	15,000	8650
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	8800	2580	6217	3596	2621	5200	6000	17,000	10,650
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.73	8800	2630	6168	3547	2620	5200	6000	15,000	8700
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	8800	2630	6168	3547	2620	5200	6000	17,000	10,700
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9000	2010	6987	4301	2686	5200	6000	20,000	12,850
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9000	2090	6909	4238	2671	5200	6000	20,000	12,950
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9000	2090	6909	4238	2671	5200	6000	20,000	12,950

2500 RAM QUAD CAB 4WD SHORT BED SLT

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	3.73	8800	2500	6298	3632	2666	5200	6010	15,000	8550
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	8800	2500	6298	3632	2666	5200	6010	17,000	10,550
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.73	8800	2550	6249	3584	2665	5200	6010	15,000	8600
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	8800	2550	6249	3584	2665	5200	6010	17,000	10,600
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9000	1930	7067	4320	2746	5200	6010	20,000	12,800
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9000	2010	6989	4257	2732	5200	6010	20,000	12,850
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9000	2010	6989	4257	2732	5200	6010	20,000	12,850

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

2500 RAM QUAD CAB 4WD SHORT BED LARAMIE

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	3.73	8,800	2,410	6,390	3,682	2,708	5,200	6,010	15,000	8,450
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	8,800	2,410	6,390	3,682	2,708	5,200	6,010	17,000	10,450
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.73	8,800	2,460	6,341	3,634	2,707	5,200	6,010	15,000	8,500
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	8,800	2,460	6,341	3,634	2,707	5,200	6,010	17,000	10,500
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9,000	1,840	7,158	4,370	2,788	5,200	6,010	20,000	12,700
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9,000	1,920	7,080	4,307	2,773	5,200	6,010	20,000	12,750
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9,000	1,920	7,080	4,307	2,773	5,200	6,010	20,000	12,750

2500 RAM QUAD CAB 4WD SHORT BED SLT

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.56	8,510	2,020	6,486	3,883	2,603	4,500	6,140	17,000	10,350
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.56	8,510	2,070	6,437	3,835	2,602	4,500	6,140	17,000	10,400

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

2500 RAM QUAD CAB 4WD LONG BED ST

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	3.73	8800	2530	6274	3692	2582	5200	6000	15,000	8600
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	8800	2530	6274	3692	2582	5200	6000	17,000	10,600
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.73	8800	2580	6225	3644	2581	5200	6000	15,000	8650
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	8800	2580	6225	3644	2581	5200	6000	17,000	10,650
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9,000	1940	7064	4409	2655	5200	6000	20,000	12,800
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9000	2010	6986	4346	2640	5200	6000	20,000	12,850
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9000	2010	6986	4346	2640	5200	6000	20,000	12,850

2500 RAM QUAD CAB 4WD LONG BED SLT

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	3.73	8800	2360	6436	3744	2692	5200	6010	15,000	8400
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	8800	2360	6436	3744	2692	5200	6010	17,000	10,400
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.73	8800	2410	6387	3696	2691	5200	6010	15,000	8450
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	8800	2410	6387	3696	2691	5200	6010	17,000	10,450
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9000	1820	7181	4467	2714	5200	6010	20,000	12,650
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9000	1900	7103	4404	2699	5200	6010	20,000	12,750
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9000	1900	7103	4404	2699	5200	6010	20,000	12,750

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

2500 RAM QUAD CAB 4WD LONG BED LARAMIE

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	3.73	8800	2340	6457	3795	2662	5200	6010	15,000	8400
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	8800	2340	6457	3795	2662	5200	6010	17,000	10,400
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.73	8800	2390	6408	3746	2661	5200	6010	15,000	8450
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	8800	2390	6408	3746	2661	5200	6010	17,000	10,450
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9000	1730	7272	4521	2751	5200	6010	20,000	12,600
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9000	1810	7194	4458	2736	5200	6010	20,000	12,650
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9000	1810	7194	4458	2736	5200	6010	20,000	12,650

2500 RAM REGULAR CAB 4WD LONG BED ST

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	3.73	8650	2770	5882	3482	2400	5200	6000	15,000	8950
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	8650	2770	5882	3482	2400	5200	6000	17,000	10,950
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.73	8650	2820	5833	3434	2399	5200	6000	15,000	9000
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	8650	2820	5833	3434	2399	5200	6000	17,000	11,000
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9000	2340	6662	4208	2454	5200	6000	20,000	13,200
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9000	2420	6584	4145	2439	5200	6000	20,000	13,250
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9000	2420	6584	4145	2439	5200	6000	20,000	13,250

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

2500 RAM REGULAR CAB 4WD LONG BED SLT

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	3.73	8650	2600	6055	3555	2500	5200	6010	15,000	8800
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	8650	2600	6055	3555	2500	5200	6010	17,000	10,800
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.73	8650	2640	6006	3507	2499	5200	6010	15,000	8850
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	8650	2640	6006	3507	2499	5200	6010	17,000	10,850
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9000	2250	6746	4248	2499	5200	6010	20,000	13,100
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9000	2330	6668	4185	2484	5200	6010	20,000	13,200
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9000	2330	6668	4185	2484	5200	6010	20,000	13,200

2500 RAM REGULAR CAB 4WD LONG BED LARAMIE

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	3.73	8650	2690	5959	3517	2443	5200	6010	15,000	8900
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	8650	2690	5959	3517	2443	5200	6010	17,000	10,900
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.73	8650	2740	5910	3469	2442	5200	6010	15,000	8950
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	8650	2740	5910	3469	2442	5200	6010	17,000	10,950
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9000	2240	6757	4256	2501	5200	6010	20,000	13,100
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9000	2320	6679	4193	2486	5200	6010	20,000	13,150
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9000	2320	6679	4193	2486	5200	6010	20,000	13,150

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

2500 RAM REGULAR CAB 4WD LONG BED SLT

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.56	8510	2270	6243	3806	2437	4500	6140	17,000	10,600
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.56	8510	2320	6194	3758	2436	4500	6140	17,000	10,650

3500 RAM QUAD CAB 2WD SHORT BED ST

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9900	3120	6780	3919	2861	4750	6200	23,000	16,050
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9900	3200	6703	3856	2847	4750	6200	21,000	14,150
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9900	3200	6703	3856	2847	4750	6200	23,000	16,150

3500 RAM QUAD CAB 2WD SHORT BED SLT

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9900	3200	6703	3940	2763	4750	6200	23,000	16,150
5.9L 24V TDHO	A4	48RE 4 spd. AUTO (DG8)	3.73	9900	3270	6625	3877	2749	4750	6200	21,000	14,200
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9900	3270	6625	3877	2749	4750	6200	23,000	16,200

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

3500 RAM QUAD CAB 2WD SHORT BED LARAMIE

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9900	3160	6739	3964	2776	4750	6200	23,000	16,100
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9900	3240	6661	3901	2761	4750	6200	21,000	14,200
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9900	3240	6661	3901	2761	4750	6200	23,000	16,200

3500 RAM QUAD CAB 2WD LONG BED ST

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	11,000	4660	6342	3361	2981	4110	9350	17,000	10,500
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	11,000	4710	6293	3313	2980	4110	9350	17,000	10,550
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	11,500	4440	7059	4057	3002	4750	9350	23,000	15,800
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	11,500	4520	6981	3994	2987	4750	9350	21,000	13,850
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	11,500	4520	6981	3994	2987	4750	9350	23,000	15,850

3500 RAM QUAD CAB 2WD LONG BED ST

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9900	3210	6690	4018	2673	4750	6200	23,000	16,150
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9900	3290	6613	3954	2658	4750	6200	21,000	14,250
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9900	3290	6613	3954	2658	4750	6200	23,000	16,250

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

3500 RAM QUAD CAB 2WD LONG BED SLT

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	11,000	4540	6460	3425	3034	4110	9350	17,000	10,400
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	11,000	4590	6410	3377	3033	4110	9350	17,000	10,450
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	11,500	4240	7262	4099	3162	4750	9350	23,000	15,600
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	11,500	4320	7184	4036	3147	4750	9350	21,000	13,650
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	11,500	4320	7184	4036	3147	4750	9350	23,000	15,650

3500 RAM QUAD CAB 2WD LONG BED SLT

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9900	3000	6903	4065	2838	4750	6200	23,000	15,950
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9900	3080	6825	4002	2823	4750	6200	21,000	14,050
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9900	3080	6825	4002	2823	4750	6200	23,000	16,050

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

3500 RAM QUAD CAB 2WD LONG BED LARAMIE

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	11,000	4440	6558	3479	3079	4110	9350	17,000	10,300
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	11,000	4490	6509	3431	3078	4110	9350	17,000	10,350
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	11,500	4360	7137	4093	3044	4750	9350	23,000	15,700
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	11,500	4440	7059	4029	3030	4750	9350	21,000	13,800
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	11,500	4440	7059	4029	3030	4750	9350	23,000	15,800

3500 RAM QUAD CAB 2WD LONG BED LARAMIE

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9900	3120	6778	4058	2720	4750	6200	23,000	16,050
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9900	3200	6700	3995	2705	4750	6200	21,000	14,150
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9900	3200	6700	3995	2705	4750	6200	23,000	16,150

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

3500 RAM REGULAR CAB 2WD LONG BED ST

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	11,000	4990	6007	3183	2824	4110	9350	17,000	10,850
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	11,000	5040	5958	3135	2823	4110	9350	17,000	10,900
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	11,500	4820	6677	3846	2831	4750	9350	23,000	16,150
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	11,500	4900	6599	3783	2817	4750	9350	21,000	14,250
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	11,500	4900	6599	3783	2817	4750	9350	23,000	16,250

3500 RAM REGULAR CAB 2WD LONG BED SLT

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	11,000	4960	6043	3189	2854	4110	9350	17,000	10,800
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	11,000	5010	5994	3141	2853	4110	9350	17,000	10,850
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	11,500	4780	6723	3895	2828	4750	9350	23,000	16,150
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	11,500	4860	6645	3832	2813	4750	9350	21,000	14,200
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	11,500	4860	6645	3832	2813	4750	9350	23,000	16,200

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

3500 RAM REGULAR CAB 2WD LONG BED LARAMIE

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	11,000	4850	6154	3284	2870	4110	9350	17,000	10,700
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	11,000	4900	6105	3236	2869	4110	9350	17,000	10,750
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	11,500	4770	6728	3916	2812	4750	9350	23,000	16,100
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	11,500	4850	6650	3853	2797	4,750	9350	21,000	14,200
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	11,500	4850	6650	3853	2797	4750	9350	23,000	16,200

3500 RAM QUAD CAB 4WD SHORT BED ST

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9900	2840	7057	4296	2761	5200	6200	23,000	15,800
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9900	2920	6979	4233	2746	5200	6200	21,000	13,850
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9900	2920	6979	4233	2746	5200	6200	23,000	15,850

3500 RAM QUAD CAB 4WD SHORT BED SLT

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9900	2760	7138	4341	2797	5200	6200	23,000	15,700
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9900	2840	7060	4278	2782	5200	6200	21,000	13,800
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9900	2840	7060	4278	2782	5200	6200	23,000	15,800

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

3500 RAM QUAD CAB 4WD SHORT BED LARAMIE

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9900	2750	7146	4282	2863	5200	6200	23,000	15,700
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9900	2830	7068	4219	2848	5200	6200	21,000	13,800
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9900	2830	7068	4219	2848	5200	6200	23,000	15,800

3500 RAM QUAD CAB 4WD LONG BED ST

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	11,500	4690	6814	3764	3050	5200	9350	17,000	10,050
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	11,500	4740	6765	3716	3049	5200	9350	17,000	10,100
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	12,200	4700	7504	4441	3063	5200	9350	23,000	15,350
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	12,200	4770	7426	4378	3048	5200	9350	21,000	13,400
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	12,200	4770	7426	4378	3048	5200	9350	23,000	15,400

3500 RAM QUAD CAB 4WD LONG BED ST

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9900	2750	7155	4401	2754	5200	6200	23,000	15,700
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9900	2820	7077	4338	2739	5200	6200	21,000	13,750
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9900	2820	7077	4338	2739	5200	6200	23,000	15,750

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

3500 RAM QUAD CAB 4WD LONG BED SLT

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	11,500	4620	6876	3808	3068	5200	9350	17,000	9950
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	11,500	4670	6827	3760	3067	5200	9350	17,000	10,000
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	12,200	4650	7545	4400	3145	5200	9350	23,000	15,300
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	12,200	4730	7467	4337	3130	5200	9350	21,000	13,400
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	12,200	4730	7467	4337	3130	5200	9350	23,000	15,400

3500 RAM QUAD CAB 4WD LONG BED SLT

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9900	2690	7206	4365	2841	5200	6200	23,000	15,650
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9900	2770	7128	4302	2826	5200	6200	21,000	13,700
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9900	2770	7128	4302	2826	5200	6200	23,000	15,700

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

3500 RAM QUAD CAB 4WD LONG BED LARAMIE

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	11,500	4470	7030	3914	3116	5200	9350	17,000	9800
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	11,500	4520	6981	3866	3115	5200	9350	17,000	9850
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	12,200	4580	7622	4525	3097	5200	9350	23,000	15,250
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	12,200	4660	7544	4462	3082	5200	9350	21,000	13,300
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	12,200	4660	7544	4462	3082	5200	9350	23,000	15,300

3500 RAM QUAD CAB 4WD LONG BED LARAMIE

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	9900	2620	7282	4489	2792	5200	6200	23,000	15,550
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	9900	2700	7204	4426	2778	5200	6200	21,000	13,650
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	9900	2700	7204	4426	2778	5200	6200	23,000	15,650

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

3500 RAM REGULAR CAB 4WD LONG BED ST

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	11,500	5050	6454	3564	2890	5200	9350	17,000	10,400
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	11,500	5100	6405	3516	2889	5200	9350	17,000	10,450
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	12,200	5030	7166	4281	2885	5200	9350	23,000	15,700
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	12,200	5110	7088	4218	2870	5200	9350	21,000	13,750
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	12,200	5110	7088	4218	2870	5200	9350	23,000	15,750

3500 RAM REGULAR CAB 4WD LONG BED SLT

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	11,500	5020	6483	3582	2902	5200	9350	17,000	10,350
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	11,500	5070	6434	3534	2901	5200	9350	17,000	10,400
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	12,200	5040	7165	4229	2936	5200	9350	23,000	15,700
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	12,200	5110	7087	4166	2921	5200	9350	21,000	13,750
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	12,200	5110	7087	4166	2921	5200	9350	23,000	15,750

continued

2006

DODGE RAM 2500/3500 (REGULAR CAB AND QUAD CAB™)

2500/3500 SPECIFICATIONS

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

3500 RAM REGULAR CAB 4WD LONG BED LARAMIE

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
5.7L V-8 gas	M6	POSG56 6-spd. MANU (DEG)	4.10	11,500	4880	6621	3691	2930	5200	9350	17,000	10,250
5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	4.10	11,500	4930	6572	3642	2929	5200	9350	17,000	10,300
5.9L 24V TDHO	M6	POSG56 6-spd. MANU (DEG)	3.73	12,200	4990	7206	4317	2889	5200	9350	23,000	15,650
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	3.73	12,200	5070	7128	4254	2874	5200	9350	21,000	13,700
5.9L 24V TDHO	A4	48RE 4-spd. AUTO (DG8)	4.10	12,200	5070	7128	4254	2874	5200	9350	23,000	15,700

continued