

FCA CANADA

2020 Jeep® Compass

SPECIFICATIONS

Specifications are based on the latest product information available at the time of publication.

All dimensions are in millimetres (inches) unless otherwise noted.

All dimensions measured at curb weight with standard tires and wheels.

GENERAL INFORMATION

Body Style	Sport-utility Vehicle (SUV)
Assembly Plant	Toluca, Mexico
EPA Vehicle Class	Multipurpose vehicle

BODY AND CHASSIS

Layout	Transverse front engine, 4x2 and 4x4
Construction	Steel uniframe

ENGINE: 2.4-LITRE TIGERSHARK WITH MULTIAIR2 WITH ENGINE STOP-START (ESS)

Availability	Standard — all models
Type and Description	In-line four-cylinder, 16-valve MultiAir with multiport fuel injection
Displacement	2,360 cu cm (144 cu. in.)
Bore x Stroke	88 x 97 (3.46 x 3.82)
Valve System	SOHC, four valves per cylinder
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	Aluminum block, aluminum cylinder head
Compression Ratio	10:1
Power (SAE net)	180 hp (134 kW) @ 6,400 rpm
Torque (SAE net)	175 lb.-ft. (237 N•m) @ 3,900 rpm
Max. Engine Speed	6,400 rpm
Fuel Requirement	Unleaded regular, 87 octane
Oil Capacity	5.2 litres (5.5 quarts)
Coolant Capacity	6.4 (6.8 quarts)
Emission Controls	Single catalytic converter, heated wide band lambda sensor upstream and mid-catalyst heated oxygen sensor
EnerGuide (2019) Fuel Consumption Ratings L/100 km (MPG – imp. gal.) (city/hwy/combined)	(FWD, MTX) 10.4 (27)/ 7.3 (39)/9.0(31)
	(AWD, MTX) 10.8 (26) / 7.6 (37)/9.4(30)
	(FWD, 6-speed ATX) 10.6 (27)/ 7.6 (37)/9.3(30)
	(AWD, 9-speed ATX) 10.8 (26)/ 7.8 (36)/9.5(30)

Based on 2019 EnerGuide fuel consumption ratings. Government of Canada test methods used. Your actual fuel consumption will vary based on driving habits and other factors. For EnerGuide information, please visit the Government of Canada website: www.vehicles.nrcan.gc.ca

Towing	907 kg (2,000 lb.) (not recommended for FWD)
Engine Assembly Plant	Saltillo Engine Plant, Saltillo, Mexico

TRANSMISSION: 948TE NINE-SPEED AUTOMATIC

Availability	2.4-litre Tigershark engine with MultiAir2 (4x4)
Description	Planetary gear train, transverse layout
Ratio Spread	9.81
Gear Ratios	
1st	4.71
2nd	2.84
3rd	1.91
4th	1.38
5th	1.00
6th	0.81
7th	0.70
8th	0.58
9th	0.48
Reverse	3.81
Final-drive Ratio	3.734

C635 SIX-SPEED MANUAL TRANSMISSION

Availability	2.4-litre Tigershark engine with MultiAir2 (4x2)
Description	Planetary gear train, transverse layout
Gear Spread	6.635
Gear Ratios	
1st	4.459
2nd	2.508
3rd	1.556
4th	1.142
5th	0.852
6th	0.672
Final Drive Ratio	3.833

AT6 AISIN SIX-SPEED AUTOMATIC TRANSMISSION

Availability	2.4-litre Tigershark engine with MultiAir2 (4x2)
Description	Planetary gear train, transverse layout
Gear Spread	6.635
Gear Ratios	
1st	4.459
2nd	2.508
3rd	1.556
4th	1.142
5th	0.852
6th	0.672
Final Drive Ratio	3.502

4X4 SYSTEMS: JEEP ACTIVE DRIVE, JEEP ACTIVE DRIVE LOW

Availability	Jeep Active Drive is standard on all 4x4 models Jeep Active Drive Low is standard on Trailhawk
Type	Fully disconnecting 4x2 mode with automatic 4x4 engagement Full-time 4x4 mode with active on demand clutch
Operating Modes	Auto 4x2/4x4, neutral
Center Differential Type	None
Terrain Response	Unique tuning in all terrain modes
Crawl Ratio	20:1 (with Jeep Active Drive Low)

ELECTRICAL SYSTEM

Alternator	160-amp (2.4-litre Tigershark with MultiAir2)
Battery	Dual batteries when equipped with electronic stop-start system: 500-amp (primary) 150-amp (secondary) (2.4-litre Tigershark with MultiAir2 with engine stop-start)

SUSPENSION

Front	MacPherson strut, coil springs, flat front steel crossmember, high-strength steel double shell lower control stabilizer bar
Rear	Chapman strut, high-strength steel links, isolated steel rear cradle for 4x4 and not isolated for 4x2, coil springs, stabilizer bar

STEERING

Type	Electric power rack and pinion
Overall Ratio	15.7
Turning Diameter (curb-to-curb)	11.07 (36.3) 4x2 and 4x4

	10.76 (35.3) Trailhawk 4x4
Steering Turns (lock-to-lock)	2.68 (4x2 and 4x4)
	2.76 (Trailhawk 4x4)
BRAKES	
Front	
Size and type	305 x 28 (12 x 1.1) vented rotor with 60 (2.36) single-piston floating caliper
Swept area (per caliper)	895.3 sq cm (138.77 sq. in.), 1 x 60
	747.6 sq cm (.88 sq. in.), 1 x 57
Rear	
Size and type	278 x 112 (10.95 x 0.47) solid rotor with 1.5 (38) single-piston floating caliper
Swept area (per caliper)	656.4 sq cm (101.7 sq. in.), 1 x 38
Power-assist type	254 (10) vacuum assist
Four-wheel anti-lock brake system (ABS)	Standard
Electronic stability control (ESC)	Standard
Parking brake type	Electric motor
DIMENSIONS AND CAPACITIES	
Wheelbase	2,636 (103.8)
Track, Front	1,542 (60.7)
Track, Rear	1,532 (60.3)
Overall Length	4.394 (173)
Overall Width (with folded side mirrors)	1,874 (73.8)
Overall Width (with open side mirrors)	2,033 (80)
Overall Height	1,641 (64.6) without rails; 1,647 (64.8) with rails
Load-floor Height	754 (29.7) (height measured from curb ground to load floor)
Sill-step Height	494 (19.4) (height measured from curb ground to sill trim)
Ground Clearances	4x2 – 198 (7.8)
	4x4 – 208 (8.2)
	Trailhawk 4x4 – 216 (8.5)
Approach Angle (with air dam) (degrees)	4x2 15.8
	4x4 16.8
	Trailhawk 4x4 30.3
Breakover Angle (degrees)	4x2 21.8
	4x4 22.9

	Trailhawk 4x4 24.4
Departure Angle (degrees)	4x2 30.8 4x4 31.7 Trailhawk 4x4 33.6
Curb Weight (kg)	1,444 (3,184) 4x2 and 2.4-litre Tigershark with MultiAir2 1,509 (3,327) 4x4 and 2.4-litre Tigershark with MultiAir2 1,648 (3,633) Trailhawk 4x4 with 2.4-litre Tigershark with MultiAir2
Fuel-tank Capacity	51 litres (13.5 gal.)
ACCOMMODATIONS	
Seating Capacity — Front/Rear	2/3
Front Row	
Headroom without sunroof	995 (39.2)
Headroom with sunroof	981 (38.6)
Legroom	1,046 (41.8)
Shoulder room	1,439 (56.7)
Hip room	1,375 (54.1)
Seat travel	220 (8.7) fore/aft travel range
Recliner range (degrees)	Manual/power recliner travel: 69 degrees Manual fold FWD recliner travel: 107.5 degrees
SAE volume (standard roof), litres (cu. ft.)	1,497.9 (52.9) front passenger volume
Second Row	
Headroom	978 (38.5)
Legroom	973 (38.3)
Shoulder room	1,400 (55.1)
Hip room	1,250 (49.2)
SAE volume, litres (cu. ft.)	1,322.3 (46.7) second-row passenger volume
Cargo Access	
Liftover height	792 (31.1) (height measured from curb ground to liftgate scuff trim)
Maximum cargo width at liftgate opening	1,069 (42.1)
Minimum cargo width at liftgate opening	938 (36.9)
Maximum cargo height at liftgate opening	691 (27.2)

Distance between wheelhouse interior trim	968 (38.1)
SAE Cargo Volume	
Rear seats up, litres (cu. ft.)	767.3 (27.2)
Rear seats folded, litres (cu. ft.)	1,693.3 (59.8)
EPA interior volume index, litres (cu. ft.)	3,587.7(126.7)
TIRES	
Availability	Standard — Sport 4x2, Sport 4x4
Size and type	215/65R16 BSW All-season
Mfr. and model	Continental CrossContact LX Sport or Kumho Crugen Premium
Revs per km (mile)	479 (770)
Availability	Standard — North 4x2, North 4x4
Size and type	225/60R17 BSW All-season
Mfr. and model	Kumho Crugen Premium or Firestone Destination LE2
Revs per km (mile)	466 (749)
Availability	Optional — Limited 4x4
Size and type	235/45R19 BSW All-season
Mfr. and model	Continental ContiProContact
Revs per km (mile)	476 (766)
Availability	Standard — Trailhawk
Size and type	215/65R17 OWL All-season
Mfr. and model	Falken WildPeak H/T
Revs per km (mile)	462,8 (744)
Availability	Optional — North, Limited
Size and type	225/55 R18 BSW All-season
Mfr. and model	Continental
Revs per km (mile)	462 (744)
Availability	Optional — North, Limited
Size and type	225/55 R18 BSW All-season

Mfr. and model	Yokohama
Revs per km (mile)	462 (744)