

## FCA Canada: 2021 Ram 1500 TRX SPECIFICATIONS

*Specifications are based on the latest product information available at the time of publication.*

*All dimensions are in millimetres (inches) unless otherwise noted.*

*All dimensions measured at curb weight with standard tires and wheels.*

### GENERAL INFORMATION

Vehicle Type	Crew Cab: 4x4
Assembly Plant	Sterling Heights Assembly Plant, Sterling Heights, Michigan, USA
EPA Vehicle Class	Standard Pickup

### BODY/CHASSIS

	4x4 — Longitudinal, front engine, transfer case, ladder-type frame, steel cab, double-wall steel pickup box
--	---

### ENGINE: 6.2-LITRE HEMI® SUPERCHARGED V-8

Type and Description	90-degree V-type, liquid-cooled
Displacement	(6,166 cu. cm) (376 cu. in.)
Bore x Stroke	103.9 x 90.9 (4.09 x 3.58)
Valve System	Pushrod-operated overhead valves, 16 valves with sodium-filled exhaust valves and hollow stem intake valves, 16 conventional hydraulic lifters, all with roller tips
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	Deep-skirt cast-iron block with cross-bolted main bearing caps, aluminum-alloy heads with hemispherical combustion chambers
Compression Ratio	9.5:1
Power (SAE J2723)	702 hp (523 kW) @ 6,100 rpm
Torque (SAE J2723)	650 lb.-ft. (882 Nm) @ 4,800 rpm
Max. Engine Speed	6,200 rpm (electronically limited)
Fuel Requirement	Premium 91 octane (R+M)/2 — required
Oil Capacity	6.6 litres (7.0 quarts)
Coolant Capacity	14.4 litres (15.0 quarts)
Factory Oil Fill	0W-40 Pennzoil Ultra synthetic

Emission Controls	Dual close-coupled two-way catalytic converters heated wide-range upstream and switching downstream O <sub>2</sub> sensors and internal engine features
Exhaust Type	Dual 76.2 mm (3-in.) straight-thru exhaust system with dual 127 mm (5-in.) Black tips
EnerGuide Fuel Economy L/100km (imp. mpg) (city/hwy/combined)	22.4 city / 16.5 highway / 19.8 combined (13/17/14)
Assembly Plant	Saltillo Engine Plant, Saltillo, Mexico

#### **TRANSMISSION: TORQUEFLITE 8HP95 EIGHT-SPEED AUTOMATIC**

Availability	Standard with 6.2-litre HEMI supercharger V-8
Description	Adaptive electronic control with full manual control via gear selector or paddle shifters with six TRX-unique selectable modes: Sport, Snow, Tow, Mud, Baja and Auto (features performance shifting and gear holding feature)
Gear Ratios	
1st	4.71
2nd	3.14
3rd	2.11
4th	1.67
5th	1.29
6th	1.00
7th	0.84
8th	0.67
Reverse	3.30
Final Drive Ratio	2.62
Overall Top Gear	1.76
Axle Ratios	3.55

#### **TRANSFER CASE: BW 48-13 FULL-TIME**

Availability	6.2-litre HEMI supercharged V-8 4x4
Shift Mechanism	Electric
Available Speeds	Two-speed
Operating Modes	4WD Auto, 4WD High, Locked; Neutral; 4WD Low, Locked
Torque Split, Front/Rear	Variable – 40/60 Auto, 45/55 Snow, 45/55 Tow, 30/70 Sport, 25/75 Baja, 45/55 Mud/Sand and 50/50 Rock (in 4L)
Low-range Ratio	2.64
Centre Differential Type	None

## AXLES

Front	215 (8.5)
Rear	256 (10.1) Dana 60 with available open, limited slip or electronic locking differential
Available Ratios	3.55

## ELECTRICAL SYSTEM

Architecture	Powernet
Alternator	250-amp
Battery	H7 AGM 80AH 800CCA

## SUSPENSION

Front	Upper and lower A-arms, coil springs, Bilstein e2 Blackhawk active performance shock absorber
Rear	Five-link with track bar, coil springs, Bilstein e2 Blackhawk active damping twin-tube performance shock absorbers, solid axle

## BRAKES

Front	
Size and Type	378 x 30 (15 x 1.2) inverted hat (outboard venting) rotors with 57 mm (2.2 in.) two-piston pin-slider caliper and anti-lock braking system (ABS)
Swept Area	3,184 sq.cm (493.6 sq.in.)
Rear	
Size and Type	375 x 22 (15 x 0.87) disc with 57 mm (2.2 in.) single-piston pin-slider caliper and ABS
Swept Area	2,371.9 sq.cm (367.6 sq.in.)
Power-assist	Dual-rate, tandem diaphragm vacuum

## STEERING

Power assist	Electric power steering
--------------	-------------------------

## AIR BAGS

Crew Cab	6
----------	---

**CARGO BOX**

<b>NOMINAL BOX SIZE</b>	<b>5FT., 7IN. (CREW)</b>
SAE volume, litres (cu. ft.)	1,679 (53.9)
Length-at-Floor, Tailgate Closed	1,711 (67.4)
Cargo Width	1,687 (66.4)
Distance Between Wheelhouses	1,295 (51.0)
Depth	543 (21.4)
Tailgate Opening Width	1,525 (60.0)

**EXTERIOR DIMENSIONS****CREW CAB PICKUP**

<b>MODEL – TIRE SIZE</b>	<b>4x4 – 325/65/R18</b>
<b>BOX LENGTH</b>	<b>5ft., 7in.</b>
Wheelbase (nominal)	3,686 (145.1)
Track, Front	1,892 (74.5)
Track, Rear	1,882 (74.1)
Overall Length	5,916 (232.9)
Overall Width	2,235 (88)
Overall Height	2,055 (80.9)

**GROUND CLEARANCE**

Front Axle	238.8 (9.4)
Rear Axle	203.2 (8.0)
Open Tailgate to Ground	967 (38.1)
Approach Angle, degrees	30.2
Departure Angle, degrees	23.5
Ramp Breakover Angle, degrees	21.9
Ground Clearance With Skid Plate	299.7 (11.8)
Fuel Tank Capacity	125-litre (33-U.S. gal.) (standard)

## INTERIOR DIMENSIONS

### ACCOMMODATIONS

MODEL	CREW CAB
Seating Capacity, F/R	2/3
FRONT	CREW CAB
Headroom	1,038 (40.9)
Legroom	1,040 (40.9)
Shoulder Room	1,676 (66.0)
Hip Room	1,610 (63.4)
Seat Travel	220 (8.7)
Recliner Range (degrees)	Total travel 71 degrees (from full forward) 18 degrees forward (from design) 53 degrees rearward (from design)
REAR	CREW CAB
Headroom	1,011 (39.8)
Legroom	1,147 (45.2)
Shoulder Room	1,670 (65.7)
Hip Room	1,611 (63.4)

### INTERIOR VOLUME

	CREW CAB
Front – litres (cu. ft.)	1,809 (63.9)
Rear – litres (cu. ft.)	1,940 (68.5)

### MEASUREMENT

	TRX 4WD
Wheelbase (nominal)	3685.5 (145.1)
Overall Ratio	16.3:1
Steering Wheel Turns (lock-to-lock)	3.1
18-in. Wheel Turning Diameter (m / ft. )*	14.7/ 48.3

\* = Curb-to-curb turning diameter is measured at the outside of the tires at curb height. Turning diameters and steering wheel turns, lock-to-lock may differ with optional tires and wheels.

• • •

Additional information and news from FCA Canada Inc. are available at <http://fcamedia.ca/>