LEGEND: S=Standard, O=Optional, P=Package, — = Not available

Complete package information is listed at the end of the Feature Availability section.

NOTE: Information shown is correct at time of publication, and is subject to change without notice.

## 2007 Chrysler Crossfire **FEATURE AVAILABILITY**

	Coupe	Coupe Ltd.	Roadster	Roadster Ltd.
EXTERIOR				
Colors				
Black	S	_	S	_
Inferno Red Crystal Pearl Coat	_	0	Ρ	0
Aero Blue Pearl Coat, Black, Bright Silver Metallic, Machine Gray Crystal				
Pearl Coat, Oyster Gold Crystal Metallic, Sapphire Silver Metallic	_	0	_	0
Classic Yellow	_	_	_	0
Back Light—Heated, glass	_	_	S	S
Badges—Chrysler wing, hood and liftgate	S	S	S	S
Badge—"Crossfire," liftgate	S	S	S	S
Mold-in-color Black Bracket—Front license plate	S		S	_
Mold-in-color Gray Metallic Bracket—Front license plate		S	_	S
Door Handles—Body-color Black	S		S	_
Door Handles—Satin Silver	_	S	Ρ	S
Engine Cover—Mold-in-color Black	S	_	S	_
Engine Cover—Satin Silver painted	_	S	_	S
Exhaust Tips—Dual, center-mounted	S	_	S	_
Exhaust Tips—Dual bright, center-mounted		S	_	S
Fabric Top—Power, convertible		_	S	S
Fascias—Body color	S	S	S	S
Fuel Filler Door—Locking		S	S	S
Grilles, Upper, Lower—Mold-in-color Black	S		S	
Grilles, Upper, Lower—Mold-in-color Gray Metallic	_	S	_	S
Lighting				
Daytime running lamps (Canada only)	S	S	S	S
Headlamps—Halogen projector	S	S	S	S
Lamp—Center hi-mount stop	S	S	S	S
Fog lamps	_	S	_	S
Mirrors—Exterior—Dual Power Fold-away	S	_	S	_
Mirrors—Exterior—Dual Heated Power Fold-away	_	S	_	S
Monotone Paint		S	S	S
Side Louvers—Body-color Black	S	_	S	_
Side Louvers—Satin Silver	_	S	Р	S
Spoiler—Rear, active aerodynamic				
automatic and manual operation	S	S	S	S
Tonneau Cover – Full power, hard	_	_	S	S
Tow Hooks	S	S	S	S
Windows—Tinted glass	S	S	S	S
Windshield Glass—Tinted	S	S	S	S
Windshield Molding—Body-color Black	S	_	S	_
Windshield Molding—Satin Silver	_	S	_	S
Windshield Washer	S	_	S	_

Windshield Washer—Heated nozzlesWindshield Wipers—Intermittent	_ S	S S	_ s	S S
	Coupe	Coupe Ltd.	Roadster	Roadster Ltd.
INTERIOR				
Air Conditioning—Dual zone semi-automatic temperature control		S	S	S
Air Filtering—Electrostatic	_	S	_	S
Carpet—Floor and cargo area	_	_	_	_
Dark Slate Gray	S	S	S	S
Cigar Lighter	_		_	
Black finish		_	S	_
Satin Silver finish	_	S	_	S
Colors	0	_	_	_
Dark Slate Gray monotone	S	0	S	0
Dark Slate Gray and Cedar two-tone, Dark Slate Gray and Medium Slate		_		_
Gray two-tone, Dark Slate Gray monotone	_	0	_	0
Dark Slate Gray and Cool Vanilla two-tone	_ S		_	0
Console with Cubby Bin and Storage Compartment			S	_
Console with Cup Holders and Storage Compartment		S S	_ S	S S
Defroster—Rear window  Door Trim Panels	3	3	3	3
	S	_	S	
Soft, with map pockets, Black trim ringsSoft, with map pockets Satin Chrome trim rings		s	3	s
Floor Moto	_	S	_	S
Floor Mats	_	S		S
Garage Door Opener—Universal Glove Box—Locking	s	S	s	S
Instrument Cluster—Tachometer, speedometer	3	3	3	3
160-mph primary scale (U.S.)	S	s	S	S
260-kph primary scale (Canada)	S	S	S	S
Lamps	J	J	J	J
Cargo compartment	S	S	S	S
Front courtesy/map		S	S	S
Glove box		S	S	S
Mirror—Rearview, day/night		s	S	S
Pedals—Black rubber		_	S	_
Bright sport	_	S	P	S
Power Accessory Delay	S	S	S	S
Scuff Pads—Door Sill				
Mold-in-color Black	S	_	S	_
Bright stainless "Crossfire" inserts		S	_	S
Seat Adjusters				
Manual with driver height adjustment	S	_	S	_
Power—Eight-way driver; four-way passenger	_	S	_	S
Seats				
Cloth, low-back buckets with child seat anchor system (LATCH ready)	S	_	S	
Leather-trimmed high-back buckets; heated; with Child Seat				
Anchor System (LATCH ready)		S	_	S
Anchor System (LATCH ready)Sound Insulation: Hood silencer, Premium Insulation Group	_	S	Ρ	S
Sound System				
Amplifier—240-watt		S	_	S
Antenna—Integrated in rear window		S	_	_
Radio—AM/FM compact disc			S	S
Radio—Infinity Modulus AM/FM/CD with GPS navigation	_		_	0
Speakers—Six, Infinity® with dual subwoofers	_	S	_	S
Four standard door speakers	S	_	S	_
Steering Column—Telescoping	S	S	S	S

Steering Wheel—Leather-wrapped	S	S	S	S
Storage Pockets	_	S	_	S
Sun Visors with Covered Vanity Mirror	S	S	S	S
Warning—Low washer fluid	S	S	S	S
Windows—Power, driver and passenger w/one-touch auto down		S	S	S
, 1 5				
	Coupe	Coupe	Roadster	Roadster
		Ltd.		Ltd.
POWERTRAIN, CHASSIS, ELECTRICAL				
3.2-liter V-6 engine—SOHC 18-valve		S	S	S
Battery—510 CCA	S	_	S	_
Battery—700 CCA	_	S	_	S
Brakes—Anti-lock four-wheel disc		S	S	S
Emissions—Ultra-low emission vehicle U.S. 50-state	S	S	S	S
Fuel Tank—15.85 gallons	S	S	S	S
Engine Cover—Mold-in-color Black	S	_	S	_
Engine Cover—Satin Silver painted	_	S	_	S
Overall Top Gear Ratio—2.7	S	S	S	S
Stabilizer Bar—Front and rear		S	S	S
Steering—Power		S	S	S
Suspension—Touring		S	Š	S
Tire Fit System	_	_	_	_
Air compressor				
Can—Tire fit sealant	S	S	S	S
Tires	O	U	O	O
Continental SportContact 2				
	0		S	0
Front—225/40ZR18 Rear—255/35ZR19	S S	_	S	S S
	3	_	3	3
Ultra-high performance Michelin Pilot Sport 2®		0		
Front—225/40ZR18	_	S S	_	_
Rear—255/35ZR19	_	5	_	_
Continental All-Season Performance	_	_	_	•
Front—225/40ZR18		0	0	0
Rear—255/35ZR19		0	0	0
Tire Pressure Monitoring	_	S	_	S
Transmission	_	_	_	0
Six-speed manual		S	S	S
Five-speed automatic with Auto Stick	_	0	Р	0
Wheels	_	_	_	_
Front—18-inch aluminum		S	S	S
Rear—19-inch aluminum	S	S	S	S
	•	•	<b>5</b>	<b>5</b> 1.
	Coupe	Coupe Ltd.	Roadster	Roadster Ltd.
SAFETY AND SECURITY		LIG.		Liu.
Air Bags				
Multi-stage driver front	S	S	S	S
Next generation passenger front	S	S	S	S
Side—Driver and passenger supplemental, door-mounted		S	S	S
Knee airbags for both driver and passenger		S	S	S
Electronic Stability Program (ESP)	_ S	S	S	S
Brake Assist	S	S	S	S
		S	S	S
Horns—Electric, dual-note		S	S	S
Night Security Illumination		S	S	S
Illuminated Entry				
Keyless Entry	S	S	S	S
Locks—Power auto central locking		S	S	S
Occupant Classification System (OCS), front passenger seat		S	S	S
Seat Belt Pretensioners, driver and passenger	S	S	S	S

Seat Belt Retractors, constant force, driver and passenger Security Alarm—Premium Sentry Key® Theft Deterrent System Speed Control Tire Pressure Monitoring Warning Traction Control—All-speed	s s s s   s	S S S S S S	s s s s   s	
EQUIPMENT GROUPS The Special Edition package is offered with an automatic transmission and is exclusively available with an Inferno Red Crystal Pearl Coat exterior paint. Inside, Dark Slate Gray cloth seats are featured, while SRT6-style cast-aluminum wheels, a Black windshield surround and Satin Silver door handles and hallmark side louvers grace the exterior of Special Edition Package cars	_	_	Р	_
SPECIFICATIONS All dimensions are in inches (millimeters) unless otherwise noted.				
GENERAL INFORMATION				
Body Style Spo Assembly Plant	rt Cou Osn	ipe an abrück	d Roa	dster
EPA Vehicle Class	OSII	abiucr	t, Gen Two-s	eater
ENGINE				
Type and Description 90-degree bank angle, liquid-cooled	with (	_ <b>3.z</b> - dual-tu	ined ir	ntake
			vin ign	
Displacement195				
Bore x StrokeSOHC, two intake valves and one exhaust valve per cylir	3.54 )	(3.31	(89.9)	x 84)
Fuel InjectionSequentia				
Construction High-pressure die-cast aluminum alloy block with	Silite	c allo	, cicci / liners	and
cast	alumi	num a	lloy he	eads
Compression Ratio			1	0.0:1
Power (SAE net) 215 hp (160 kW) @ 9				
Torque (SAE net)				
Fuel Requirement Unleaded premiur				
Oil Capacity8.5				
Coolant Capacity		11.8	qt. (1	1.2L)
Emission Controls Three-way catalytic converters and inte	rnal e	ngine	featur	es(a)
Max. Gross Trailer Weight	N		omme	
Estimated EPA Fuel Economy mpg (City/Hwy) 17/25—mai	nual, 2	21/28–	–autor	matic
(a) Meets ULEV 1 requirements for CA, NY, MA, ME and VT; meets Tier 2, Bin 5 for all Meets Stage IV emission requirements in Europe.	other	states.		
TRANSMISSIONS				
MANUAL SIX-SPEED OVERDRIVE		-11.4		
Description Synchroniz Gear Ratios	ed in	all for	ward g	jears
1st				
2nd			4	1.459
				1.459 2.614
3rd			2	
3rd4th			2 1 1	2.614 .723 .245
4th 5th			2 1 1	2.614 .723 .245 .000
4th			2 1 1	2.614 .723 .245 .000

Final DriveOverall Top Gear	
Overall Top Geal	2.17
${\bf AUTOMATIC,FIVE\text{-}SPEEDOVERDRIVE}$	
	otive electronic control and lockup torque converter clutch
	1.8
Gear Ratios	
1st	3.95
	2.423
	1.486
	1.00
	0.833
	3.147, 1.93
	3.27
	2.74
Electrical System	
Alternator	120-amp
Battery	Group 48, maintenance-free, 510 or 700 CCA
DIMENSIONS AND CAPACITIES(a)	
Wheelbase	94.5 (2400)
Track, Front	58.8 (1493)
	59.1 (1502)
Overall Length	159.8 (4058)
Overall Width	
Overall Height	Coupe, 51.5 (1307), Roadster, 51.8 (1315)
Ground Clearance	
	3,010 lbs. (1365 kg)—Coupe
	3,061 lbs. (1388 kg)—Coupe Limited, manual;
	3,084 lbs. (1399 kg)—Coupe Limited, automatic;
	3,089 lbs. (1401 kg)—Roadster;
	3,140 lbs. (1424 kg)—Roadster Limited, manual;
	3,174 lbs. (1440 kg)—Roadster Limited, automatic
Weight Distribution % F/R	54/46—Coupe
vvoigne blothbation, 70 i 710	53/47—Roadster
Cargo Canacity (NAFTA)	115 lbs. (52 kg)
Frontal Area	
Tional Alea	20.62 sq. ft. (1.916 sq. m)—Roadster
Drag Coefficient	
Drag Coefficient	0.370—Coupe 0.384—Roadster
Fuel Tank Capacity	15.9 gal. (60L)
(a) All dimensions measured at curb weight in ir	
(a) All differsions measured at curb weight in it	iones (mm) unless otherwise specified.
ACCOMMODATIONS	
Seating Capacity	2
Front	
Head room	36.9 (936)—Coupe
	37.3 (948)—Roadster
Leg room	42.7 (1085)
Shoulder room	52.7 (1338)
	53.3 (1354)
	7.ô (194)
	48.0 cu. ft. (1.36 cu. m)—Coupe
	48.6 cu. ft. (1.37 cu. m)—Roadster
Cargo Volume Index	
<u> </u>	6.5 cu. ft. (190L) with top up—Roadster;
	3.6 cu. ft. (104L) with top down—Roadster
	5.5 52. In (10 12) that top down intoductor

BODY	
Layout	Longitudinal front engine, rear-wheel driv
	Unitized steel boo
	Manual liftgate/deck lie
SUSPENSION	
	Upper and lower "A" arm independent with coil springs, gas-charged shoo
	absorbers and stabilizer ba
Rear	Five-link independent with coil springs, link-type stabilizer ba
	and gas-charged shock absorber
STEERING	
	Power recirculating ba
= -	1 6Wel recirediating 58
Turning Diameter	10/1.
	32.2 ft. (9.8 m
	34.8 ft. (10.6 m
	lock) 3.
TIRES(a)	
Standard	
Mfr. and model	Michelin Pilot Sport 2—Coupe Limited
	Continental SportContact 2—Coupe, Roadster & Roadster Limited
Size and type	225/40ZR18—front, 255/35ZR19—rea
Revs per mile (km)	818 (509)—front, 787 (489)—rea
(a) Other sizes and brands	may also be used.
WHEELS	
Standard	
Type and material	Cast-aluminur
	All models: 18 x 7.5—front, 19 x 9—rea
BRAKES	
Front	
	11.8 x 1.1 (300 x 28) vented discs with 2.25 (57) diamete
71	single-piston sliding calipers and AB
Swept area	281.2 sq. in. (1814 sq. cm
Rear	
Size and type	10.9 x 0.35 (278 x 9) disc with 1.42 (36) diameter
	opposed-piston caliper and AB
Swept area	219.6 sq. in. (1417 sq. cm
Davis Assist Time	7/8" Tandem diaphragm vacuur