LEGEND: S=Standard, O=Optional, P=Package, — = Not available

Complete package information is listed at the end of the Feature Availability section.

NOTE: Information shown is correct at time of publication, and is subject to change without notice.

2007 Chrysler Town & Country FEATURE AVAILABILITY

	Town & Country		LWB	LWB
EVTEDIOD	SWB	LX	Touring	Limited
EXTERIOR	c	s	S	c
Air Dam, Front	S	3	3	S
Badges Charaler wing, grille	0	0	6	6
Chrysler wing, grille		S S	S S	S S
"Town & Country" on liftgate			5	5
"LX" on liftgate		S	_	_
"Limited" on liftgate	_	_	S	_
"Touring" on liftgate	_	_	_	S
Colors				
Bright Silver Metallic, Inferno Red Tinted Pearl Coat, Modern Blue				
Pearl Coat, Stone White, Marine Blue Pearl Coat, Magnesium Pearl Coat,				
Linen Gold Metallic, Brilliant Black Crystal Pearl Coat, Cognac Crystal	_	_	_	_
Clear Coat	0	О	0	0
Cladding—Lower bodyside, body color (P2)	_	_	Р	S
Door Handles, Body color	S	S	S	S
Doors				
Manual driver and passenger sliding doors	S	S	_	_
Power driver and passenger-side sliding doors (included with				
side-curtain air bags)	_	S	S	S
Power passenger sliding door	0	_	_	_
Fascias				
Body color, front and rear	S	S	S	_
Body color/chrome, front and rear (P2)	_	_	Р	S
Scuff pad, rear	S	S	S	S
Fog Lamps (P2)	_	_	Р	S
Glass—Sunscreen	S	S	S	S
Headlamps—Halogen	S	S	S	S
Automatic (P2)			Ρ	S
Headlamps off time delay	S	S	S	S
License Plate Brow—Bright		S	S	S
Liftgate—Power	_	_	S	S
Mirrors				
Foldaway	S	_	_	_
Foldaway, power, heated (P3)	Р	S	S	S
Foldaway, power, heated, driver memory				S
Moldings				
Bodyside, body color	_	S		_
Bodyside, body color w/chrome insert			S	
Bodyside, accent color	S	_	_	_
Spat, black	S	S	S	_
Roof Rack, Black (P3, P4)		P	S	_
Buffed stainless steel rails and crossbars	<u>.</u>	_	_	S
2454 5.4111000 51001 14110 4114 515555410				9

Windshield Wipers—Variable intermittent	_ s s	_ s s	0 S S	0 S S
INTERIOR				
Assist Handles—Passenger	_	S	S	S
Bezel, Instrument Panel				
Woodgrain		S	_	_
Woodgrain/Silver	_	_	_	S
Satin Silver	_	_	S	_
Climate Controls		0		
Air conditioning—Manual temperature control	S O	S	_	_
Air conditioning with dual-zone manual temperature control rear air	O	_	_	_
conditioning and heat ducts (P4)	_	Р	S	_
Air conditioning with three-zone automatic temperature control and		•	O	
rear air conditioning and heat ducts (P4)	_	_	Р	S
Air filtration		_	_	S
Cargo Net(s)				_
One front	S	_	_	_
One front, two rear		S	S	S
Consoles				
Center console between front seats (removable)		_	0	S
Instrument panel, lower open bin	S	S	S	S
Overhead with trip computer, compass, outside temperature display,				
storage includes Electronic Vehicle Information Center (EVIC)				
in Limited (P3, P4)		Ρ	S	S
Defroster—Rear window, electric		S	S	S
Door Locks—Power	S	S	S	S
Door Trim	_	_	_	
Vinyl with map pocket	S	S	S	_
Luxury	_	_	_	S
Floor Covering		0	_	
	S			
Carpets, passenger and cargo area, 12 oz.		S	S	_
Carpets, full-length, 18 oz.	_	_	_	S
Carpets, full-length, 18 ozFloor mats—Front, intermediate and rear	_ S	<u>S</u>	- S	_
Carpets, full-length, 18 ozFloor mats—Front, intermediate and rear	_ S	_ s _	_ s _	_ s
Carpets, full-length, 18 oz	 S P	 S P	_ S _ S	_ s s
Carpets, full-length, 18 oz	_ S	_ s _	_ s _	_ s
Carpets, full-length, 18 oz			_ s _ s s	
Carpets, full-length, 18 oz		 S P	S S P	_ s s
Carpets, full-length, 18 oz. Floor mats—Front, intermediate and rear Luxury floor mats—Front and rear Garage Door Opener—HomeLink® universal transceiver (P3, P4) Grocery Bag Hooks Instrument Cluster Electroluminescent (P2) Silver face with tachometer			_ s _ s s	
Carpets, full-length, 18 oz. Floor mats—Front, intermediate and rear Luxury floor mats—Front and rear Garage Door Opener—HomeLink® universal transceiver (P3, P4) Grocery Bag Hooks Instrument Cluster Electroluminescent (P2) Silver face with tachometer White face			S S P	- s s s - -
Carpets, full-length, 18 oz. Floor mats—Front, intermediate and rear Luxury floor mats—Front and rear Garage Door Opener—HomeLink® universal transceiver (P3, P4) Grocery Bag Hooks Instrument Cluster Electroluminescent (P2) Silver face with tachometer White face Illuminated Entry			_ S _ S _ P _ S	
Carpets, full-length, 18 oz. Floor mats—Front, intermediate and rear Luxury floor mats—Front and rear Garage Door Opener—HomeLink® universal transceiver (P3, P4) Grocery Bag Hooks Instrument Cluster Electroluminescent (P2) Silver face with tachometer White face Illuminated Entry Lamp(s)	S P S S S		_ S _ S _ P _ S	s s s s s
Carpets, full-length, 18 oz. Floor mats—Front, intermediate and rear Luxury floor mats—Front and rear Garage Door Opener—HomeLink® universal transceiver (P3, P4) Grocery Bag Hooks Instrument Cluster Electroluminescent (P2) Silver face with tachometer White face Illuminated Entry Lamp(s) Door courtesy	S P S S S		_ S _ S _ P _ S	- s s s - -
Carpets, full-length, 18 oz. Floor mats—Front, intermediate and rear Luxury floor mats—Front and rear Garage Door Opener—HomeLink® universal transceiver (P3, P4) Grocery Bag Hooks Instrument Cluster Electroluminescent (P2) Silver face with tachometer White face Illuminated Entry Lamp(s)	S P S S S S	S P S S S	S S S P S S S	
Carpets, full-length, 18 oz. Floor mats—Front, intermediate and rear Luxury floor mats—Front and rear Garage Door Opener—HomeLink® universal transceiver (P3, P4) Grocery Bag Hooks Instrument Cluster Electroluminescent (P2) Silver face with tachometer White face Illuminated Entry Lamp(s) Door courtesy Flood, liftgate	S P S S S S S	S P S S S	0 00 P 0 0 0 0	
Carpets, full-length, 18 oz. Floor mats—Front, intermediate and rear Luxury floor mats—Front and rear Garage Door Opener—HomeLink® universal transceiver (P3, P4) Grocery Bag Hooks Instrument Cluster Electroluminescent (P2) Silver face with tachometer White face Illuminated Entry Lamp(s) Door courtesy Flood, liftgate Front courtesy/map	S P S S S S S	S P S S S S S	0 00	
Carpets, full-length, 18 oz. Floor mats—Front, intermediate and rear Luxury floor mats—Front and rear Garage Door Opener—HomeLink® universal transceiver (P3, P4) Grocery Bag Hooks Instrument Cluster Electroluminescent (P2) Silver face with tachometer White face Illuminated Entry Lamp(s) Door courtesy Flood, liftgate Front courtesy/map Map/dome reading (included with overhead console) Rear courtesy/reading Rear dome	S P S S S S S S	S P S S S S S P P S	0 00 P0 0 0 00	
Carpets, full-length, 18 oz. Floor mats—Front, intermediate and rear Luxury floor mats—Front and rear Garage Door Opener—HomeLink® universal transceiver (P3, P4) Grocery Bag Hooks Instrument Cluster Electroluminescent (P2) Silver face with tachometer White face Illuminated Entry Lamp(s) Door courtesy Flood, liftgate Front courtesy/map Map/dome reading (included with overhead console) Rear courtesy/reading Rear dome Light—Overhead ashtray/cup holder (P2, P3, P4)	S P S S S S S S	S P S S S S S P P	0 00	
Carpets, full-length, 18 oz. Floor mats—Front, intermediate and rear Luxury floor mats—Front and rear Garage Door Opener—HomeLink® universal transceiver (P3, P4) Grocery Bag Hooks Instrument Cluster Electroluminescent (P2) Silver face with tachometer White face Illuminated Entry Lamp(s) Door courtesy Flood, liftgate Front courtesy/map Map/dome reading (included with overhead console) Rear courtesy/reading Rear dome Light—Overhead ashtray/cup holder (P2, P3, P4) Memory System (includes memory settings for radio, driver's seat,	S P S S S S S S P	S P S S S S S P P S	0 00 P0 0 0 00	SSS
Carpets, full-length, 18 oz. Floor mats—Front, intermediate and rear Luxury floor mats—Front and rear Garage Door Opener—HomeLink® universal transceiver (P3, P4) Grocery Bag Hooks Instrument Cluster Electroluminescent (P2) Silver face with tachometer White face Illuminated Entry Lamp(s) Door courtesy Flood, liftgate Front courtesy/map Map/dome reading (included with overhead console) Rear courtesy/reading Rear dome Light—Overhead ashtray/cup holder (P2, P3, P4) Memory System (includes memory settings for radio, driver's seat, driver-side exterior mirror and adjustable pedals)	S P S S S S S S P	S P S S S S S P P S	0 00 P0 0 0 00	
Carpets, full-length, 18 oz. Floor mats—Front, intermediate and rear Luxury floor mats—Front and rear Garage Door Opener—HomeLink® universal transceiver (P3, P4) Grocery Bag Hooks Instrument Cluster Electroluminescent (P2) Silver face with tachometer White face Illuminated Entry Lamp(s) Door courtesy Flood, liftgate Front courtesy/map Map/dome reading (included with overhead console) Rear courtesy/reading Rear dome Light—Overhead ashtray/cup holder (P2, P3, P4) Memory System (includes memory settings for radio, driver's seat, driver-side exterior mirror and adjustable pedals) Mirror	S P S S S S P	S P S S S S S P P S P	S SS PS S S SS P	sss s s ss ss P s
Carpets, full-length, 18 oz	S P S S S S S S P P	S P S S S S S P P S P P	S SS PS S S SS P P	SSS
Carpets, full-length, 18 oz. Floor mats—Front, intermediate and rear Luxury floor mats—Front and rear Garage Door Opener—HomeLink® universal transceiver (P3, P4) Grocery Bag Hooks Instrument Cluster Electroluminescent (P2) Silver face with tachometer White face Illuminated Entry Lamp(s) Door courtesy Flood, liftgate Front courtesy/map Map/dome reading (included with overhead console) Rear courtesy/reading Rear dome Light—Overhead ashtray/cup holder (P2, P3, P4) Memory System (includes memory settings for radio, driver's seat, driver-side exterior mirror and adjustable pedals) Mirror Auto-dimming rearview (P2) Day/night rearview	S P S S S S S S P P	S P S S S S S P P S P	S SS PS S S SS P	sss s s ss ss P s
Carpets, full-length, 18 oz	S P S S S S S S P P S	S P S S S S S P P S P P	S SS PS S S SS P P	sss s s ss ss P s

Pedals—Power adjustable	0	0	0	S
Power Outlets				
Front and rear, 12-volt	S	S	S	S
Auxiliary 12-volt in instrument panel	_	_	S	S
Seating, Front	_	_	_	
Low-back cloth bucket	S	S	S	_
Low-back leather bucket (P1)		_	Р	S
Heated front seats (P1)		_	Р	S
Lumbar adjustment, manual, driver seat	S	S	S	S
Power eight-way driver seat	O	0	S	S
Power six-way front passenger seat (P1)	_	_	Р	S
Seating, Intermediate and Rear	_			
Deluxe intermediate and rear bench	S	_	_	_
Intermediate bench seats with two integrated child seats	0	_	_	_
Easy Out® Roller Seats	S	_	_	_
Stow 'n Go® intermediate bucket seats with fold-in-floor and rear				
60/40 split-folding bench seat with fold-in-floor and tailgate		_	_	_
position feature	_	S	S	S
Second-row buckets with rear 50/50 split bench	0	_	_	_
Sound/entertainment/navigation Systems (CD/DVD,				
DVD-audio, DVD-R and DVD-RW playback)	_	_		
AM/FM stereo radio with CD player, four speakers		S	_	_
AM/FM stereo radio with cassette, CD player, six speakers (P4)	Р	Р	S	_
AM/FM stereo radio with navigation system, six-disc in-dash				
CD/DVD changer	_	_	0	S
AM/FM stereo radio with six-disc CD changer	0	_	0	_
SIRIUS Satellite Radio	0	0	0	0
UConnect® Hands-free Communications System with Bluetooth®		0	0	0
Steering wheel-mounted audio controls	_	_	S	S
Sound Insulation				
Deluxe		S	S	S
Hood pad		S	S	S
Speed Control	S	S	S	S
Steering Column—Tilt	S	S	S	S
Steering Wheel				
Leather-wrapped	_	_	S	S
Luxury		S	_	_
Sun Visors				
Driver and passenger vanity mirrors	S	_	_	_
Driver and passenger illuminated vanity mirrors (P3)	Р	S	S	S
Storage				
Drawer—Under front passenger seat, lockable (non-lockable if center				
console is selected)	S	S	S	_
Lower instrument panel storage bin (deleted with UConnect®)	S	S	S	S
Under-floor storage bins available when Stow 'n Go seats are in the				
upright position	_	S	S	S
Windows—Power front and rear quarter vents	S	S	S	S
POWERTRAIN/OUA COIO				
POWERTRAIN/CHASSIS				
3.3-liter V-6 engine with four-speed automatic transaxle and	•	_		
2.49 overall top gear ratio	S	S	_	_
3.8-liter V-6 engine with four-speed automatic transaxle and			_	_
2.37 overall top gear ratio	_	_	S	S
Alternator	_	_		
140-amp		S	_	_
160-amp (P7)	_	Р	S	S
Battery	_	_	_	_
500-amp		S	S	S
600-amp (P7)	_	Р	Р	Р

Brakes				
Power four-wheel disc		S	S	S
Power front disc/rear drum		_	_	_
Anti-lock brakes (ABS)	0	S	S	S
Drivetrain				
Front-wheel drive		S	S	S
Engine block heater	0	0	0	0
Fuel tank—20 gallons, with tethered cap	S	S	S	S
Steering—Power rack and pinion	S	S	S	S
Suspension				
Normal duty	S	S	S	S
Load-leveling and height control (P7)	_	Ρ	Ρ	Ρ
Tire Pressure Monitoring System			S	S
Tires				
Compact spare	S	S	S	S
215/70R15 BSW all-season		S	_	_
215/65R16 LBL all-season		_	S	S
Traction control—Low-speed	_	_	S	S
Wheels and Wheel Covers				
15-inch steel wheels with wheel covers	S	S	_	_
16-inch aluminum wheels	_	_	S	_
16-inch chrome-clad aluminum wheels	_	_	0	S
SAFETY AND SECURITY				
Brake-Park Interlock	S	S	S	S
Bumpers—Front and rear, 5-mph		S	S	S
Lower Anchors and Tethers for CHildren	O	U	J	J
(LATCH) child seat anchor system ready	S	S	S	S
Door Locks—Power	S	S	S	S
Headlamps-Off Time Delay		S	S	S
Horns, Electric Dual Note		S	S	S
Illuminated Entry System		S	S	S
Keyless Entry with Sentry Key Engine Immobilizer		S	S	S
ParkSense® Rear Backup System (P2)	_		P	S
Restraint Systems	_		Г	3
·				
Seat belts(a)				
Front: Three-point belts with shoulder belt height adjusters,	0		0	0
pretensioners, constant force retractors, and driver/passenger BeltAlert		S S	S S	S S
Intermediate: Three-point belts with shoulder belt height adjusters	S	S	S	
Rear: Three-point belts, outboard; lap belt, center	5	5	5	S
Air Bags				
Advanced multi-stage driver and front passenger with	•	_	•	_
Occupant Classification System (OCS)(b)(c)	S	S	S	S
Driver-side inflatable knee blocker	S	S	S	S
Supplemental Three-row Side-curtain Air Bags(a)(d)		0	0	0
Security Alarm (P2)	_	_	Р	S
Sliding Door Alert Warning	S	S	S	S
Tire Pressure Monitoring		S	S	S
Traction Control—Low-speed	_	_	S	S

Drokes

- (a) Certified to federal regulations that allow less forceful air bags. Always use seat belts. Remember, a back seat is the safest place for children.
- (b) Certified to the federal regulation for automatic passenger occupant classification. Always use seat belts. Children 12 and under should always be in a back seat correctly using an infant or child restraint system, or seat belt positioned correctly for the child's age and size.
- (c) The OCS determines the conditions for activation or deactivation of the passenger-side front air bag based upon the weight of the occupant. It may not activate the air bag if the occupant has incorrect seating posture or is moving in the seat. You should observe the air bag light to determine if the OCS is deciding properly. Passengers should sit properly in the seat with the seat belt fastened at all times.

(d) Always sit properly in the seat with the seat belt fastened. Always observe the passenger air bag indicator lamp to determine if the OCS classification is appropriate. Children 12 and under should always be in a back seat correctly using an infant or child restraint system or the seat belt positioned correctly for the child's age and weight.

PACKAGES					
P1 – Leather Interior Group—Includes leather-trimmed bucket seats, three-					
zone automatic temperature control, six-way power front passenger					
seat, heated front seats, Electronic Vehicle Information Center	_	_	0	_	
P2 – Luxury Group—Includes lower bodyside cladding (body color), removable	9				
center console, auto-dimming driver side exterior mirror, body					
color/chrome front and rear fascias, fog lamps, automatic headlamps,					
electroluminescent instrument cluster, auto-dimming rearview mirror,					
rear park assist, power adjustable pedals, security alarm, Infinity®					
speaker system, overhead rail system (delete credit when power					
sun roof is ordered)	_	_	0	_	
P3 – Popular Equipment Group I—Includes dual-zone manual temperature					
control, overhead console with trip computer, HomeLink garage					
door opener, foldaway power heated mirrors, overhead ashtray/cup					
holder light, roof rack, illuminated vanity mirrors, AM/FM stereo radio					
with cassette, CD player and six speakers	0	_	_		
P4 – Popular Equipment Group II—Includes three-zone manual temperature					
control, rear air conditioning with heater, 160-amp alternator, overhead					
console with trip computer, HomeLink garage door opener, silver					
face instrument cluster with tachometer, overhead ashtray/cup holder					
light, roof rack, AM/FM stereo radio with cassette, CD player and					
six speakers	_	0	_	_	
P5 –Rear Seat Video System—Includes second-row overhead seven-inch		O			
video screen, wireless infrared headphones, video remote control,					
overhead rail system (when ordered with power sun roof the					
overhead rail system is deleted)			0	0	
P6 – Trailer Tow Prep Group—Includes 160-amp alternator, 600-amp battery,		_	O	O	
engine oil cooler, heavy-duty transmission oil cooler, load leveling					
and height control, heavy-duty radiator, wiring harness		0	0	0	
P7 – Rear Entertainment Group—Second-row seven-inch overhead screen		O	O	O	
with six speakers, AM/FM/CD/DVD Video Audio MP3 radio and					
remote control	0				
Tomoto control	•				
Legend: S = Standard O = Optional P = Available within package or group noted in pare	nthese	es — =	Not a	vailable O	/P =
Available as stand alone option or as part of package/group)					
NOTE: The information shown here is preliminary and based on data available at the time	e of p	ublicat	ion.		
,					
SPECIFICATIONS					
All dimensions are in inches (millimeters) unless otherwise noted.					
7 il diffictiono die in mones (milimeters) diffesso differinse ficted.					
GENERAL INFORMATION					
Body Style			ose ve		
Assembly Plant Windsor, Ontario, Canada a	nd St	. Loui	s, Mis	souri	
EPA Vehicle Class	_ Mult	ipurpo	ose ve	hicle	
ENGINE: 3.3-LITER, OHV, 12-VALVE SMPI V-6					
	1 6/	MB or	nd LW	DIV	
AvailabilityStc Type and DescriptionSix-cylinder, 60					
			01 cu		
Bore x Stroke			9 (93 :		
Valve SystemOHV, 12 valves, roller follo					
Fuel Injection Sequentia					
Construction Cast-iron block,	aıumı	num a	-		
Compression Ratio				9.3:1	

	170 bhp (134 kW) @ 5,000 rpm (54.5 bhp/L)
Torque (SAE net)	200 lbft. (285 N•m) @ 4,000 rpm
Max. Engine Speed	5,600 rpm 87 octane (R+M)/2
Fuel Recommendation	87 octane (R+M)/2
Oil Capacity	4 qt. (3.8L) plus filter
Coolant Capacity	13.36 qt. (12.64L)—std.; 16.28 qt. (15.4L)—with rear heater
	Three-way catalytic converter, heated oxygen sensors,
	electronic EGR and internal engine features(a)
Max Gross Trailer Weight	2,000 lbs. (900 kg)—std.;
	,600 lbs. (1724 kg)—with optional Trailer Tow Preparation Group
	g (City/Hwy)19/26
ENGINE: 3.8-LITER, OHV, 12-VA	
Availability	
	Six-cylinder, 60° V-type, liquid-cooled
	3.78 x 3.43 (96 x 87)
Volvo Svotom	OHV, 12 valves, roller followers, hydraulic lifters
Valve System	Onv, 12 valves, folier followers, flydraulic lifters
Fuel Injection	Sequential, multi-port, electronic
Construction	Cast-iron block, aluminum alloy heads
Compression Ratio	9.6:1 200 bhp (153 kW) @ 5,200 rpm (54.5 bhp/L) Torque (SAE net)
Power (SAE net)	
	235 lbft. (325 N•m) @ 4,000 rpm
Max. Engine Speed	
	Unleaded regular, 87 octane (R+M)/2
Oil Capacity	4 qt. (3.8L) plus filter
	13.36 qt. (12.64L)—std.; 16.28 qt. (15.4L)—with rear heater
Emission Controls	Three-way catalytic converter, heated oxygen sensors,
	electronic EGR and internal engine features(a)
Max. Gross Trailer Weight	2,000 lbs. (900 kg)—std.;
FWD: 3	,800 lbs. (1724 kg)—with optional Trailer Tow Preparation Group
Estimated EPA Fuel Economy mpg	g (City/Hwy)18/25
(a) Moote Tior 2 Rin 5 (fodoral)	and LEV 2 (CA) emission requirements.
, ,	and LLV 2 (OA) emission requirements.
ELECTRICAL SYSTEM	
Alternator	160-amp, high-speed CA—std.; 600 CCA—included with Trailer Tow Preparation Group
Battery 500 C0	CA—std.; 600 CCA—included with Trailer Tow Preparation Group
TRANSAXLE: AUTOMATIC, FOU	R-SPEED OVERDRIVE
	aptive electronic control, electronically modulated converter clutch
Gear Ratios	aptive electronic control, electronically modulated converter clutch
	2.84
2nd	1.57
2nd 3rd	1.57 1
2nd 3rd 4th	1.57 1 0.69
2nd	1.57 1 0.69 3.3L—3.62, 3.8L—3.43
2nd	1.57 1 0.69
2nd	1.57 1
2nd	1.57 1
2nd	1.571
2nd	

Weight distribution, %F/R	58/42—Base
Frontal area	
Drag coefficient	
Fuel tank capacity	
Long Wheelbase LX, Touring and Limited	• , ,
Wheelbase	119.3 (3030)
Track, front	
Track, rear	
Overall length	
Overall width	
Overall height (without Roof Rails)	
Ground clearance	
Turning diameter (curb-to-curb)	
Weight (estimated)	4,239 lbs. (1923 kg)—LX;
	rring; 4,442 lbs. (2015 kg)—Limited
Weight distribution57/43—L	
Frontal area	
Drag coefficient	
Fuel tank capacity	
Tuertank capacity	20 gai. (75L)
(a) Meets Tier 2 Bin 5 (federal) and LEV 2 (CA) emission requirements. (b) All dimensions measured at curb weight with standard tires.	
ACCOMMODATIONS	
Short Wheelbase	
Seating Capacity, F/I/R	2/2/3
Front	
Head room	39.6 (1005)
Leg room	
Shoulder room	
Hip room	
Seat travel	8.6 (220)
Front volume index	55 0 ou ft (1 65 ou m)
Intermediate	55.9 cd. it. (1.65 cd. iii)
	20.7 (4007.5)
Head room	
Leg room	
Knee clearance	
Shoulder room	
Hip room	
Interior volume index	54.3 cu. ft. (1.53 cu. m)
Rear	
Head room	37.3 (948)
Leg room	
Knee clearance	
Shoulder room	61.9 (1574)
Hip room	49 (1246)
Rear Volume Index	43.2 cu. ft. (1.19 cu. m)
Interior Volume Index	161.3 cu. ft. (4.58 cu. m)
Cargo Volume Indexes	
Aft of second row seats	72.0 cu. ft. (2.04 cu. m)
Aft of third row seats	
Seats removed—max cargo	
Long Wheelbase LX, Touring and Limited with Stow 'n Go seatin	
Seating Capacity, F/I/R	
Front	2,2,0
Head room	39.6 (1005)
Leg room	
Shoulder room	
Hip room	
THP TOOTH	57.2 (1452)

Seat travel	8.6 (220)
Front volume index	58.2 cu. ft. (1.65 cu. m)
Recliner range	38°
Intermediate	
Head room	
Leg room	
Knee clearance	
Shoulder room	
Hip room	
Intermediate volume index	
Long Wheelbase LX, Touring and Limited with Stow 'n Go seatir Rear	ng and storage
	20.2 (072)
Head room	
Leg roomKnee clearance	
Shoulder room	
Hip room	
Rear volume index	
Interior volume index	
Cargo Volume Indexes	101.7 00.10 (1.00 00.10)
Aft of second row seats	85.9 cu. ft. (2.43 cu. m)
Aft of third row seat	
Seats stowed—max cargo (fold-in-the-floor)	144.2 cu. ft. (4.08 cu. m)
	,
SUSPENSION	armed about aboutbors soil aprions
Front ISO struts with integral gas-cha	
asymmetrical lower control arms, link-type stabi	olated cast-aluminum crossmember
Tubbet-isc	Dialed Cast-aluminum crossmember
RearRubber-isolated longitudinal sir	ada laaf anringa tuhular haam ayla
track bar and gas-charged shock absort	bers—std.; revised spring rates and
track bar and gas-charged shock absorl load-leveling shock absorbers—	
track bar and gas-charged shock absorbers—load-leveling shock absorbers—	bers—std.; revised spring rates and included in Trailer Tow Prep Group
track bar and gas-charged shock absorbers—load-leveling shock absorbers— STEERING Type	bers—std.; revised spring rates and included in Trailer Tow Prep Group Rack-and-pinion, power-assisted
track bar and gas-charged shock absorbers— load-leveling shock absorbers— STEERING Type Overall Ratio	bers—std.; revised spring rates and included in Trailer Tow Prep Group Rack-and-pinion, power-assisted 17.8:1
track bar and gas-charged shock absorbers— load-leveling shock absorbers— STEERING Type Overall Ratio Turning Diameter (curb-to-curb)	bers—std.; revised spring rates and included in Trailer Tow Prep Group Rack-and-pinion, power-assisted 17.8:1 39.4 ft. (12.0 m)
track bar and gas-charged shock absorbers— load-leveling shock absorbers— STEERING Type Overall Ratio Turning Diameter (curb-to-curb) Steering Turns (lock-to-lock)	bers—std.; revised spring rates and included in Trailer Tow Prep Group Rack-and-pinion, power-assisted 17.8:1 39.4 ft. (12.0 m)
track bar and gas-charged shock absorbers—load-leveling shock absorbers—STEERING TypeOverall Ratio Turning Diameter (curb-to-curb) Steering Turns (lock-to-lock) TIRES	bers—std.; revised spring rates and included in Trailer Tow Prep Group Rack-and-pinion, power-assisted 17.8:1 39.4 ft. (12.0 m)
track bar and gas-charged shock absorbers— load-leveling shock absorbers— STEERING Type Overall Ratio Turning Diameter (curb-to-curb) Steering Turns (lock-to-lock) TIRES Standard—SWB and LX	bers—std.; revised spring rates and included in Trailer Tow Prep Group Rack-and-pinion, power-assisted 17.8:1 39.4 ft. (12.0 m) 3.14
track bar and gas-charged shock absorbers— STEERING Type Overall Ratio Turning Diameter (curb-to-curb) Steering Turns (lock-to-lock) TIRES Standard—SWB and LX Size and type 2	Ders—std.; revised spring rates and cincluded in Trailer Tow Prep Group Rack-and-pinion, power-assisted 17.8:1 39.4 ft. (12.0 m) 3.14
track bar and gas-charged shock absorbers— STEERING Type Overall Ratio Turning Diameter (curb-to-curb) Steering Turns (lock-to-lock) TIRES Standard—SWB and LX Size and type Mfr. and model	Ders—std.; revised spring rates and cincluded in Trailer Tow Prep Group Rack-and-pinion, power-assisted 17.8:1 39.4 ft. (12.0 m) 3.14 215/70R15 black sidewall all-season Goodyear Integrity
track bar and gas-charged shock absorbers— STEERING Type Overall Ratio Turning Diameter (curb-to-curb) Steering Turns (lock-to-lock) TIRES Standard—SWB and LX Size and type Mfr. and model Revs per mile (km)	Ders—std.; revised spring rates and cincluded in Trailer Tow Prep Group Rack-and-pinion, power-assisted 17.8:1 39.4 ft. (12.0 m) 3.14 215/70R15 black sidewall all-season Goodyear Integrity
track bar and gas-charged shock absorbers— STEERING Type Overall Ratio Turning Diameter (curb-to-curb) Steering Turns (lock-to-lock) TIRES Standard—SWB and LX Size and type Mfr. and model Revs per mile (km) Standard—Touring and Limited	Ders—std.; revised spring rates and cincluded in Trailer Tow Prep Group Rack-and-pinion, power-assisted 17.8:1 39.4 ft. (12.0 m) 3.14 215/70R15 black sidewall all-season Goodyear Integrity 780 (485)
track bar and gas-charged shock absorbers— STEERING Type Overall Ratio Turning Diameter (curb-to-curb) Steering Turns (lock-to-lock) TIRES Standard—SWB and LX Size and type Mfr. and model Revs per mile (km) Standard—Touring and Limited Size and type 26	Ders—std.; revised spring rates and cincluded in Trailer Tow Prep Group Rack-and-pinion, power-assisted 17.8:1 39.4 ft. (12.0 m) 3.14 Parallel State Sidewall all-season Goodyear Integrity 780 (485)
track bar and gas-charged shock absorbers— STEERING Type Overall Ratio Turning Diameter (curb-to-curb) Steering Turns (lock-to-lock) TIRES Standard—SWB and LX Size and type Mfr. and model Revs per mile (km) Standard—Touring and Limited Size and type Mfr. and model Size and type Mfr. and model	Ders—std.; revised spring rates and cincluded in Trailer Tow Prep Group Rack-and-pinion, power-assisted 17.8:1 39.4 ft. (12.0 m) 3.14 215/70R15 black sidewall all-season Goodyear Integrity 780 (485) 15/65R16 low-black letter all-season Bridgestone Turanza EL42
track bar and gas-charged shock absorbers— STEERING Type Overall Ratio Turning Diameter (curb-to-curb) Steering Turns (lock-to-lock) TIRES Standard—SWB and LX Size and type Mfr. and model Revs per mile (km) Standard—Touring and Limited Size and type Mfr. and model Revs per mile (km) Standard—Touring and Limited Revs per mile (km) Revs per mile (km)	Ders—std.; revised spring rates and cincluded in Trailer Tow Prep Group Rack-and-pinion, power-assisted 17.8:1 39.4 ft. (12.0 m) 3.14 215/70R15 black sidewall all-season Goodyear Integrity 780 (485) 15/65R16 low-black letter all-season Bridgestone Turanza EL42
track bar and gas-charged shock absorbers— STEERING Type Overall Ratio Turning Diameter (curb-to-curb) Steering Turns (lock-to-lock) TIRES Standard—SWB and LX Size and type Mfr. and model Revs per mile (km) Standard—Touring and Limited Size and type Mfr. and model Revs per mile (km) Standard—Touring and Limited Size and type Mfr. and model Revs per mile (km) WHEELS	Ders—std.; revised spring rates and cincluded in Trailer Tow Prep Group Rack-and-pinion, power-assisted 17.8:1 39.4 ft. (12.0 m) 3.14 215/70R15 black sidewall all-season Goodyear Integrity 780 (485) 15/65R16 low-black letter all-season Bridgestone Turanza EL42
track bar and gas-charged shock absorbers— STEERING Type Overall Ratio Turning Diameter (curb-to-curb) Steering Turns (lock-to-lock) TIRES Standard—SWB and LX Size and type Mfr. and model Revs per mile (km) Standard—Touring and Limited Size and type Mfr. and model Revs per mile (km) Standard—Touring and Limited Size and type Mfr. and model Revs per mile (km) WHEELS Standard—SWB and LX	Ders—std.; revised spring rates and included in Trailer Tow Prep Group Rack-and-pinion, power-assisted 17.8:1 39.4 ft. (12.0 m) 3.14 Parallel State Sidewall all-season Goodyear Integrity 780 (485) 15/65R16 low-black letter all-season Bridgestone Turanza EL42 778 (483)
track bar and gas-charged shock absorbers— STEERING Type Overall Ratio Turning Diameter (curb-to-curb) Steering Turns (lock-to-lock) TIRES Standard—SWB and LX Size and type	Ders—std.; revised spring rates and cincluded in Trailer Tow Prep Group Rack-and-pinion, power-assisted 17.8:1 39.4 ft. (12.0 m) 3.14 Parallel Stamped-steel Stamped-steel
track bar and gas-charged shock absorbers— STEERING Type Overall Ratio Turning Diameter (curb-to-curb) Steering Turns (lock-to-lock) TIRES Standard—SWB and LX Size and type	Ders—std.; revised spring rates and cincluded in Trailer Tow Prep Group Rack-and-pinion, power-assisted 17.8:1 39.4 ft. (12.0 m) 3.14 Parallel Stamped-steel Stamped-steel
track bar and gas-charged shock absorbers— STEERING Type Overall Ratio Turning Diameter (curb-to-curb) Steering Turns (lock-to-lock) TIRES Standard—SWB and LX Size and type Mfr. and model Revs per mile (km) Standard—Touring and Limited Size and type Mfr. and model Revs per mile (km) Standard—Touring and Limited Size and type Mfr. and model Revs per mile (km) WHEELS Standard—SWB and LX Type and material Size Optional –SWB and LX	Ders—std.; revised spring rates and cincluded in Trailer Tow Prep Group Rack-and-pinion, power-assisted 17.8:1 39.4 ft. (12.0 m) 3.14 Parallel Stamped-steel 15 x 6.5
track bar and gas-charged shock absorbers— STEERING Type Overall Ratio Turning Diameter (curb-to-curb) Steering Turns (lock-to-lock) TIRES Standard—SWB and LX Size and type Mfr. and model Revs per mile (km) Standard—Touring and Limited Size and type Mfr. and model Revs per mile (km) Standard—SWB and LX Size and type Office and material Size Optional—SWB and LX Type and material Size Optional—SWB and LX Type and material	Ders—std.; revised spring rates and cincluded in Trailer Tow Prep Group Rack-and-pinion, power-assisted 17.8:1 39.4 ft. (12.0 m) 3.14 Parallel Stamped-steel 15 x 6.5 Cast-aluminum
track bar and gas-charged shock absorbers— STEERING Type Overall Ratio Turning Diameter (curb-to-curb) Steering Turns (lock-to-lock) TIRES Standard—SWB and LX Size and type Mfr. and model Revs per mile (km) Standard—Touring and Limited Size and type Mfr. and model Revs per mile (km) Standard—SWB and LX Size and type Office and material Size Optional—SWB and LX Type and material Size Optional—SWB and LX Type and material Size Size Optional—SWB and LX Type and material Size	Ders—std.; revised spring rates and cincluded in Trailer Tow Prep Group Rack-and-pinion, power-assisted 17.8:1 39.4 ft. (12.0 m) 3.14 Parallel Stamped-steel 15 x 6.5 Cast-aluminum
track bar and gas-charged shock absorbers— STEERING Type Overall Ratio Turning Diameter (curb-to-curb) Steering Turns (lock-to-lock) TIRES Standard—SWB and LX Size and type Mfr. and model Revs per mile (km) Standard—Touring and Limited Size and type Mfr. and model Revs per mile (km) Standard—SWB and LX Size and type Office and material Size Optional—SWB and LX Type and material Size Standard—Touring Standard—Touring	Ders—std.; revised spring rates and included in Trailer Tow Prep Group Rack-and-pinion, power-assisted
track bar and gas-charged shock absorbers— STEERING Type Overall Ratio Turning Diameter (curb-to-curb) Steering Turns (lock-to-lock) TIRES Standard—SWB and LX Size and type Mfr. and model Revs per mile (km) Standard—Touring and Limited Size and type Mfr. and model Revs per mile (km) WHEELS Standard—SWB and LX Type and material Size Optional—SWB and LX Type and material Size Standard—Touring Type and material Type and material Size Standard—Touring Type and material	Ders—std.; revised spring rates and included in Trailer Tow Prep Group Rack-and-pinion, power-assisted
track bar and gas-charged shock absorbers— STEERING Type Overall Ratio Turning Diameter (curb-to-curb) Steering Turns (lock-to-lock) TIRES Standard—SWB and LX Size and type Mfr. and model Revs per mile (km) Standard—Touring and Limited Size and type Mfr. and model Revs per mile (km) Standard—SWB and LX Size and type Office and material Size Optional—SWB and LX Type and material Size Standard—Touring Standard—Touring	Ders—std.; revised spring rates and cincluded in Trailer Tow Prep Group Rack-and-pinion, power-assisted 17.8:1 39.4 ft. (12.0 m) 3.14 215/70R15 black sidewall all-season Goodyear Integrity 780 (485) 15/65R16 low-black letter all-season Bridgestone Turanza EL42 778 (483) Stamped-steel 15 x 6.5 Cast-aluminum Cast-aluminum

	Chrome cast-aluminum 16 x 6.5
BRAKES	
Standard—Short Wheelbase Town & Co	puntry
Front	
	x 28) vented disc with 2.60 (66) single-piston sliding caliper 228.5 sq. in. (1474 sq. cm)
Rear	. , , , ,
Size and type	9.8 x 2.2 (250 x 55) dual-action drum
	134 sq. in. (864 sq. cm)
Power Assist Type	10.62 (270) single-diaphragm vacuum
Optional—Short Wheelbase Town & Co	untry
Front	
Size and type1	1.1 x 1.10 (281 x 28) vented disc with 2.60 (66) single-piston sliding caliper with ABS
Swept area	228.5 sq. in. (1474 sq. cm)
Rear	
Size and type	9.8 x 2.2 (250 x 55) dual-action drum with ABS
	134 sq. in. (864 sq. cm)
	10.62 (270) single-diaphragm vacuum
Standard—Long Wheelbase Town & Co	untry LX, Touring and Limited
Front	
Size and type1	1.1 x 1.10 (281 x 28) vented disc with 2.60 (66) single-piston sliding caliper with ABS
Swept area	228.5 sq. in. (1474 sq. cm)
Rear	
Size and type	11.4 x 0.5 (290 x 12.5) solid disc with 1.65 (42) single-piston
	sliding caliper with ABS
	190.5 sq. in. (1234 sq. cm)
Power Assist Type	10.62 (270) single-diaphragm vacuum