

LEGEND: S=Standard, O=Optional, P=Package, — = Not available

Complete package information is listed at the end of the Feature Availability section.

NOTE: Information shown is correct at time of publication, and is subject to change without notice.

2007 Dodge Ram 1500 FEATURE AVAILABILITY

	ST	SLT	Laramie
EXTERIOR			
Air Dam—Front (not available with Sport Appearance Group) _____	S	S	S
Box Bedliner—Under-rail _____	O	O	O
Badges and Decals			
4x4, Bright; (4WD models) _____	S	S	S
Ram's head in grille _____	S	S	S
SLT _____	—	S	—
Laramie _____	—	—	S
TRX, decal (P2, P3, P4) _____	P	P	P
Bumper			
Front			
Chrome _____	S	S	S
Rear with step pads			
Chrome _____	S	S	S
Body color (P7) _____	—	P	P
Colors			
Atlantic Blue Pearl Coat, Black, Bright Silver Metallic, Bright White, Red Flame, Inferno Red Crystal Pearl Coat, Light Khaki Metallic, Patriot Blue Pearl Coat and Mineral Gray Metallic _____	O	O	O
Fascia			
Front, body color (P7) _____	—	P	P
Dark Gray (P9) _____	P	—	—
Fog Lamps (Optional on SLT, included in P7) _____	—	P	S
Glass—Tinted _____	S	S	S
Grille Surround			
Chrome _____	S	S	S
Body color (P7) _____	—	P	P
Dark Gray (P9) _____	P	—	—
Headlamps			
Halogen _____	S	S	S
Head Restraints, rear adjustable outboard (Quad) _____	S	S	S
Mirrors			
Manual adjusting, fold-away, black (6" x 9") _____	S	—	—
Power, heated, fold-away _____	—	S	S
Trailer tow, power, heated, fold-away, flip-up (7" x 10") _____	—	O	O
Trailer tow, manual, fold-away, flip-up _____	O	—	—
Molding			
Bodyside, body color (P7) _____	—	P	P
Bodyside, Black _____	O	O	—
Bodyside, Chrome _____	—	—	S
Paint			
Monotone _____	S	S	S
Two-tone lower _____	O	O	O

Rear Window			
Fixed, tinted _____	S	S	S
Sliding, deep tint _____	O	O	O
Defroster, fixed, deep tint _____	—	O	O
Power sliding (with defroster—Quad Cab® only) _____	O	O	O
Shield, Front Hood Protection _____	O	O	O
Spoiler, Rear Liftgate _____	S	S	S
Sun Roof—Power (Quad Cab Short Box only) _____	—	O	O
Tow Hooks (two- and four-wheel drive) (P5) _____	P	P	P

INTERIOR

Air Conditioning			
Dual-zone climate control _____	—	—	S
Single-zone temperature control _____	S	S	—
Assist Handles—Four: Quad Cab; two: regular cab _____	S	S	S
Bezel—Instrument panel and doors, <i>Satin Silver</i> _____	—	—	S
Colors			
Medium Slate Gray _____	O	O	O
Khaki _____	O	O	O
Console			
Overhead (includes compass mini trip computer and dual courtesy/reading lamps) _____	—	S	S
Overhead (includes compass mini trip computer, HomeLink® three-channel universal remote transceiver and dual courtesy/reading lamps) _____	—	—	O
Electrical Power Outlet—Auxiliary 12-volt _____	S	S	S
Floor Covering			
Front seat area carpet (includes front floor mats; color-keyed) _____	O	S	S
Vinyl (black) _____	S	—	—
Instrument Cluster with 120-mph speedometer and tachometer _____	S	S	S
Lamps			
Ash tray (P1) _____	—	P	S
Cargo _____	S	S	S
Glove box _____	S	S	S
Front dome with on/off switch (P1) _____	—	P	S
Underhood (P1) _____	—	P	S
Lighter—Cigar _____	S	S	S
Mirror—Rearview			
Manual day/night _____	S	S	—
Automatic dimming _____	—	O	S
Pedals—Power adjustable _____	O	O	S
Power Accessory Delay _____	S	S	S
Radios			
AM/FM CD with changer controls and four speakers _____	S	—	—
AM/FM six-disc in-dash with MP3 playback capability _____	—	S	—
AM/FM with six-disc in-dash CD, Infinity speaker system with eight speakers in seven locations and 240-watt digital amplifier; not available on Laramie J Package _____	—	—	S
Navigation Radio with full-color display, AM/FM stereo, CD player and DVD-based navigation system, Infinity speaker system with eight speakers in seven locations and 240-watt digital amplifier; not available on Laramie J Package _____	—	O	O
Rear Seat DVD Entertainment System (Quad Cabs) _____	—	O	O
SIRIUS Satellite Radio (must have Infinity speaker system) _____	—	O	O
Steering Wheel-mounted Audio Controls; must have AM/FM cassette/CD or AM/FM radio with CD and six-disc in-dash CD changer with Infinity speaker system _____	—	O	S
UConnect® Hands-free Communication System with wireless Bluetooth® cellular phone connection _____	—	O	O
Seats			
YES Essentials® Seat Fabric 40/20/40 bench (Quad Cab includes folding rear seat) _____	O	—	—

Heavy-duty vinyl 40/20/40 bench (Quad Cab includes folding rear seat) _____	S	—	—
Leather 40/20/40 bench (includes 60/40 split-folding rear seat, fold-out rear load floor, front center armrest storage and six-way power driver seat and leather-wrapped steering wheel) _____	—	—	S
Leather 40/20/40 bench (includes front center armrest storage; Quad Cab also includes 60/40 split-folding rear and fold-out rear load floor) _____	—	—	S
YES Essentials Seat Fabric (includes 60/40 split-folding rear seat, fold-out rear load floor, front center armrest storage and six-way power driver seat) _____	—	S	—
Power six-way driver (included with premium cloth or leather 40/20/40 bench; regular cab only) _____	—	O	S
Power six-way driver and passenger (Quad Cab only) _____	—	—	S
Driver and front passenger, heated _____	—	—	O
Front bucket seats (leather) with full center console _____	--	O	O
Rear ladder-style headrest (Quad Cabs) _____	S	S	S
Speed Control _____	O	S	S
Steering Wheel _____			
Four-spoke _____	S	—	—
Leather-wrapped (optional with cloth seats and included with leather seats on SLT, P7) _____	—	P	S
Storage _____			
Cab back (regular cab only) _____	S	S	S
Rear underseat compartment (Quad Cab only) _____	S	S	S
Sun Visors _____			
Sliding, cloth _____	S	—	—
Sliding, cloth with passenger covered mirror _____	—	S	—
Sliding, cloth with lighted driver- and passenger-covered mirror (P1) _____	—	P	S
Windows—Power with driver one-touch open _____	—	S	S
Windshield Wiper and Washer System— _____			
Two-speed with variable-delay intermittent _____	S	S	S
POWERTRAIN AND CHASSIS			
Brakes _____			
Four-wheel disc with rear anti-lock _____	S	S	—
Four-wheel disc with four-wheel anti-lock _____	O	O	S
Engine Block Heater (standard in Canada) _____	O	O	O
Full-time Four-wheel Drive Electric Shift (NV 244) (must have five-speed automatic transmission) _____	S	S	S
Tires _____			
P245/70R17 black sidewall all-season _____	S	S	—
P265/70R17 black sidewall all-season (optional on ST four-wheel drive only) _____	O	O	S
P265/70R17 black sidewall on-off-road (four-wheel drive only) _____	O	—	—
P265/70R17 outline white letter on-off-road (four-wheel drive only) _____	—	O	O
P265/70R17 outline white letter all-season _____	—	O	O
LT275/70R17 outline white letter all-terrain (P2) _____	—	P	—
P275/60R20 black sidewall all-season (20" wheels only) _____	—	O	O
Spare, full-size _____	S	S	S
Tow/Haul Mode (requires automatic transmission) _____	S	S	S
Wheels _____			
Aluminum 17" x 8" TRX4 Off-Road Group wheels (P2) _____	—	P	—
Cast-aluminum, painted, 17" x 8.0" (P3, P4) _____	—	P	—
Cast-aluminum, 20", chrome-clad (included in Sport Package) _____	—	O	O
Cast-aluminum, 20" x 9.0", machined _____	—	O	—
Cast-aluminum, 17" x 8.0", chrome-clad _____	O	O	S
Steel, Argent, 17" x 7.0" _____	S	—	—
Full-size spare, steel _____	S	S	S

SAFETY AND SECURITY

Door Locks—Power _____	—	S	S
Energy-absorbing Steering Column _____	S	S	S
Keyless Entry—Remote (included in Security Group) _____	—	S	S
Electronic Stability Program (ESP) _____	O	O	O
Adjustable Rear Headrests (Quad Cabs) _____	S	S	S
Remote Start _____	O	O	O
Restraints			
Front—Next-generation driver and passenger air bags(a) and knee bolsters _____	S	S	S
Height-adjustable three-point seat belts, outboard front _____	S	S	S
Lap belt, front center(b) _____	S	S	S
Three-point seat belt, front center(c) _____	S	S	S
Passenger air bag on/off switch(c)(d) _____	S	S	S
Front Passenger Occupant Classification System (OCS—Quad Cabs) _____	S	S	S
Rear—Three-point seat belts (three)(b) _____	S	S	S
Supplemental side air bag inflatable curtains (SABIC) _____	O	O	O
Lower Anchors and Tethers for CHildren (LATCH) child seat anchor system _____	S	S	S
Security Alarm (P6) _____	—	P	S
Sentry Key® engine immobilizer (P6) _____	—	P	S

(a) Certified to federal regulations that allow less forceful air bags. Always use seat belts.

Remember, a back seat is the safest place for children.

(b) Quad Cab only.

(c) Regular cab only.

(d) Important, always remove key. Rearward-facing child seats can be used in the front seat only with the passenger air bag turned off.

PACKAGES

	ST	SLT	Laramie
P1 -- Light Group—Underhood lamp, cup holder lamp, ashtray lamp, switchable dome lamp, vanity mirror lamp for driver and passenger, electrochromic rearview mirror _____	—	O	S
P2 – TRX4 Off-road Group—(4x4 only) Unique 17-inch aluminum wheels; unique shocks (painted red); P265 on/off road OWL all-terrain tires; body color grille surround; TRX4 Off-Road decal; tow hooks; transfer case skid plate; front suspension skid plate; anti-spin differential; fog lamps. Options: LT275 OWL tire and 3.92 axle ratio _____	O	O	O
P3 – TRX4 Group—(4x4 only) Unique 17-inch aluminum wheels; unique shocks (painted red); P265 on/off road OWL all-terrain tires; body color grille surround; TRX4 decal _____	O	O	O
P4 – TRX Group—(4x2 only) Unique 17-inch aluminum wheels unique shocks; (painted red); P265 on/off road OWL all-terrain tires; body color grille surround; TRX decal _____	O	O	O
P5 – Protection Group—Tow hooks, transfer case and front suspension skid plates (four-wheel drive only) _____	O	O	O
P6 – Security Group—Security alarm, Sentry Key engine immobilizer and remote keyless entry system _____	—	O	S
P7 – Sport Package—Fog lamps, body color grille with platinum chrome billet texture, body color full-coverage front fascia, body color moldings, body color rear bumper with step pads, 20" chrome-clad aluminum wheels "Sport" badge, 5.7-liter HEMI® engine, cloth bucket seats with full console, leather-wrapped steering wheel. Options: Leather bucket seats with sport appearance ("Sport" embroidered on backrest in red; French-stitched seams in red; perforated leather on bolsters) or cloth bench seat and all options offered in SLT model (except leather bucket seats) _____	—	O	O
P8 – Trailer Tow Group—Class IV hitch receiver, seven-circuit wiring harness, 750-amp battery, heavy-duty engine cooling and auxiliary transmission oil cooler when equipped with automatic transmission _____	O	O	O

P9 – Work Special Group—Dark Gray front fascia, Dark Gray grille and 17" x 7"

Argent steel wheels with Black hubs _____ O — —

Legend: S = Standard O = Optional P = Available in group — = Not available

NOTE: The information shown is preliminary and based on data available at the time of publication.

1500 PAYLOAD SELECTOR

		Estimated Curb Weight, lbs.(a)			Estimated Payload, lbs.(b)		
Box Size, ft.	GVWR, lbs.	3.7L V-6	4.7L V-8	5.7L V-8	3.7L V-6	4.7L V-8	5.7L V-8
Regular Cab Pickup—2WD							
6.3	6350	4459	4517	4620	1750	1700	1600
8	6550	4649	4712	4819	1750	1700	1600
Regular Cab Pickup—4WD							
6.3	6350		4905	5017		1300	1200
8	6550		4997	5108		1400	1300
Quad Cab® Pickup—2WD							
6.3	6650	4761	4867	4925	1750	1650	1550
8	6650	—	5041	5166	—	1450	1350
Quad Cab Pickup—4WD							
6.3	6650		5120	5233		1400	1250
8	6800		5381	5466		1250	1200

(a) Curb weight is for a base model with standard equipment.

(b) Payload is the maximum allowable weight of driver, passengers and cargo rounded to the nearest 10 pounds.

It is reduced by the weight of optional equipment.

NOTE: The information shown is preliminary and based on data available at the time of publication.

POWERTRAIN AVAILABILITY

Regular Cab Pickup—2WD

Engine(b)	Transmission and Axle Ratio Combinations		
	Manual Transmission(a) Six-speed	Automatic Transmission Four-speed	Automatic Transmission Five-speed
3.7L V-6	3.21, 3.55	3.55, 3.92	—
4.7L V-8	3.21, 3.92	—	3.55, 3.92
5.7L V-8	—	—	3.55, 3.92

Regular Cab Pickup—4WD

Engine(b)	Transmission and Axle Ratio Combinations				
	Manual Transmission(a) Six-speed	Automatic Transmission Five-speed	Part-time, Manual Shift	Transfer Cases Part-time, Electric Shift	Full-time, Electric Shift
4.7L V-8	3.55, 3.92	3.55, 3.92	Std.	Opt.	Opt.
5.7L V-8	—	3.55, 3.92	Std.	Opt.	Opt.

Quad Cab Pickup—2WD

Engine(b)	Transmission and Axle Ratio Combinations		
	Manual Transmission(a) Six-speed	Automatic Transmission Four-speed	Automatic Transmission Five-speed
3.7L V-6	3.21, 3.55	3.92	—
4.7L V-8	3.21, 3.92	—	3.55, 3.92
5.7L V-8	—	—	3.55, 3.92

Quad Cab Pickup—4WD

Engine(b)	Transmission and Axle Ratio Combinations				
	Manual	Automatic	Transfer Cases		
	Transmission(a) Six-speed	Transmission Five-speed	Part-time, Manual Shift	Part-time, Electric Shift	Full-time, Electric Shift
4.7L V-8	3.55, 3.92(c)	3.55, 3.92(c)	Std.	Opt.	Opt.
5.7L V-8	—	3.55, 3.92(c)	Std.	Opt.	Opt.

(a) Manual transmission standard where available.

(b) Standard engine listed first.

(c) 3.55 ratio is not available with Quad Cab Long Box 4x4.

NOTE: The information shown is preliminary and based on data available at the time of publication.

SPECIFICATIONS

All dimensions are in inches (millimeters) unless otherwise noted.

GENERAL INFORMATION

Body Styles _____ Regular cab and Quad Cab® pickup

Assembly Plant _____ Regular cab: St. Louis, Missouri;

Quad Cab: Dodge City (Warren, Michigan); St. Louis, Missouri; Satallo, Mexico

EPA Vehicle Class _____ Standard Pickup

ENGINE: NEXT-GENERATION 3.7-LITER, SOHC, 12-VALVE SMPI V-6 MAGNUM®

Availability _____ Std.—2WD regular and 2WD Quad Cab Short Box

Type and Description _____ 90-degree V-6, liquid-cooled with balance shaft

Displacement _____ 226 cu. in. (3701 cu. cm)

Bore x Stroke _____ 3.66 x 3.57 (93.0 x 90.8)

Valve System _____ Chain-driven SOHC, 12 valves, hydraulic end-pivot roller rockers

Fuel Injection _____ Sequential, multi-port, electronic, returnless

Construction _____ Cast-iron block and bedplate, aluminum alloy heads, balance shaft

Compression Ratio _____ 9.7:1

Power (SAE net) _____ 215 bhp (160 kW) @ 5,200 rpm (58.1 bhp/L)

Torque (SAE net) _____ 235 lb.-ft. (319 N•m) @ 4,000 rpm

Max. Engine Speed _____ 6,000 rpm (electronically limited)

Fuel Requirement _____ Unleaded regular, 87 octane (R + M)/2

Oil Capacity _____ 5.0 qt. (4.7L)

Emission Controls _____ Three-way catalytic converters and internal engine features(a)

Estimated EPA Fuel Economy mpg (City/Hwy) _____ 16/21—manual(b), 15/21—automatic(b)

ENGINE: NEXT-GENERATION 4.7-LITER MAGNUM®, SOHC, 16-VALVE SMPI V-8

Availability _____ Std.—Quad Cab Long Box models and 4WD regular cabs

Type and Description _____ 90-degree V-8, liquid-cooled

Displacement _____ 287 cu. in. (4701 cu. cm)

Bore x Stroke _____ 3.66 x 3.40 (93.0 x 86.5)

Valve System _____ Chain-driven SOHC, 16 valves, hydraulic end-pivot roller rockers

Fuel Injection _____ Sequential, multi-port, electronic, returnless

Construction _____ Cast-iron block, aluminum alloy heads

Compression Ratio _____ 9.0:1

Power (SAE net) _____ 235 bhp (175 kW) @ 4,800 rpm (50.0 bhp/L) estimated(b)

Torque (SAE net) _____ 300 lb.-ft. (407 N•m) @ 3,200 rpm

Max. Engine Speed _____ 6,000 rpm (electronically limited)

Fuel Requirement _____ Unleaded regular, 87 octane (R + M)/2, E85 Compatible

Oil Capacity _____ 6 qt. (5.7L)

Emission Controls _____ Three-way catalytic converters, heated oxygen sensors, electronic EGR and internal engine features(a)(b)

Estimated EPA Fuel Economy mpg (City/Hwy) _____ 2WD: 14/19—manual, 14/19—automatic;
4WD: 13/17—manual, 14/17—automatic

(a) Meets LEV 1 emission requirements in CA, NY, MA, ME and VT. Meets Tier 2, Bin 10A emission requirements in all other states.

(b) Flexible fuel version available to fleet customers.

ENGINE: 5.7-LITER HEMI® MAGNUM 16-VALVE V-8

Availability _____ Optional
Type and Description _____ Eight cylinders, 90° V-type, liquid-cooled
Displacement _____ 343 cu. in. (5654 cu. cm)
Bore x Stroke _____ 3.92 x 3.58 (99.5 x 90.9)
Valve System _____ Pushrod-operated overhead valves, 16 valves, hydraulic lifters with roller followers
Fuel Injection _____ Sequential, multi-port, electronic, returnless
Construction _____ Deep-skirt cast-iron block with cross-bolted main bearing caps, aluminum alloy heads with hemispherical combustion chambers
Compression Ratio _____ 9.6:1
Power (SAE net) _____ 345 bhp (257 kW) @ 5,400 rpm, (61.0 bhp/L)
Torque (SAE net) _____ 375 lb.-ft. (508 N•m) @ 4,200 rpm
Max. Engine Speed _____ 5,800 rpm
Fuel Requirement _____ Unleaded mid-grade, 89 octane (R+M)/2—recommended
Unleaded regular, 87 octane (R+M)/2—acceptable
Oil Capacity _____ 7 qt. (6.6L)
Coolant Capacity _____ 18.7 qt. (17.7L)
Emission Controls _____ Three-way catalytic converters, heated oxygen sensors and electronic EGR and internal engine features(a)
Estimated EPA Fuel Economy mpg (City/Hwy)(b) _____ 2WD: 14/18; 4WD: 13/17

(a) Meets SULEV 1 emissions requirements in CA, NY, MA, ME and VT. Meets Tier 2 Bin 10C emissions in all other states.

(b) Tentative EPA label values, pending official test results.

NOTE: All dimensions measured at curb weight with standard tires and wheels.

ELECTRICAL SYSTEM

Alternator _____ 136-amp
Battery _____ Group 65, low-maintenance, 600 CCA—std., 700 CCA—opt.

TRANSMISSION: GETRAG G56—MANUAL, SIX-SPEED OVERDRIVE

Availability _____ Std.—all with 3.7- and 4.7-liter engines
Description _____ Synchronized in all gears
Gear Ratios
1st _____ 4.23
2nd _____ 2.53
3rd _____ 1.67
4th _____ 1.23
5th _____ 1.0
6th _____ 0.79
Reverse _____ 3.84
Overall Top Gear Ratio _____ 2.53 with 3.21 axle; 2.80 with 3.55 axle; 3.10 with 3.92 axle

TRANSMISSION: 45RFE—AUTOMATIC, MULTI-SPEED OVERDRIVE

Availability _____ Opt.—all with 3.7-liter engine
Description _____ Three planetary gear sets, one overrunning clutch, full electronic control, electronically controlled converter clutch
Gear Ratios
1st _____ 3
2nd _____ 1.67—upshift; 1.50—kick-down
3rd _____ 1
4th _____ 0.75
Reverse _____ 3
Overall Top Gear _____ 2.66 with 3.55 axle and 2.94 with 3.92 axle

TRANSMISSION: 5-45RFE—AUTOMATIC FIVE-SPEED

Availability _____ Opt. with 4.7-liter, Std. with 5.7-liter engines

Description _____ Three planetary gear sets, one overrunning clutch,
full electronic control, electronically controlled converter clutch**Gear Ratios**

1st _____ 3

2nd _____ 1.67—upshift; 1.50 kick-down

3rd _____ 1

4th _____ 0.75

5th _____ 0.67

Reverse _____ 3

Overall Top Gear _____ 2.38 with 3.55 axle and 2.63 with 3.92 axle

TRANSFER CASE: NV243 PART-TIME

Availability _____ Optional with 4.7-liter and 5.7-liter engines

Shift Mechanism _____ Electric

Operating Modes _____ 2WD High; 4WD High, Locked; Neutral; 4WD Low

Low Range Ratio _____ 2.72

Center Differential Type _____ None

Torque Split, F/R _____ 48/52

TRANSFER CASE: NV246 ON-DEMAND

Availability _____ Optional with 4.7-liter and 5.7-liter engines

Shift Mechanism _____ Electric

Operating Modes _____ 2WD; 4WD Auto; 4WD High; Neutral; 4WD Low

Low Range Ratio _____ 2.72

Center Differential Type _____ None

Torque Split, F/R _____ 48/52

DIMENSIONS AND CAPACITIES

	2WD		4WD	
	Short	Long	Short	Long
<i>Quad Cab</i>				
Box Length, ft. (nominal)	6.3	8	6.3	8
Wheelbase	140.5	160.5	140.5	160.5
Track, Front	68.6	68.6	68.0	68.0
Track, Rear	67.9	67.9	67.9	67.9
Overall Length	227.7	249.7	227.7	249.7
Overall Width	79.5	79.5	79.5	79.5
Overall Height	74.0	73.8	75.9	34.2
Tailgate Load Height	33.7	33.6	35.1	35
Ground Clearance				
Front Axle	7.7	7.7	9.6	9.6
Rear Axle	7.4	7.4	7.3	7.3
Approach Angle	14.7°	14.9°	18.3°	18.4°
Ramp Breakover Angle	19.7°	18.4°	21.1°	20.0°
Departure Angle	24.2°	23.1°	25.8°	24.8°
Frontal Area	34.6 sq. ft.	34.6 sq. ft.	34.9 sq. ft.	34.9 sq. ft.
Drag Coefficient	—	—	0.528	—
Fuel Tank Capacity	26 gal. (98L)	35 gal. (132L)	26 gal. (98L)	35 gal. (132L)
Optional (Quad only)	34 gal. (128L)	—	34 gal. (128L)	—
<i>Regular Cab</i>				
Box Length, ft. (nominal)	6.3	8	6.3	8
Wheelbase	120.5	140.5	120.5	140.5
Track, Front	68.6	68.6	68.0	68.0
Track, Rear	67.9	67.9	67.9	67.9
Overall Length	207.7	229.7	207.7	229.7
Overall Width	79.5	79.5	79.5	79.5

Overall Height	73.6	73.4	75.5	75.3
Tailgate Load Height	33.0	32.9	34.4	34.3
Ground Clearance				
Front Axle	7.7	7.7	9.6	9.6
Rear Axle	7.4	7.4	7.3	7.3
Approach Angle	14.5°	14.7°	18.1°	18.3°
Ramp Breakover Angle	21.6°	19.7°	22.9°	21.1°
Departure Angle	24.4°	23.2°	26.0°	25.0°
Frontal Area	34.6 sq. ft.	34.6 sq. ft.	34.9 sq. ft.	34.9 sq. ft.
Fuel Tank Capacity	26 gal. (98L)	35 gal. (132L)	26 gal. (98L)	35 gal. (132L)

All dimensions are in inches (millimeters) unless otherwise noted.

CARGO BOX

Nominal Box Size, ft.	6.3	8
SAE Volume	60.9 cu. ft. (1.72 cu. m)	74.9 cu. ft. (2.12 cu. m)
Length at Floor, Tailgate Closed	76.3 (1928)	98.3 (2497.1)
Cargo Width	70.2 (1783.3)	66.4 (1687)
Distance between Wheelhouses	51.0 (1295)	51.0 (1295)
Depth	20.2 (512)	20.2 (512)
Tailgate Opening Width	60.6 (1538)	63.5 (1612)

ACCOMMODATIONS

	Regular Cab	Quad Cab
Seating Capacity, F/R	3/—	3/3
Front		
Head room	40.9 (1040)	40.8 (1037)
Leg room	41.0 (1041)	41.0 (1041)
Shoulder room	67.1 (1705.6)	67.0 (1702)
Hip room	64.9 (1648.2)	64.9 (1648.2)
Seat travel	9.0 (229)	9.0 (229)
Recliner range	45°	45°
Rear		
Head room	—	40.0 (1015)
Leg room	—	36.7 (1648.2)
Shoulder room	—	66.7 (1694)
Hip room	—	64.6 (1640)
Knee clearance	—	1.1 (28.4)
Interior Volume		
Front	65.2 cu. ft.	64.92 cu. ft.
Rear	—	56.7 cu. ft.

BODY AND CHASSIS

	2WD	4WD
Layout	Longitudinal, front engine; Hotchkiss drive transfer case	Longitudinal, front; engine, Hotchkiss drive transfer case
Construction	Ladder-type, fully-box frame, steel cab, double-wall steel pickup box	Ladder-type, fully boxed frame, steel cab, double-wall steel pickup box

SUSPENSION

	2WD	4WD
Front	Upper and lower "A" arms, coil springs, gas-charged shock absorbers, stabilizer bar	Double Upper and lower "A" arms, torsion bars, gas-charged shock absorbers, stabilizer bar
Rear	Live axle, longitudinal leaf springs, gas-charged shock absorbers	Live axle, longitudinal leaf springs, gas-charged shock absorbers

STEERING

	2WD		4WD	
<i>Quad Cab</i>				
Wheelbase	140.5	160.5	140.5	160.5
Overall Ratio	14.1:1	13.3:1	14.1:1	13.3:1
Steering Wheel Turns				
Lock to lock	2.75	2.6	2.75	2.6
Turning Diameter(a)	45.7 ft. (13.9 m)	52.0 ft. (15.85 m)	46.0 ft. (14.02 m)	52.5 ft. (16 m)

Regular Cab Pickup

Wheelbase	120.5	140.5	120.5	140.5
Overall Ratio	15.4:1	14.1:1	15.4:1	14.1:1
Steering Wheel Turns				
Lock to lock	3	2.75	3	2.75
Turning Diameter(a)	39.3 ft. (11.97 m)	45.7 ft. (13.9 m)	39.6 ft. (12.07 m)	46.00 ft. (14.02 m)

BRAKES

Front

Size and type _____ 13.2 x 1.1 (336 x 28) vented disc with 2.13 (54) two-piston pin-slider caliper(b)

Swept area _____ 292 sq. in. (1884 sq. cm)

Rear

Size and type _____ 13.8 x 0.87 (352 x 22) disc with 2.13 (54) single-piston pin-slider caliper and ABS

Swept area _____ 274 sq. in. (1768 sq. cm)

Power Assist Type _____ Dual-rate, tandem diaphragm vacuum

(a) Turning diameter is measured at the outside of the tires at curb height. Turning diameters and steering wheel turns, lock-to-lock may differ with optional tires and wheels.

(b) Also available with ABS.

ESTIMATED TRAILER TOWING CAPACITIES

RAM QUAD CAB 2WD SHORT BED ST

Tire Type	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
17" base	3.7L V-6 gas	M6	Getrag 238 6-spd. MANU (DEJ)	3.21	6700	1750	4952	2749	2203	3700	3900	8000	2900
17" base	3.7L V-6 gas	M6	Getrag 238 6-spd. MANU (DEJ)	3.55	6700	1750	4952	2749	2203	3700	3900	8000	2900
17" base	3.7L V-6 gas	A4	42RLE VLP 4-spd. AUTO (DG6)	3.92	6700	1760	4939	2743	2197	3700	3900	8500	3400
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.21	6700	1700	5000	2830	2170	3700	3900	9000	3850
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.92	6700	1700	5000	2830	2170	3700	3900	10,500	5350
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6700	1640	5061	2879	2182	3700	3900	11,500	6300
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1640	5061	2879	2182	3700	3900	12,500	7300
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6700	1600	5096	2884	2212	3700	3900	11,500	6250
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1600	5096	2884	2212	3700	3900	12,500	7250
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6700	1570	5127	2906	2221	3700	3900	13,000	7700
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1570	5127	2906	2221	3700	3900	14,000	8700

(a) Payload is rounded to the nearest 10 lbs. Payload = GVWR—curb wt.
(b) Maximum trailer weights are rounded to the nearest 50 lbs. Maximum Trailer Weight = GCWR - curb wt. - 150 lbs. (allowance for driver).
(c) 4.7L V-8 Gas FFV 45-State Emission Fleet Only.

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

RAM QUAD CAB 2WD SHORT BED LARAMIE

Tire Type	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6700	1540	5165	2910	2254	3700	3900	11,500	6200
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1540	5165	2910	2254	3700	3900	12,500	7200
20"	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1530	5172	2913	2259	3700	3900	11,500	6200
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6700	1500	5199	2915	2284	3700	3900	11,500	6150
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1500	5199	2915	2284	3700	3900	12,500	7150
20"	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1490	5207	2918	2289	3700	3900	11,500	6150
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6700	1460	5244	2966	2278	3700	3900	13,000	7600
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1460	5244	2966	2278	3700	3900	14,000	8600
20"	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1450	5252	2969	2283	3700	3900	13,000	7600

(a) Payload is rounded to the nearest 10 lbs. Payload = GVWR—curb wt.

(b) Maximum trailer weights are rounded to the nearest 50 lbs. Maximum Trailer Weight = GCWR - curb wt. - 150 lbs. (allowance for driver).

(c) 4.7L V-8 Gas FFV 45-State Emission Fleet Only

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

RAM QUAD CAB 2WD LONG BED ST

Tire Type	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.21	6700	1540	5165	2931	2234	3700	3900	9000	3700
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.92	6700	1540	5165	2931	2234	3700	3900	10,500	5200
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6700	1470	5228	2982	2246	3700	3900	11,500	6100
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1470	5228	2982	2246	3700	3900	12,500	7100
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6700	1440	5260	2984	2276	3700	3900	11,500	6100
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1440	5260	2984	2276	3700	3900	12,500	7100
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6700	1410	5286	3012	2274	3700	3900	13,000	7550
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1410	5286	3012	2274	3700	3900	14,000	8550

(a) Payload is rounded to the nearest 10 lbs. Payload = GVWR—curb wt.

(b) Maximum trailer weights are rounded to the nearest 50 lbs. Maximum Trailer Weight = GCWR - curb wt. - 150 lbs. (allowance for driver).

(c) 4.7L V-8 Gas FFV 45-State Emission Fleet Only.

RAM QUAD CAB 2WD LONG BED SLT

Tire Type	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.21	6700	1550	5154	2923	2231	3700	3900	9000	3700
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.92	6700	1550	5154	2923	2231	3700	3900	10,500	5200
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6700	1480	5217	2974	2243	3700	3900	11,500	6150
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1480	5217	2974	2243	3700	3900	12,500	7150
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6700	1450	5251	2978	2273	3700	3900	11,500	6100
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1450	5251	2978	2273	3700	3900	12,500	7100
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6700	1380	5319	3050	2269	3700	3900	13,000	7550
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1380	5319	3050	2269	3700	3900	14,000	8550

--	--	--	--

Tire Type	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6700	1360	5341	3036	2306	3700	3900	11,500	6000
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1360	5341	3036	2306	3700	3900	12,500	7000
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6700	1320	5376	3040	2336	3700	3900	11,500	5950
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1320	5376	3040	2336	3700	3900	12,500	6950
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6700	1280	5421	3091	2329	3700	3900	13,000	7450
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGO)	3.92	6700	1280	5421	3091	2329	3700	3900	14,000	8450

(a) Payload is rounded to the nearest 10 lbs. Payload = GVWR—curb wt.

(b) Maximum trailer weights are rounded to the nearest 50 lbs. Maximum Trailer Weight = GCWR - curb wt. - 150 lbs. (allowance for driver).

(c) 4.7L V-8 Gas FFV 45-State Emission Fleet Only.

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

RAM REGULAR CAB 2WD SHORT BED ST

Tire Type	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
17" base	3.7L V-6 gas	M6	Getrag 238 6-spd. MANU (DEJ)	3.21	6025	1470	4560	2573	1987	3700	3900	8000	3300
17" base	3.7L V-6 gas	M6	Getrag 238 6-spd. MANU (DEJ)	3.55	6025	1470	4560	2573	1987	3700	3900	8000	3300
17" base	3.7L V-6 gas	A4	42RLE VLP 4-spd. AUTO (DG6)	3.92	6025	1480	4547	2567	1981	3700	3900	8500	3800
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.21	6025	1370	4660	2624	2036	3700	3900	9000	4200
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.92	6025	1370	4660	2624	2036	3700	3900	10,500	5700
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6025	1300	4723	2671	2052	3700	3900	11,500	6650
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6025	1300	4723	2671	2052	3700	3900	12,500	7650
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6025	1300	4729	2724	2005	3700	3900	11,500	6600
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6025	1300	4729	2724	2005	3700	3900	12,500	7600
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6200	1460	4736	2715	2021	3700	3900	13,000	8100
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6200	1460	4736	2715	2021	3700	3900	14,000	9100

(a) Payload is rounded to the nearest 10 lbs. Payload = GVWR—curb wt.

(b) Maximum trailer weights are rounded to the nearest 50 lbs. Maximum Trailer Weight = GCWR - curb wt. - 150 lbs. (allowance for driver).

(c) 4.7L V-8 Gas FFV 45-State Emission Fleet Only.
--

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

RAM REGULAR CAB 2WD SHORT BED SLT													
Tire Type	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.21	6025	1390	4633	2670	1963	3700	3900	9000	4200
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.92	6025	1390	4633	2670	1963	3700	3900	10,500	5700
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6025	1330	4696	2717	1979	3700	3900	11,500	6650
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6025	1330	4696	2717	1979	3700	3900	12,500	7650
20"	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.92	6025	1290	4731	2705	2026	3700	3900	9,500	4600
20"	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6025	1230	4794	2752	2042	3700	3900	11,500	6550
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6025	1300	4729	2724	2005	3700	3900	11,500	6600
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6025	1300	4729	2724	2005	3700	3900	12,500	7600
20"	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6025	1200	4826	2758	2068	3700	3900	11,500	6500
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6200	1470	4734	2731	2003	3700	3900	13,000	8100
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6200	1470	4734	2731	2003	3700	3900	14,000	9100
20"	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6200	1370	4830	2765	2065	3700	3900	13,000	8000
(a) Payload is rounded to the nearest 10 lbs. Payload = GVWR—curb wt.													
(b) Maximum trailer weights are rounded to the nearest 50 lbs. Maximum Trailer Weight = GCWR - curb wt. - 150 lbs. (allowance for driver).													
(c) 4.7L V-8 Gas FFV 45-State Emission Fleet Only.													

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

RAM REGULAR CAB 2WD SHORT BED LARAMIE													
Tire Type	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6025	1310	4719	2710	2009	3700	3900	11,500	6650
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6025	1310	4719	2710	2009	3700	3900	12,500	7650
20"	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6025	1300	4726	2713	2014	3700	3900	11,500	6600
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6025	1270	4753	2715	2039	3700	3900	11,500	6600
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6025	1270	4753	2715	2039	3700	3900	12,500	7600
20"	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6025	1260	4761	2717	2044	3700	3900	11,500	6600
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6200	1400	4798	2766	2032	3700	3900	13,000	8050
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6200	1400	4798	2766	2032	3700	3900	14,000	9050
20"	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6200	1390	4806	2769	2037	3700	3900	13,000	8050

(a) Payload is rounded to the nearest 10 lbs. Payload = GVWR—curb wt.
(b) Maximum trailer weights are rounded to the nearest 50 lbs. Maximum Trailer Weight = GCWR - curb wt. - 150 lbs. (allowance for driver).
(c) 4.7L V-8 Gas FFV 45-State Emission Fleet Only.

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

RAM REGULAR CAB 2WD LONG BED ST

Tire Type	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
17" base	3.7L V-6 gas	M6	Getrag 238 6-spd. MANU (DEJ)	3.21	6600	1800	4798	2706	2092	3700	3900	8000	3050
17" base	3.7L V-6 gas	M6	Getrag 238 6-spd. MANU (DEJ)	3.55	6600	1800	4798	2706	2092	3700	3900	8000	3050
17" base	3.7L V-6 gas	A4	42RLE VLP 4-spd. (AUTO DG6)	3.92	6600	1820	4785	2700	2086	3700	3900	8500	3550
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.21	6600	1760	4838	2783	2055	3700	3900	9000	4000
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.92	6600	1760	4838	2783	2055	3700	3900	10,500	5500
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6600	1700	4896	2831	2064	3700	3900	11,500	6450
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6600	1700	4896	2831	2064	3700	3900	12,500	7450
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6600	1670	4934	2837	2097	3700	3900	11,500	6400
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6600	1670	4934	2837	2097	3700	3900	12,500	7400
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6600	1640	4960	2865	2095	3700	3900	13,000	7900
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6600	1640	4960	2865	2095	3700	3900	14,000	8900

(a) Payload is rounded to the nearest 10 lbs. Payload = GVWR—curb wt.
(b) Maximum trailer weights are rounded to the nearest 50 lbs. Maximum Trailer Weight = GCWR - curb wt. - 150 lbs. (allowance for driver).
(c) 4.7L V-8 Gas FFV 45-State Emission Fleet Only.

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

RAM REGULAR CAB 2WD LONG BED SLT

Tire Type	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.21	6600	1790	4815	2751	2064	3700	3900	9000	4050
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.92	6600	1790	4815	2751	2064	3700	3900	10,500	5550
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6600	1730	4873	2799	2073	3700	3900	11,500	6500
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6600	1730	4873	2799	2073	3700	3900	12,500	7500
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6600	1690	4910	2804	2106	3700	3900	11,500	6450
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6600	1690	4910	2804	2106	3700	3900	12,500	7450
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6600	1650	4947	2856	2091	3700	3900	13,000	7900
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGO)	3.92	6600	1650	4947	2856	2091	3700	3900	14,000	8900

(a) Payload is rounded to the nearest 10 lbs. Payload = GVWR—curb wt.

(b) Maximum trailer weights are rounded to the nearest 50 lbs. Maximum Trailer Weight = GCWR - curb wt. - 150 lbs. (allowance for driver).

(c) 4.7L V-8 Gas FFV 45-State Emission Fleet Only.

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

RAM REGULAR CAB 2WD LONG BED LARAMIE

Tire Type	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6600	1680	4915	2813	2103	3700	3900	11,500	6450
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6600	1680	4915	2813	2103	3700	3900	12,500	7450
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6600	1650	4950	2817	2133	3700	3900	11,500	6400
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6600	1650	4950	2817	2133	3700	3900	12,500	7400
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6600	1610	4995	2869	2126	3700	3900	13,000	7850
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6600	1610	4995	2869	2126	3700	3900	14,000	8850

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

RAM QUAD CAB 4WD SHORT BED ST

Tire Type	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.55	6700	1460	5240	3067	2173	3900	3900	9500	4100
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.92	6700	1460	5240	3067	2173	3900	3900	10,500	5100
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6700	1400	5297	3111	2186	3900	3900	11,500	6050
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1400	5297	3111	2186	3900	3900	12,500	7050
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6700	1370	5335	3120	2215	3900	3900	11,500	6000
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1370	5335	3120	2215	3900	3900	12,500	7000
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6700	1330	5366	3142	2224	3900	3900	13,000	7500
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1330	5366	3142	2224	3900	3900	14,000	8500

(a) Payload is rounded to the nearest 10 lbs. Payload = GVWR—curb wt.

(b) Maximum trailer weights are rounded to the nearest 50 lbs. Maximum Trailer Weight = GCWR - curb wt. - 150 lbs. (allowance for driver).

(c) 4.7L V-8 Gas FFV 45-State Emission Fleet Only.

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

RAM QUAD CAB 4WD SHORT BED SLT

Tire Type	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.55	6700	1480	5216	3034	2182	3900	3900	9500	4150
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.92	6700	1480	5216	3034	2182	3900	3900	10,500	5150
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6700	1430	5273	3078	2195	3900	3900	11,500	6100
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1430	5273	3078	2195	3900	3900	12,500	7100
20"	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.92	6700	1390	5314	3071	2243	3900	3900	9500	4050
20"	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1330	5371	3115	2256	3900	3900	11,500	6000
LT 275	4.7L V-8 gas OHC	M6	Getrag 6-spd. MANU (DEJ)	3.92	6700	1410	5287	3077	2210	3900	3900	10,500	5050
LT 275	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1360	5344	3121	2223	3900	3900	12,500	7000
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6700	1390	5312	3088	2224	3900	3900	11,500	6050
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1390	5312	3088	2224	3900	3900	12,500	7050
20"	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1290	5409	3124	2285	3900	3900	11,500	5950
LT 275	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1320	5383	3131	2252	3900	3900	12,500	6950
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6700	1350	5353	3120	2233	3900	3900	13,000	7500
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1350	5353	3120	2233	3900	3900	14,000	8500
20"	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1250	5451	3157	2294	3900	3900	13,000	7400
LT 275	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1280	5424	3163	2261	3900	3900	14,000	8450

(a) Payload is rounded to the nearest 10 lbs. Payload = GVWR—curb wt.

(b) Maximum trailer weights are rounded to the nearest 50 lbs. Maximum Trailer Weight = GCWR - curb wt. - 150 lbs. (allowance for driver).

(c) 4.7L V-8 Gas FFV 45-State Emission Fleet Only.

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

RAM QUAD CAB 4WD SHORT BED LARAMIE

Tire Type	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6700	1310	5386	3138	2248	3900	3900	11,500	5950
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1310	5386	3138	2248	3900	3900	12,500	6950
20"	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1310	5393	3140	2253	3900	3900	11,500	5950
LT 275	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1240	5457	3180	2277	3900	3900	12,500	6900
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6700	1390	5312	3088	2224	3900	3900	11,500	6050
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1390	5312	3088	2224	3900	3900	12,500	7050
20"	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1290	5409	3124	2285	3900	3900	11,500	5950
LT 275	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1320	5383	3131	2252	3900	3900	12,500	6950
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6700	1210	5486	3198	2288	3900	3900	13,000	7350
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1210	5486	3198	2288	3900	3900	14,000	8350
20"	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1210	5493	3201	2292	3900	3900	13,000	7350
LT 275	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6700	1140	5557	3241	2316	3900	3900	14,000	8300

(a) Payload is rounded to the nearest 10 lbs. Payload = GVWR—curb wt.

(b) Maximum trailer weights are rounded to the nearest 50 lbs. Maximum Trailer Weight = GCWR - curb wt. - 150 lbs. (allowance for driver).

(c) 4.7L V-8 Gas FFV 45-State Emission Fleet Only.

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

RAM QUAD CAB 4WD LONG BED ST													
Tire Type	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.92	6800	1400	5404	3167	2237	3900	3900	10,500	4950
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6800	1340	5461	3213	2248	3900	3900	12,500	6900
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6800	1300	5500	3221	2279	3900	3900	12,500	6850
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6800	1220	5578	3293	2286	3900	3900	14,000	8250

RAM QUAD CAB 4WD LONG BED SLT

Tire Type	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.92	6800	1410	5393	3159	2234	3900	3900	10,500	4950
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6800	1350	5450	3205	2245	3900	3900	12,500	6900
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6800	1310	5489	3213	2276	3900	3900	12,500	6850
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6800	1230	5568	3285	2282	3900	3900	14,000	8300

RAM QUAD CAB 4WD LONG BED LARAMIE

Tire Type	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6800	1240	5562	3263	2299	3900	3900	12,500	6800
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6800	1140	5662	3323	2339	3900	3900	14,000	8200

(a) Payload is rounded to the nearest 10 lbs. Payload = GVWR—curb wt.

(b) Maximum trailer weights are rounded to the nearest 50 lbs. Maximum Trailer Weight = GCWR - curb wt. - 150 lbs. (allowance for driver).

(c) 4.7L V-8 Gas FFV 45-State Emission Fleet Only.

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

RAM REG CAB 4WD SHORT BED ST

Tire Type	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.55	6350	1450	4899	2861	2039	3900	3900	9500	4450
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.92	6350	1450	4899	2861	2039	3900	3900	10,500	5450
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6350	1390	4956	2902	2054	3900	3900	11,500	6400
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6350	1390	4956	2902	2054	3900	3900	12,500	7400
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6350	1360	4995	2914	2081	3900	3900	11,500	6350
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6350	1360	4995	2914	2081	3900	3900	12,500	7350
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6350	1280	5074	2986	2088	3900	3900	13,000	7800
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6350	1280	5074	2986	2088	3900	3900	14,000	8800

(a) Payload is rounded to the nearest 10 lbs. Payload = GVWR—curb wt.

(b) Maximum trailer weights are rounded to the nearest 50 lbs. Maximum Trailer Weight = GCWR - curb wt. - 150 lbs. (allowance for driver).

(c) 4.7L V-8 Gas FFV 45-State Emission Fleet Only.

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

RAM REG CAB 4WD SHORT BED SLT

Tire Type	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.55	6350	1430	4919	2842	2077	3900	3900	9500	4450
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.92	6350	1430	4919	2842	2077	3900	3900	10,500	5450
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6350	1370	4975	2884	2092	3900	3900	11,500	6350
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6350	1370	4975	2884	2092	3900	3900	12,500	7350
20"	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.92	6350	1330	5015	2876	2139	3900	3900	9500	4350
20"	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6350	1280	5072	2918	2154	3900	3900	11,500	6300
LT 275	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.92	6350	1360	4990	2884	2105	3900	3900	10,500	5350
LT 275	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6350	1300	5046	2926	2120	3900	3900	12,500	7300
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6350	1340	5014	2895	2119	3900	3900	11,500	6350
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6350	1340	5014	2895	2119	3900	3900	12,500	7350
20"	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6350	1240	5111	2930	2181	3900	3900	11,500	6250
LT 275	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6350	1170	5182	2972	2209	3900	3900	12,500	7150
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6350	1360	4994	2932	2062	3900	3900	13,000	7850
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6350	1360	4994	2932	2062	3900	3900	14,000	8850
20"	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6350	1260	5091	2967	2124	3900	3900	13,000	7750
LT 275	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6350	1280	5065	2975	2090	3900	3900	14,000	8800

(a) Payload is rounded to the nearest 10 lbs. Payload = GVWR—curb wt.

(b) Maximum trailer weights are rounded to the nearest 50 lbs. Maximum Trailer Weight = GCWR - curb wt. - 150 lbs. (allowance for driver).

(c) 4.7L V-8 Gas FFV 45-State Emission Fleet Only.

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)**RAM REG CAB 4WD SHORT BED LARAMIE**

Tire Type	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6350	1390	4959	2907	2051	3900	3900	11,500	6400
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6350	1390	4959	2907	2051	3900	3900	12,500	7400
20"	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6350	1380	4966	2910	2056	3900	3900	11,500	6400
LT 275	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6350	1320	5030	2950	2080	3900	3900	12,500	7300
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6350	1360	4993	2912	2081	3900	3900	11,500	6350
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6350	1360	4993	2912	2081	3900	3900	12,500	7350
20"	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6350	1350	5001	2914	2086	3900	3900	11,500	6350
LT 275	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6350	1290	5064	2954	2110	3900	3900	12,500	7300
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6350	1290	5059	2968	2091	3900	3900	13,000	7800
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6350	1290	5059	2968	2091	3900	3900	14,000	8800
20"	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6350	1280	5066	2970	2096	3900	3900	13,000	7800
LT 275	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6350	1220	5130	3010	2119	3900	3900	14,000	8700

(a) Payload is rounded to the nearest 10 lbs. Payload = GVWR—curb wt.

(b) Maximum trailer weights are rounded to the nearest 50 lbs. Maximum Trailer Weight = GCWR - curb wt. - 150 lbs. (allowance for driver).

(c) 4.7L V-8 Gas FFV 45-State Emission Fleet Only.

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)**RAM REG CAB 4WD LONG BED ST**

Tire Type	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.55	6600	1520	5078	3020	2058	3900	3900	9500	4250
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.92	6600	1520	5078	3020	2058	3900	3900	10,500	5250
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6600	1470	5134	3064	2071	3900	3900	11,500	6200
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6600	1470	5134	3064	2071	3900	3900	12,500	7200
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6600	1430	5173	3073	2100	3900	3900	11,500	6200
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6600	1430	5173	3073	2100	3900	3900	12,500	7200
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6600	1350	5252	3145	2107	3900	3900	13,000	7600
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6600	1350	5252	3145	2107	3900	3900	14,000	8600

(a) Payload is rounded to the nearest 10 lbs. Payload = GVWR—curb wt.

(b) Maximum trailer weights are rounded to the nearest 50 lbs. Maximum Trailer Weight = GCWR - curb wt. - 150 lbs. (allowance for driver).

(c) 4.7L V-8 Gas FFV 45-State Emission Fleet Only.

ESTIMATED TRAILER TOWING CAPACITIES (CONTINUED)

RAM REG CAB 4WD LONG BED SLT

Tire Type	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.55	6600	1510	5093	2998	2095	3900	3900	9500	4250
17" base	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.92	6600	1510	5093	2998	2095	3900	3900	10,500	5250
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6600	1450	5150	3042	2108	3900	3900	11,500	6200
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6600	1450	5150	3042	2108	3900	3900	12,500	7200
LT 275	4.7L V-8 gas OHC	M6	Getrag 238 6-spd. MANU (DEJ)	3.92	6600	1440	5164	3041	2124	3900	3900	10,500	5200
LT 275	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6600	1380	5221	3085	2136	3900	3900	12,500	7150
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6600	1410	5189	3052	2137	3900	3900	11,500	6150
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6600	1410	5189	3052	2137	3900	3900	12,500	7150
LT 275	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6600	1340	5260	3094	2166	3900	3900	12,500	7100
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6600	1380	5216	3080	2135	3900	3900	13,000	7650
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6600	1380	5216	3080	2135	3900	3900	14,000	8650
LT 275	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6600	1310	5287	3123	2164	3900	3900	14,000	8550

(a) Payload is rounded to the nearest 10 lbs. Payload = GVWR—curb wt.

(b) Maximum trailer weights are rounded to the nearest 50 lbs. Maximum Trailer Weight = GCWR - curb wt. - 150 lbs. (allowance for driver).

(c) 4.7L V-8 Gas FFV 45-State Emission Fleet Only.

RAM REG CAB 4WD LONG BED LARAMIE

RAM REG CAB 4WD LONG BED LARAMIE													
Tire Type	Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trailer Wt.
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6600	1440	5155	3010	2145	3900	3900	11,500	6200
17" base	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6600	1440	5155	3010	2145	3900	3900	12,500	7200
LT 275	4.7L V-8 gas OHC	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6600	1370	5226	3052	2174	3900	3900	12,500	7100
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6600	1410	5190	3014	2175	3900	3900	11,500	6150
17" base	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6600	1410	5190	3014	2175	3900	3900	12,500	7150
LT 275	4.7L V-8 gas FFV(c)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6600	1340	5261	3057	2204	3900	3900	12,500	7100
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.55	6600	1340	5255	3070	2185	3900	3900	13,000	7600
17" base	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6600	1340	5255	3070	2185	3900	3900	14,000	8600
LT 275	5.7L V-8 gas	A5	545RFE 5-spd. AUTO (DGQ)	3.92	6600	1270	5326	3113	2213	3900	3900	14,000	8500

(a) Payload is rounded to the nearest 10 lbs. Payload = GVWR—curb wt.

(b) Maximum trailer weights are rounded to the nearest 50 lbs. Maximum Trailer Weight = GCWR - curb wt. - 150 lbs. (allowance for driver).

(c) 4.7L V-8 Gas FFV 45-State Emission Fleet Only.