All dimensions are in inches (millimeters) unless otherwise noted.

GENERAL INFORMATION _____Two-door sport-utility vehicle Body Style Assembly Plant _____ Toledo, Ohio Multipurpose vehicle EPA Vehicle Class _____ WRANGLER 4WD IOB RATINGS Base Curb Max. Max **GAWR** Weight, Tongue Trailer Axle **GVWR GCWR** Front/Rear Weight Weight est.(a) Transmission Engine Ratio (lbs.) (lbs.) (lbs.) (lbs.) (lbs.) (lbs.) 2.4L Six-speed manual 3.73 4450 6250 2200/2650 3200 100 1000 4.0L Six-speed manual 3.07 4450 6250 2200/2650 3438 200 2000 3.73 4450 6250 2200/2650 3539 200 2000 4.11 4600 6350 2200/2700 3832 200 2000 Four-speed automatic 3.73(b) 4450 5350 2200/2650 3337 100 1000 200 2000 3.73 (c) 4450 6250 2200/2650 3463 4.11 4600 6350 2200/2700 3857 200 2000 ENGINE: 2.4-LITER, DOHC, 16-VALVE POWER TECH I-4 _ Std.-SE Availability Type and Description ______ Four-cylinder, in-line, liquid-cooled Displacement _______148.2 cu. in. (2429 cu. cm) Bore x Stroke _____ 3.44 x 3.98 (88 x 101) Valve System________Belt-drive, DOHC, 16 valves, stamped-steel followers, hydraulic lash adjustment _____ Sequential, multi-port electronic Fuel Injection _____ Cast-iron block, cast-iron bedplate, aluminum head, balance shafts Construction Compression Ratio _____ 147 hp (110 kW) @ 5200 rpm Power (SAE net) _____ Torque (SAE net) 165 lb.-ft. (224 N•m) @ 4000 rpm Max. Engine Speed______6240 rpm, electronically limited Fuel Requirement ______Regular unleaded, 87 octane (R+M)/2 Coolant Capacity _____ _____ 10.1 gt. (9.6L) Emission Controls ______Catalytic converters, oxygen sensors, on-board vapor recovery system, leak detection pump system(d) ______1,000 lbs. (454 kg) Max. Gross Trailer Weight (lbs.) ____ (a) Curb weight includes standard equipment and full quantities of fuel, lubricant and coolant. (b) SE model. (c) X model. (d) Meets LEV II emission requirements in California, New York, Massachusetts, Maine, and Vermont Meets Tier 2, Bin 5 emission

continued

requirements in other states

ENGINE: 4.0-LITER, OHV, 12-VALVE SMPI POWER	FECH I-6
Availability	StdX, Sport and Rubicon
	In-line, liquid-cooled
Displacement	242 cu. in. (3956 cu. cm)
	3.88 x 3.41 (98.4 x 86.7)
Valve System	OHV, 12 valves, flat followers, hydraulic lifters
	Sequential, multi-port, electronic
	Cast-iron block and head
Compression Ratio	8.8:1
	190 bhp (142 kW) @ 4600 rpm (47.5 bhp/L)
Torque (SAE net)	235 lbft. (319 N•m) @ 3200 rpm
	5300 rpm
Fuel Requirement	Unleaded regular, 87 octane (R+M)/2
Oil Capacity	6.0 qt. (5.7L)
Coolant Capacity	10.5 qt. (9.9L)
Emission ControlsThree-way catalyti	c converters, heated oxygen sensors, internal engine features(a)
Max. Gross Trailer Weight (lbs.)	2,000 lbs. (907 kg)
	16/20-manual, 16/20-automatic
TRANSMISSION: NSG 370—MANUAL, SIX-SPEED	
Availability	StdAll models
Description Six	-speed, overdrive, synchronized in all forward gears and reverse,
	single-rail shift system with top-mounted shift lever
Clutch	Hydraulic actuation, dual mass flywheel system
Gear Ratios	
1st	4.459
2nd	2.614
3rd	1.723
4th	1
5th	0.838
Reverse	4.06
	3.73-2.4L and 4.0L, 4.11-Rubicon
Overall Top Gear	2.98-2.4L and 4.0L; 3.29-Rubicon

⁽a) Meets Federal Tier 2, Bin 9A emission requirements in all 50 states.

Description	Opt.—All model Electronic governor, electronically controlled converter clutcl
Gear Ratios	
1st	2.84
	1.57
	0.69
	2.2
	3.73–2.4L and 4.0L; 3.06– Std. X and Sport; 4.11–Rubicon
	2.57–2.4L and 4.0L; 2.11–Std. X and Sport; 2.84–Rubicon
TRANSFER CASE: NV231 COMMAND-TRAC®	
Гуре	Part-time
	2WD High; 4WD High; Neutral; 4WD Lov
Low Range Ratio	2.72:
Center Differential Type	None
TRANSFER CASE: NV241 ROCK-TRAC™	
	Part-time, heavy-duty
	2WD High; 4WD High; Neutral; 4WD Lov
	4.0:
Center Differential Type	None
Electrical System	
	136-amp with 2.4L engine; 117-amp with 4.0L engine
Battery	Group 34, 600 CCA
DIMENSIONS AND CAPACITIES(a)	
Wheelbase	93.4 (2373
Track, Front	
15 x 7 wheel	57.8
15 x 8 wheel	58.5
16 x 8 wheel	59.!
Track, Rear	
15 x 7 wheel	58.3
15 x 8 wheel	58.5
16 x 8 wheel	57.1
Overall Length	
To spare tire	154.9 (3947
To bumper	150.2 (3813
Overall Width	68.3 (1693
Overall Height	·
Hard top	69.8 (1764
	71.2 (1802
· · · · · · · · · · · · · · · · · · ·	68.4 (1737
Ground Clearance	
Front axle	8.7 (226) min., 9.2 (228) max
	8.6 (208) min., 9.1 (217) max

Approach Angle	
	220
· -	31.(
Curb weight	3,200 lbs. (1467 kg)—SE
	3,438 lbs. (1545 kg)—X
	3,539 lbs. (1565 kg)—Sport
Mariana Dada di Galada a anna ata and anna)	3,832 lbs. (1686 kg)–Rubicor
	800 lbs. (363 kg
Weight Distribution, F/R	•
	50/50–X, Sport and Rubicon
	27.8 sq. ft. (2.58 sq. m
Hard top	0.5
	0.58
	0.55 hard top, 0.58 soft top
	19 gal. (72L
Cargo Volume	
	11.6 cu. ft. (252L
	11.9 cu. ft. (258L
	24.2 cu. ft. (1175L
	25.4 cu. ft. (1209L
	45.8 cu. ft. (1303L
Rear seat removed, soft top	47.1 cu. ft. (1337L
ACCOMMODATIONS(b)	
` ,	2/2
Front	
	41.3 (1038) hard top; 42.5 (1064) soft top
	40.9 (1044
	50.8 (1289
	51.8 (1292
	8.27 (210
	44.5
	50.0 cu. ft. (1.4 cu. m) hard top, 51.4 cu. ft. (1.5 cu. m) soft top
Rear	00.0 0d. 12. (1.1 0d. 11) hard top; 01.1 0d. 12. (1.0 0d. 11) 0012 top
	39.5 (1004) hard top; 39.7 (1031) soft top
	35.3 (890
	57.3 (1455
	42.7 (1105
	42.4 cu. ft. (1.2 cu. m) hard top and soft top
one voiding(s)	
BODY AND CHASSIS	
_ayout	
Construction	Ladder-type frame, open steel body
a) All dimensions measured with two passengers	
a) All dimensions measured with two passengers.	
(b) All dimensions measured at curb weight.	
(c) Without footwell.	

low-pressure gas-charged shock absorbers—std.; Monotube high-pressure gas-charged shock absorbers—std.; Monotube high-pressure gas-charged shock absorbers—std. Notube high-pressure gas-charged shock absorbers—std. Notuber gas-charged shock absorbers—std. N	SUSPENSION	
Monotube high-pressure gas-charged shock absorbers—std. Rubicon; opt. Live axle, trailing arms, track bar, coil springs, stabilizer bar, low-pressure gas-charged shock absorbers—std.; Monotube high-pressure gas-charged shock obsorbers—std. Rubicon; opt. STEERING Type	Front	
Rear Live axle, trailing arms, track bar, coil springs, stabilizer bar, low-pressure gas-charged shock absorbers-std.; Monotube high-pressure gas-charged shock absorbers-std.; Monotube high-pressure gas-charged shock absorbers-std. Rubicon; opt. STEERING Type Power recirculating ball with damper Overall Ratio 16.8:1 overall (gear-15.2:1) 12.11 2.11 2.11 2.11 2.11 2.11 2.11 2		
low-pressure gas-charged shock absorbers—std.;		Monotube high-pressure gas-charged shock absorbers—std. Rubicon; opt.
Monotube high-pressure gas-charged shock absorbers—std. Rubicon; opt. STEERING Type	Rear	Live axle, trailing arms, track bar, coil springs, stabilizer bar,
Power recirculating ball with damper Power Ratio		low-pressure gas-charged shock absorbers-std.;
Power recirculating ball with damper Dowerl Ratio		Monotube high-pressure gas-charged shock absorbers—std. Rubicon; opt.
Power recirculating ball with damper Dowerl Ratio	STEERING	
Overall Ratio 16.8:1 overall (gear-15.2:1) Turning Diameter (curb-to-curb) 36.7 ft. (11.2 m)-30 x 9.5 tire Steering Turns (lock-to-lock) 3.4 TTRES(a) Standard-SE and X Size and type P215/75R15 on/off road Mfr. and model Mer, and model Goodyear Wrangler RT/S Revs per mile 755 (469) Optional-Sport Size and type Size and type 30 x 9.5 x R15 LT on/off road Mfr. and model Mers per mile Goodyear Wrangler GS-A Size and type P225/75R15 on/off road Mfr. and model Mers per mile Goodyear Wrangler GS-A Standard-Rubicon 31 x 9.5 LT245/75R16 on/off road Mfr. and model Size and type 31 x 9.5 LT245/75R16 on/off road Mfr. and model Mey per mile Goodyear Wrangler MT/R Revs per mile Goodyear Wrangler MT/R Standard-SE, X and Sport Type and material Full-face steel Size Standard-SE, X and Sport; (SE, Sport not available with 15x7 Cast Alum Ecco wheels only X) Type and material Cast-aluminum Size Type and material Cast-aluminum Size 15 x 8 Standard-Rubicon <td< td=""><td></td><td>Power recirculating ball with damper</td></td<>		Power recirculating ball with damper
Turning Diameter (curb-to-curb)		
Steering Turns (lock-to-lock)	Turning Diameter (curb-to-curb)	36 7 ft (11 2 m)=30 x 9.5 tire
Size and type		
Size and type	TIRFS(a)	
Size and type	` '	
Mfr. and model		P215 /75P15 on /off road
Revs per mile	,	•
Optional—Sport 30 x 9.5 x R15 LT on/off road Mfr. and model		
Size and type	•	
Mfr. and model		20 v 0.5 v D45 LT /-ff
Revs per mile		
Standard—Sport; Optional—X Size and type		
Size and type		
Mfr. and model		
Revs per mile		
Standard—Rubicon Size and type		
Size and type		733 (455)
Mfr. and model		
Revs per mile		
WHEELS(a) Standard—SE, X and Sport Type and material		
Standard—SE, X and Sport Full-face steel Size	Revs per mile	677 (420)
Type and material	WHEELS(a)	
Size	Standard—SE, X and Sport	
Optional—SE, X and Sport; (SE, Sport not available with 15x7 Cast Alum Ecco wheels only X) Type and material Cast-aluminum Size Cast-aluminum Size 15 x 8 Standard—Rubicon Type and material Cast-aluminum Size Cast-aluminum Size 16 x 8	Type and material	Full-face steel
Type and material Cast-aluminum Size 15 x 7 Optional—Sport Type and material Cast-aluminum Size 15 x 8 Standard—Rubicon Type and material Cast-aluminum Size 16 x 8	Size	15 x 7
Size	Optional-SE, X and Sport; (SE, Sport	
Size	Type and material	Cast-aluminum
Type and material Cast-aluminum Size 15 x 8 Standard—Rubicon Type and material Cast-aluminum Size 16 x 8		
Type and material Cast-aluminum Size 15 x 8 Standard—Rubicon Type and material Cast-aluminum Size 16 x 8	Optional—Sport	
Size	•	Cast-aluminum Cast-aluminum
Standard—Rubicon Type and material Cast-aluminum Size 16 x 8		
Type and material Cast-aluminum Size 16 x 8	Standard—Rubicon	
Size16 x 8		Cast-aluminum
	(a) San alan Tiran under Fastura Austlahilit	

Standard—SE, X and Sport	
Front	
Size and type	11.0 x 0.94 (280 x 24) vented disc with single-piston sliding caliper
Swept area	198.5 sq. in. (1281 sq. cm)
Rear	
Size and type	9.0 x 2.5 (229 x 64) drum
Swept area	141.4 sq. in. (912 sq. cm)
Power Assist Type	8.07 (205) tandem diaphragm vacuum
Standard-Rubicon, Optional Sport	
Front	
Size and type	11.0 x 0.94 (280 x 24) vented disc with single-piston sliding caliper
Swept area	198.5 sq. in. (1281 sq. cm)
Rear	
Size and type	11.2 x 0.47 (285 x 12) solid disc with single-piston sliding caliper
Swept area	96.8 sq. in. (625 sq. cm)
Power Assist Type	8.07 (205) tandem diaphragm vacuum
Optional—Sport	
Front	
Size and type	$_{ extstyle 2}$ 11.0 x 0.94 (280 x 24) vented disc with single-piston sliding caliper with ABS
Swept area	198.5 sq. in. (1281 sq. cm)
Rear	
Size and type	9.0 x 2.5 (229 x 64) drum with ABS
Swept area	141.4 sq. in. (912 sq. cm)
	8.07 (205) tandem diaphragm vacuum

(a) See also Wheels under Feature Availability.

All dimensions are in inches (millimeters) unless otherwise noted.

ENGINE: 4.0-LITER, OHV, 12-VALVE SMPI PO	WER TECH I-6
Type and Description	
Displacement	242 cu. in. (3956 cu. cm)
	3.88 x 3.41 (98.4 x 86.7)
Valve System	OHV, 12 valves, flat followers, hydraulic lifters
	Sequential, multi-port, electronic
	Cast-iron block and head
Compression Ratio	8.8:1
	190 bhp (142 kW) @ 4600 rpm (47.5 bhp/L)
Torque (SAE net)	235 lbft. (319 N•m) @ 3200 rpm
Max. Engine Speed	5300 rpm
	Unleaded regular, 87 octane (R+M)/2
Oil Capacity	6.0 qt. (5.7L)
Coolant Capacity	10.5 qt. (9.9L)
Emission Controls	Three-way catalytic converters, heated
	oxygen sensors, internal engine features
Max. Gross Trailer Weight	3,500 lbs.
Estimated EPA Fuel Economy mpg (City/Hwy)	16/20-automatic, 16/20-manual
Gear Ratios 1st	
2nd	1.57
	1
	0.69
	3.73
Overall Top Gear	2.57
TRANSMISSION: NSG 370 — MANUAL, SIX-SI	PEED
Availability	StdAll models
Description	Six-speed, overdrive, synchronized in all forward gears and reverse,
	single-rail shift system with top-mounted shift lever
Clutch	Hydraulic actuation, dual mass flywheel system
Gear Ratios	
1st	4.459
	2.614
3rd	1.723
	1
5th	0.838
Reverse	
Axle Ratio	3.73-4.0L, 4.11-Rubicon
Overall Top Gear	2.98-4.0L; 3.29-Rubicon

Type	Part-time
Operating Modes	
Law Panas Patia	Neutral; 4WD Low, part-time
Low Range Ratio	
Center Differential Type	None
DIMENSIONS AND CAPACITIES	
Wheelbase	103.4 (2626)
Track, Front	58.5 (1473)
Track, Rear	58.5 (1473)
Overall Length	
To spare tire	, ,
To bumper	
Overall Width	66.7 (1693)/76.3 (1938)
Overall Height	
Hard top	
Soft top	,
Top down	68.4 (1737)
Ground Clearance	
Front axle	· · ·
Rear axle	
Running	
Approach Angle	
Ramp Breakover Angle	
Departure Angle	
•	3,721 lbs. (1689 kg)
Maximum Payload (includes occupants and cargo)	
Weight Distribution, F/RFrontal Area	
Hard top	
Soft top	
Drag Coefficient	
Fuel Tank Capacity	
Total Interior Volume	
Front Interior Volume	
Rear Interior Volume	
	28.5 cu. ft. (0.807 cu. m)
Enclosed Cargo Volume Index—Maximum behind front seat	63.3 cu. ft. (1.792 cu. m)
Enclosed Cargo Volume Index—Maximum behind second seat	

ACCOMMODATIONS	
Seating Capacity-F/R	2/2 std.
Front	
Head room	40.9 (1038) hard top; 41.9 (1064) soft top
Leg room	41.1 (1044)
	50.8 (1289)
	51.8 (1292)
Seat travel	8.27 (210)
	44.5°
Rear	
Head room	41.1 (1044) hard top; 40.6 (1031) soft top
Leg room	36.7 (890)
	57.3 (1455)
	43.5 (1105)
BODY AND CHASSIS	
Layout	Longitudinal front engine, four-wheel drive
	Ladder-type frame, open steel body
SUSPENSION	
Front	Live axle, leading arms, track bar, coil springs,
	stabilizer bar, low-pressure gas-charged shock absorbers
Rear	Live axle, trailing arms, track bar, coil springs,
	stabilizer bar, low-pressure gas-charged shock absorbers
STEERING	
Type	Power recirculating ball with damper
Overall Ratio	16.8:1 overall (gear–15.2:1)
	36 ft. (11.2 m)
Steering Turns (lock-to-lock)	3.4
TIRES	
Standard-Unlimited	
Size and type	30 x 9.5R15LT
Mfr. and model	Goodyear Wrangler GSA
Revs per mile	719
Unlimited Rubicon	
Size and type	31 x 9.5 LT245/75R16 on/off road
Mfr. and model	Goodyear Wrangler MT/R
	677 (420)
WHEELS	
Standard-Unlimited	
Type and material	Cast-aluminum
Size	
Unlimited Rubicon	
Type and material	Cast-aluminum
Size	16 x 8

	SE	Х	Sport	Rubicon
EXTERIOR				
Bodyside Steps (Black)		-	0	-
Bumpers—Front and rear with end caps and front bumper guards (Black)	S	S	S	S
Colors				
Flame Red, Electric Lime Green Pearl Coat, Bright Silver Metallic,				
Impact Orange, Stone White	0	0	0	0
Patriot Blue Pearl Coat, Beryl Green, Light Khaki Metallic, Black	0	0	0	0
Doors				
Full, steel with roll-up windows (not available on A Package)	0	0	S	S
Half, steel with soft windows	S	S	0	0
Fender Flares				
Medium Gray or Dark Khaki		S	S	_
Neutral Gray Metallic		-	_	S
Fog Lamps		_	S	S
Frame Overlay, Front: Black with Jeep _® logo	S	S	S	S
Fuel Cap, locking	0	0	0	0
Glass				
Windshield, tinted	S	S	S	S
Rear quarter and back light windows, deep tinted sunscreen				
(paired with Hard Top)	_	0	S	S
Rear quarter and liftgate windows, tinted	s	S	_	_
Grille (body color)	_	S	S	S
Headlamp Bezels (chrome-plated)		S	S	S
Mirrors-Dual, swing-away (Black)		S	S	S
Sill Guards, diamond plate		_	_	S
Tire Cover, Spare				
Black vinyl (not available with 30-inch Tire and Wheel Group)	_	_	0	_
Top Colors—Medium Gray or Dark Khaki		0	0	0
Tops		_	-	
Soft, easy folding with soft windows	S	S	S	S
Hard (includes full steel doors with roll-up windows, rear-window wiper and	`	Ü	Ü	Ü
washer and rear-window defroster)	_	0	0	0
Wipers and Washers, Windshield—Two-speed with variable-delay intermittent	s	S	S	S
The country will will be a second with variable delay intermittent	•	Ü	O	O
INTERIOR				
Add-a-Trunk—Lockable storage		_	0	0
Assist Handle–Passenger		S	S	S
Power outlet, auxiliary 12-volt	S	S	S	S
Carpeting (color-keyed)				
Front floor	S	S	S	S
Rear footwell, rear wheelhouse and cargo floor	S	S	S	S
Cargo Tie Down Loops (four)	S	S	S	S
Climate Control				
Air conditioning	0	0	S	S
Heater with instrument panel ventilation	S	S	_	_

Legend: S = Standard O = Optional P = Available within package or group noted in parentheses O/P = Item is a freestanding option and also included in a package or group <math>-= Not available

NOTE: The information shown is preliminary and based on data available at the time of publication.

	SE	Χ	Sport	Rubicon
INTERIOR (CONTINUED)				
Console—Floor				
Mini with dual cup holders	_ S	_	_	_
Full length with four cup holders		S	S	S
Defroster—Rear window, electric (available only with hard top)		Р	Р	Р
Door trim panels molded with map pockets and pull handles (color-keyed)		S	S	S
Floor mats—Carpeted, front (color-keyed)		0	0	0
Glove compartment—Locking		S	S	S
Instrument Cluster	_			
Gauges—speedometer, tachometer, odometer, trip odometer, temperature,				
fuel level, oil pressure, voltmeter	S	S	S	S
Mirrors	_			
Manual day/night rearview	S	S	S	S
Electrochromic with reading lamps, compass and temperature display		_	P	P
Radios	_			•
AM/FM stereo with CD	S	S	S	S
Four speakers	_	S	_	_
Seven speakers including amplified subwoofer in console (included in Premium	_ 3	3		
Audio Group)	_	Р	S	S
Six-disc in-dash CD changer (included in Premium Audio Group)		P	0	0
		0	U	U
Premium Audio GroupSeat Fabric		U	_	_
	C			
Vinyl		_	_	S S
Cloth	_ 0	S	S	5
Seats, Front	0	0	0	0
High-back reclining bucket		S	S	S
Driver and passenger tip-and-slide	_ S	S	S	S
Seats, Rear				
Fold-and-tumble bench (includes three-point rear seat belts and rear footwell,			_	•
rear wheelhouse and cargo floor carpet)		S	S	S
Speed control—(includes leather-wrapped steering wheel)		0	0	0
Sport bar padding-Full	_ S	S	S	S
Steering column–Low-pivot tilt	_ S	S	S	S
Steering wheel				
Soft-feel, four-spoke		S	_	_
Leather-wrapped, four-spoke, with speed control		Р	Р	0
Sun visors—Fold and swing (color-keyed)	_ S	S	S	S
POWERTRAIN AND CHASSIS				
2.4-liter Power Tech, DOHC, 16-valve SMPI I-4 engine and six-speed NSG 370				
manual transmission	S	_	_	_
4.0-liter Power Tech, OHV, 12-valve SMPI I-6 engine and six-speed NSG 370	_ 3	_	_	_
manual transmission		S	S	S
4.0-liter Power Tech, OHV, 12-valve SMPI I-6 engine and four-speed		3	3	3
	0	0	0	0
automatic transmission	_ 0	0	0	0
Brakes	c	C	C	
Power front disc/rear drum	_ S	S	S	_

	SE	Χ	Sport	Rubicon
POWERTRAIN AND CHASSIS (CONTINUED)				
Brakes (continued)				
Four-wheel disc (included with Brake and Traction Group)		_	Р	S
Four-wheel anti-lock		_	0	_
Differential				
Trac-Lok®(a)		0	Р	_
Tru-Lok™		_	_	S
Engine block heater	0	0	0	0
Front axle				
Dana 30		S	S	_
Dana 44-3, heavy-duty		_	_	S
Rear Axle				
Dana 35	S	S	S	_
Dana 44, heavy-duty (packaged with 30-inch tires)		_	Р	S
3.73 axle ratio (with automatic transmission)		O/P	O/P	_
4.11 axle ratio		_	_	S
Skid plates—Fuel tank and transfer case	S	S	S	S
Steering-Power	S	S	S	S
Shock absorbers				
Gas-charged		S	S	_
Digressive (in 30-inch Tire and Wheel Group)		_	Р	S
Tire—Spare, outside-mounted				
Full-size with matching wheel	S	S	S	S
Tires(b)				
P215/75R15 Goodyear Wrangler RT/S raised black letter all-terrain tires	S	S	_	_
P225/75R15 Goodyear Wrangler GS-A outline white letter all-terrain tires		O/P	S	_
30 x 9.5 R15 LT Goodyear Wrangler outline white letter all-terrain tires				
(packaged with Dana 44 rear axle)		_	Р	_
LT245/75R16 MTR Goodyear black sidewall on/off road tires		_	_	S
Tow hooks-Two, front; one, rear	0	0	S	S
Transfer case				
Command-Trac® part-time 4WD	S	S	S	_
Rock-Trac™ heavy-duty part-time four-wheel drive		_	_	S
Wheels				
Full-face steel 15" x 7" wheels	S	S	S	_
Ravine 15" x 8" aluminum wheels		_	Р	_
Moab 16" x 8" cast-aluminum wheels		_	_	S
SAFETY AND SECURITY				
Restraint systems				
Air bags(c), Next-generation driver and front passenger air bag				
	S	S	S	S
and knee blockers	s	S	S	S
(a) Trac-Lok® is a registered trademark of Spicer Technology Inc.	•	J	J	Ü
(b) Other tire sizes and brands may also be used.				
(c) Certified to federal regulations that allow less forceful air bags. Always use seat belts.				
Described to redefine regulations that allow less forceful all bags. Always use seat belts.				

continued

Remember, a back seat is the safest place for children.

	SE	Χ	Sport	Rubicon
SAFETY AND SECURITY (CONTINUED)				
Restraint systems (continued)				
Child Seat Anchor System—LATCH (Lower Anchors and Tethers for CHildren)	S	S	S	S
Seat belts				
Driver's side constant force retractors	S	S	S	S
Front—Three-point belts with adjustable turning loops				
and traveling inboard buckles	S	S	S	S
Rear-Three-point belts	S	S	S	S
Sentry Key® theft-deterrent system	. –	_	Р	Р
Brake-shift and park ignition interlocks	S	S	S	S
Warning chime—Key-in-ignition, headlamps-on, seat belt, check gauges	S	S	S	S
EQUIPMENT GROUPS				
Brake and Traction Group—Four-wheel disc brakes and Trac-Lok®(a)				
(must have 30-inch Tire and Wheel Group when ordered with Sport)				
(Tru-Lok replaces Trac-Lok on Rubicon)	_	_	0	S
Convenience Group—Passenger-side footwell courtesy lamps, underhood lamp,	-		O	Ü
full console with lockable storage, four cup holders, coin holder				
and storage tray	_	S	S	S
Security Group—Sentry Key® Theft-deterrent System and	-	Ü	O	Ü
auto-dimming rearview mirror	_	_	0	0
Smoker's Group—Removable ash tray and cigar lighter		0	0	0
Dual Top Group—Hard top and soft top in matching colors		_	0	0
Tire and Wheel Group, (Ravine) 30-inch—30 x 9.5R15 LT Goodyear Wrangler	-		Ü	Ü
GS-A all-terrain tires, Dana 44 heavy-duty rear axle, digressive shock absorbers,				
15" x 8" Ravine aluminum wheels (3.73 axle ratio only; includes matching				
spare tire and wheel)	_	_	0	_
Premium Audio Group—Six-disc in-dash CD changer and seven speakers	•	_	O	_
(includes amplified subwoofer in console)	_	0	_	_
(morados ampinios submosisi in concord)		J		

⁽a) Trac-Lok $^{\! \otimes}$ is a registered trademark of Spicer Technology Inc.

	Unlimited Base	I Unlimited Premium	Rubicon Unlimited
EXTERIOR	Duoc	11011114111	Omminicou
Bodyside steps (Black)	0	0	_
Bumpers—Front and rear with end caps and front bumper guards (Black)	_ s	S	S
Colors			
Flame Red, Electric Lime Green Pearl Coat, Impact Orange, Light Khaki Pearl Coat,			
Stone White	_ 0	_	0
Patriot Blue Pearl Coat, Deep Beryl Green Pearl Coat, Bright Silver Metallic, Black	0	0	0
Doors	_		
Full, steel with roll-up windows	_ S	S	S
Fender flares			
Medium Gray or Dark Khaki	_ S	_	_
Body color		S	_
Neutral Gray Metallic		_	S
Fog lamps		S	S
Frame overlay, Front–Black with Jeep logo	_ S	S	S
Fuel cap, locking	_ 0	0	0
Glass			
Windshield, tinted	_ S	S	S
Rear quarter and backlight windows, deep tinted sunscreen	_ S	S	S
Grille			
Body color	_ S	_	S
Bright		S	_
Headlamp bezels (chrome-plated)	_ S	S	S
Mirrors-Dual, swing-away (Black)	_ S	S	S
Sill guards, diamond plate		_	S
Top colors			
Medium Gray	_ 0	0	0
Dark Khaki	_ 0	_	0
Tops			
Sunrider soft top with sun roof feature	_ S	S	S
Hard (includes full steel doors with roll-up windows, rear-window wiper and			
washer and rear-window defroster)	_ 0	0	0
Tow hooks	_ S	S	S
Wipers and washers, windshield—Two-speed with variable-delay intermittent	_	S	S

Legend: S = Standard O = Optional P = Available within package or group noted in parentheses O/P = Item is a freestanding option and also included in a package or group — = Not available

NOTE: The information shown is preliminary and based on data available at the time of publication.

	Unlimited Unlimited Rubi Base Premium Unlim		
INTERIOR	Базе	TTEIIIIIIII	Omminiceu
Assist handle–Passenger	S	S	S
Power outlet, Auxiliary 12-volt	_	S	S
Carpeting (color-keyed)	_	ŭ	· ·
Front floor	S	S	S
Rear footwell, rear wheelhouse and cargo floor		S	S
Cargo tie down Loops (four)		S	S
Climate control	_		-
Air conditioning	S	S	S
Console-Floor			
Full length with four cup holders	S	S	S
Defroster—Rear window, electric (available only with hard top)		Р	Р
Door trim panels molded with map pockets and pull handles (color-keyed)		S	S
Floor mats—Carpeted, front (color-keyed)		Р	0
Glove compartment-Locking		S	S
Instrument cluster			
Gauges—speedometer, tachometer, odometer, trip odometer, temperature, fuel level,			
oil pressure, voltmeter	S	S	S
Instrument panel bezel—Silver paint treatment		S	_
Mirrors	_		
Manual day/night rearview	S	_	S
Electrochromic with reading lamps, compass and temperature display (included in	_		
Security Group)	_ P	S	Р
Radios			
AM/FM stereo with CD	_ S	S	S
Seven speakers including amplified subwoofer in console; (included in Premium			
Audio Group)	_ P	S	S
Six-disc in-dash CD changer (included in Premium Audio Group)	_ 0	0	0
Seat fabric			
Cloth	_ S	_	S
Premium cloth		S	_
Seats, Front			
High-back reclining bucket	_	S	S
Driver and passenger tip and slide	_ S	S	S
Seats, Rear			
Fold-and-tumble bench (includes three-point rear seat belts and rear footwell, rear			
wheelhouse and cargo floor carpet		S	S
Speed control—(included with leather-wrapped steering wheel)	_ 0	Р	0
Sport bar padding–Full	_	S	S
Steering column–Low-pivot tilt	_ S	S	S
Steering wheel			
Leather-wrapped, four-spoke, includes speed control		Р	Р
Sun visors—Fold and swing (color-keyed)	_ S	S	S

	Unlimited Base	d Unlimited Premium	Rubicon Unlimited
POWERTRAIN AND CHASSIS			
4.0-liter Power Tech, OHV, 12-valve SMPI I-6 engine and six-speed manual transmission	_ S	S	S
4.0-liter Power Tech, OHV, 12-valve SMPI I-6 engine			
and four-speed automatic transmission	_ 0	0	0
Brakes			
Four-wheel disc	_ S	S	S
Differential			
Trac-Lok(a)	_ S	S	_
Tru-Lok TM		_	S
Engine block heater		0	0
3.73 axle ratio	S	S	_
4.11 axle ratio		_	S
Front axle			
Dana 30	_ S	S	_
Dana 44-3, heavy-duty		_	S
Rear axle			
Dana 44, heavy-duty	S	S	S
Skid plates—Fuel tank and transfer case	S	S	S
Steering-Power		S	S
Shock absorbers			
Digressive valve gas-charged	_ S	S	S
Tire—Spare, outside-mounted			
Full-size with matching wheel	_ S	S	S
Tires(b)			
30 x 9.5R15 LT Goodyear Wrangler outline white letter all-terrain tires	_ S	S	_
LT245/75R16 MTR Goodyear black sidewall on/off road tires		_	S
Tow hooks—Two, front; one, rear		S	S
Transfer case			
Command-Trac® part-time four-wheel drive	S	S	_
Rock-Trac™ heavy-duty part-time four-wheel drive	_	_	S
Wheels			
Ravine 15" x 8" aluminum wheels	_ S	S	_
Moab 16" x 8" cast-aluminum wheels		_	S

⁽a) Trac-Lok® is a registered trademark of Spicer Technology, Inc.

⁽b) Other tire sizes and brands may also be used.

	Unlimited Base	Unlimited Premium	Rubicon Unlimited
SAFETY AND SECURITY	Dusc	Tremium	Ommitted
Restraint systems			
Air bags(a), next-generation driver and front passenger air bag and knee blockers	_ S	S	S
Child seat tether anchorages		S	S
Child seat anchor system—LATCH (Lower Anchors and Tethers for CHildren)	_ S	S	S
Seat belts			
Driver's side constant force retractors	_ S	S	S
Front: Three-point belts with adjustable turning loops and traveling inboard buckles		S	S
Rear: Three-point belts	_ S	S	S
Sentry Key® theft-deterrent system (included in Security Group)		S	Р
Brake-Shift and park ignition interlocks	_ S	S	S
Warning chime—Key-in-ignition, headlamps-on, seat belt, check gauges		S	S
EQUIPMENT GROUPS			
Convenience Group-Passenger-side footwell courtesy lamps, underhood lamp, full			
console with lockable storage, four cup holders, coin holder and storage tray	_ S	S	S
Security Group—Sentry Key® theft-deterrent system and auto-dimming rearview mirror	_ 0	Р	0
Smoker's Group-Removable ash tray and cigar lighter	_ 0	0	0
Premium Audio Group—Six-disc in-dash CD changer and seven speakers (includes			
amplified subwoofer in console)	_ 0	_	_

⁽a) Certified to federal regulations that allow less forceful air bags. Always use seat belts. Remember, a back seat is the safest place for children.